

EXTRUDED SOLID BRASS HINGES

BEGINS JULY 1st!



Finishes: 003, 102, 112, 150, 260

HINGE CHART - GENERAL SPECIFICATIONS

Item #	Item No.	Door Thickness	Door Width	Hinge Size	Length of Joint	Width Open	Radius	Thickness	Knuckles	Wood Screw Quantity / Size
1035.xxx.l	1035	1.375"	to 32"	3.5" x 3.5"	3.5" (89mm)	3.5" (89mm)		.125" (3.18mm)	5	6 — No. 10 x 1" Flat Head-Phillips - Undercut
1040.xxx.l	1040	1.375"	over 32"	4" x 4"	4.0" (102mm)	4.0" (102mm)		.130" (3.30mm)	5	8 — No. 12 x 1.25" Flat Head-Phillips - Undercut
1041.xxx.l	1041	1.375"	to 36"	4" x 4"	4.0" (102mm)	4.0" (102mm)		.130" (3.30mm)	5	8 — No. 12 x 1.25" Flat Head-Phillips - Undercut
1135.xxx.l	1135	1.375"	to 32"	3.5" x 3.5"	3.5" (89mm)	3.5" (89mm)	.625"	.093"	5	6 — No. 10 x 1.0" F.H. Phillips

*Always consider clearance between door flush with jamb and casing

- Ships within 7 business days
- Extruded brass hinges machined for precise installation and smooth movement
- Exceptional strength and precision tolerances

CUSTOMER SERVICE TOLL FREE LINE: Monday-Friday 8:00 am to 5 pm EST

800.437.7448 FAX: 800.255.9785

