

# DO NOT PRINT THIS PAGE

## Printing Notes:

**Material:** 20 Pound (US) or 80 GSM (International) bond paper, white

**Ink:** Black

**Printing:** 2-side (front & back), Offset Printing


**Resolution:** 150 DPI or above

**Size:** 4 x 8.5 in (W x H)

*This drawing contains proprietary information and trade secrets of The Coleman Company, Inc.  
Unauthorized use or copying is prohibited.*

METRIC (INCH)							
CRITICAL DIMENSION							
CHECKING IS COMPULSORY							
VOLUME	cm <sup>3</sup>	01	15-FEB-12	NEW		Abby K	20022277
MASS	grams	REV.	DATE	MODIFICATIONS		NAME	ECN NO.
DENSITY	g/cm <sup>3</sup>	MATERIAL: SEE NOTES				<i>The Coleman Company, Inc.</i> Wichita, Kansas USA 67219	
GENERAL TOLERANCES EXCEPT AS NOTED		FINISH: SEE NOTES				COMPOSITE- NO	SHEET 1 OF 1
0 TO	6mm	= ±0.1	SCALE:	DATE:	DRAWN BY:	APPROVED BY:	REVISION
>6 TO	30mm	= ±0.2	1:1	15-FEB-12	Abby K	Steve H	01
>30 TO	80mm	= ±0.3	NAME: INSTRUCTION MANUAL RECHARGEABLE PUMP				
>80 TO	180mm	= ±0.4	ENGLISH				
>180mm		= ±0.5	PART NO.: 4010019276				
ANGULAR		= ± 3°					

## Deflation




1. Remove adapter nozzle from inflation end and attach to deflation side of pump. Repeat same steps as inflation. This will draw the air out quickly.



## How to Use and Enjoy Your Coleman®

# Water Resistant Rechargeable Pump

## Inflating Standard Pinch Valve



- Attach pinch valve adapter to inflation end of pump.
  - Insert pinch valve adapter into pinch valve.
  - **Make sure tip of adapter is extended past inner "Flap" inside of valve.**
- Turn pump on.
- When fully inflated, remove pump from valve and seal valve.

## Other Valves



This pump is compatible with most valves on inflatable products. If you have an inflatable product with a valve other than those described above, rotate the adapter sleeve until nozzle end fits valve.



Please call or write to us at our nearest location with any comments or questions.

The Coleman Company, Inc. • 3600 North Hydraulic • Wichita, Kansas 67219 U.S.A.  
1-800-835-3278 in the United States • [www.coleman.com](http://www.coleman.com)

Sunbeam Corporation (Canada) Limited • DBA Jarden Consumer Solutions  
20B Hereford Street • Brampton, ON L6Y 0M1  
1-800-387-6161 in Canada • [www.coleman.com](http://www.coleman.com)

© 2012 The Coleman Company, Inc. All rights reserved.  
Coleman®, , and  are registered trademarks and  
QuickPump™ and Double Lock™ are trademarks of  
The Coleman Company, Inc.

## Things You Should Know

- Carefully inspect the pump for damage before first use and every use thereafter. Do not use if found damaged.
- Do not change the plug in any way.
- Keep unit out of reach of children.
- Do not expose to rain or sunlight. Household use only.
- This pump is a high-volume, low-pressure pump. It is intended to inflate items requiring low pressure (such as inflatable beds, inflatable rafts, air mattresses, etc.).
- For fast inflation and maximum motor cooling, always use the largest size nozzle possible.
- **Caution** - Risk of fire and electric shock! Do not operate for more than 10 minutes. Allow 20 minutes off between each operation.
- Water resistant for marine environments.
- Pump is water resistant, but cannot be submerged in water.
- Not for use around salt water. Salt water can cause the pump to corrode.

**Note: Pump will not work on stem valves or needle valves commonly used on bike tires, basketballs, etc.**

## Warnings

- Follow the instructions carefully on articles to be inflated, never exceed recommended pressure. Bursting items can cause serious injury.
- Do not open case, electrical hazards may result. There are no user serviceable parts.
- Never look into or point any opening toward your eyes while pump is operating.
- Do not attempt to put any objects into the inflation or deflation port at any time.
- Never leave pump unattended while in use.
- Do not leave pump connected to the power supply when not in use.
- Never twist the cord.
- Never allow sand, paper, debris or small articles to be sucked into pump while operating.
- Let pump cool before storing the pump inside the box after use.

**DO NOT EXCEED 10 MINUTES OF CONTINUOUS OPERATION.  
ALLOW 20 MINUTES OFF BETWEEN EACH OPERATION.**

**CAUTION: Do not block the air portals during operation, this could damage the motor.**


## Operation

- The Coleman rechargeable Pump needs to be charged for 10 HOURS (but no more than 24 hours) before the first use.
- Charge only with the transformer provided with the pump.
- After use, recharge the pump within 48 hours.
- Always store the pump with a full charge. To keep the battery at optimum operating levels recharge the unit every 3-5 months, even if it has not been used.
- Do not leave pump charging for more than 24 hours to avoid damage to the battery.


## About The Battery

This product used a sealed, lead acid, rechargeable battery. The battery pack is recyclable. At the end of the battery pack's useful life, the unit should be recycled or properly disposed of. **Do not discard in a landfill or incinerate.** Contact your city officials for battery disposal information. If a battery collection program does not exist in your area, call Coleman at 1-800-835-3278 in the US or at 1-800-387-6161 in Canada for battery disposal information.

## Inflating Coleman® Double Lock™ Valve




1. To begin inflation, open external cap and pull firmly on the lanyard to extend out. This will open internal yellow seal.




2. Attach adapter nozzle to inflation end of pump. Insert pump and turn on.

**Note:** The pump may look different from yours. It is for illustration purposes only.



3. When fully inflated, seal valve by pushing in with pump nozzle. This will seal the internal yellow stopper and keep air from escaping while closing cap. Gently twist adapter sleeve to right while backing pump out of valve.



4. Fully remove pump and close external cap. Valve should appear depressed into itself.