SPECIFICATION SUBMITTAL

Highlights

- Ceramic Disc Valves
- Easy Grip Wand Produces Strong Spray or Aerated Stream
- Accommodates up to 2-1/4" deck thickness

Code Compliance

Price Pfister products are designed and manufactured in compliance with the following standards and codes:

IAPMO certified

SS-WKP-60-1

- ASME A112.18.1
- CSA B125 certified
- ANSI A117.1 (Lever handles only)

	VKP-600Q	VKP-600S	VKP-600Y
Finishes	F-J	王	F-1
Tuscan Bronze			Х
Stainless Steel		Х	
Fired Copper	Х		


Features	F-WKP-600Q	F-WKP-600S	F-WKP-600Y
Braided Nylon Reinforced Vinyl Hose	Х		Χ
Deckplate with Tie-Downs	Х	Χ	Χ
Quick Connect Installation	Х	Х	Χ
Lever Handle	Х	Х	Χ
Accommodates up to 2-1/4" deck thickness	Х	Х	Χ
1 or 3-Hole Installation; Deck Plate or Single Hole Mounting Option	х	Х	х
Lead Free Compliant	Х	Χ	Х
2.2 gpm (8.33 L/M) Flow Rate	Х	Χ	Χ
ADA Compliant	Х	Χ	Χ
150 Degree Swivel Spout	Х	Χ	Х
Easy Grip Wand Produces Strong Spray or Aerated Stream	х	Х	х
One Touch Pull-Out Spray Activation	Х	Χ	Χ
Step-By-Step Installation Instructions	Х	Χ	Χ
Pforever Warranty®	Χ	Χ	Χ

SKU's beginning in F are certified to NSF 61/9 Annex G Low Lead Requirements

Wilmington™

Pull-Out Kitchen Fauce

Single Handle
1 or 3-Hole Installation
Ceramic Disc Valve



F-WKP-600Q F-WKP-600S F-WKP-600Y

For additional information, please contact your Price Pfister representative, or visit our website at www.pricepfister.com.

Project: _______ 1-800-PFAUCET www.pricepfister.com
19701 DaVinci, Lake Forest, CA 92610
09/28/10

