


DO NOT REMOVE PRIOR TO SALE!

OWNER'S MANUAL

Model No. 1470



I. APPROVAL CONDITIONS and CARRIAGE REQUIREMENTS

Model 1470 is a U.S. Coast Guard approved Type V inflatable PFD **APPROVED ONLY WHEN WORN** for use on uninspected commercial vessels less than 40 feet in length not carrying passengers for hire as a substitute for a Type II PFD when used in accordance with this owners manual. It is also approved for use on recreational boats.

CONDITIONS FOR TYPE V APPROVAL IN COMMERCIAL APPLICATIONS:

1. This PFD must be worn before getting underway and whenever above deck and not within an enclosed space to meet the carriage requirement.
2. The operator of an uninspected commercial vessel is responsible for servicing and maintaining this PFD in good serviceable condition in accordance with this owner's manual. See pages 7-9 for servicing information.
3. The operator of an uninspected commercial vessel is responsible for providing each person onboard with the safety information required for use of this PFD. See pages 3-7 for information.

When fully inflated, it will provide Type II in-water performance. This model will turn most wearers from a face down to a face up position and provide support suitable for offshore conditions. See pages 10 and 11 for rearming instructions.

Inflatables are not approved for water skiing or other high-speed activities. This inflatable was designed to be more comfortable and less restrictive to wear than inherently buoyant PFDs. When worn, used and serviced according to this owner's manual, this PFD can greatly increase your chances of survival in the water. **Not recommended for non-swimmers or weak swimmers.** Users of inflatable PFDs must be at least 16 years old.

INITIAL ARMING INSTRUCTIONS - DEVICE IS NOT ARMED.

(see Mechanism Parts List below)


Step 1: Locate CO2 Cylinder attached to the life vest.

Step 2: Install new cylinder by engaging bayonet tabs in housing, pushing in then turning clockwise 1/8 turn to a full stop.



WARNING: PFD WILL ONLY INFLATE IF CYLINDER IS TURNED TO FULL STOP.

Step 3: Check to be sure service indicator is green.



Service Indicator



If green, unit is operable.



If red, stop and service unit.

Rearming Kit No. 0927 Contains: 1 Cylinder & 1 Bobbin

The operator of the vessel is required to provide the following User information to each person on board.

Inflatable PFD's will not provide any buoyancy without being inflated. Follow these instructions to be sure your PFD is armed and donned correctly, and that you understand how to inflate the device.

BASIC VISUAL EXAMINATION

Physical Inspection of Cover and Straps - Examine outer shell fabric, seams, webbing attachments, buckles, slides, etc. Fabric fading can indicate a loss of strength. Check for strength by pulling seams and attachments snugly. Make sure that the PFD is free from rips, tears or punctures. This type of damage on the outside covering indicates that the inflatable chamber may have been exposed to potentially damaging conditions. If device shows any signs of damage, return to a certified Stearns Repair Facility or replace the entire device.

CHECK THE CO₂ CYLINDER AND INFLATION MECHANISM

The inflation mechanism is located on your right side under the protective cover.


Be sure that a cylinder is inserted into the mechanism and that the service indicator shows Green. **If the indicator shows Red**, replace with a new cylinder following the rearming instructions on pages 10-11. It is possible to see the indicators on a PFD that is being worn. If you see someone whose PFD has a Red indicator, inform them immediately.

DONNING INSTRUCTIONS



STEP 1

Wear like a jacket, inserting arms between straps and fabric.



STEP 2

Close front buckle. Manual pull lanyard should be visible on your lower right side.



STEP 3

Adjust belt through slide located on right side until a comfortably snug fit is obtained.

After donning, locate the ***Jerk To Inflate*** tab for the mechanism. It should protrude from the PFD as shown on the pictogram. Make sure that you are comfortable locating the ***Jerk To Inflate*** tab with either hand. Should an emergency develop, be prepared to use it! ***Always wear your PFD over, not under clothing.***

Caution: bulky clothing may affect the ability of this PFD to turn the wearer to a face-up position in the water.

Practice closing hardware and adjusting straps before use or prior to in-water testing.

INFLATION INSTRUCTIONS


- 1. Manual Inflation** - To inflate, grasp the ***Jerk to Inflate*** tab and pull sharply downwards.
- 2. Automatic Inflation** - The automatic ***Inflation Mechanism*** will activate when the device is totally immersed in water. The device will obtain full buoyancy within 5 to 10 seconds, unless it is very cold. It is recommended that the user regard the automatic system as a backup and always be prepared to pull the ***Jerk to Inflate*** tab upon immersion.
- 3. Oral Inflation** - The ***Oral Tube*** is located on the wearer's left side. Grasp the ***Oral Tube*** and bring to mouth. Blow air through the ***Oral Tube*** until the ***Inflatable Chamber*** is firm. **If the chamber becomes soft due to CO₂ permeance, Oral Inflation will be necessary to maintain full buoyancy.** Whenever you orally inflate the PFD it would be a good practice to remove the CO₂ cylinder prior to inflating. If you plan on going into the water after oral inflation, also remove the bobbin so it may be reused when rearming the PFD.
- 4. Cold Inflation** - Oral Inflation may be required in addition to manual or automatic inflation if chamber is not firm due to cold temperatures at or below 40° F (4° C). Inflation time using CO₂ gas will be longer at these temperatures. Activation of automatic system may also be slower. Wearing a partially inflated PFD in these conditions will provide some initial buoyancy while the PFD fully inflates. **Always be prepared to use the manual inflation system!**
- 5. Other Inflation Precautions**
 - **Caution:** Do not fully inflate orally then manually or automatically inflate with the CO₂ cylinder. Repeated CO₂ inflation after oral inflation will damage the PFD to the point that it will not hold air or float.
 - When armed in automatic mode, never orally inflate out of the water and then go into the water because the CO₂ system will automatically inflate, which could damage the PFD.
 - **Never** inflate this PFD with a Pump or Air-Compressor.
 - Permeation loss is greater when the device is inflated with CO₂ than with air, and earlier replenishment by means of the oral inflation system will be necessary after several hours.

INFLATED DONNING INSTRUCTIONS

Inflatable PFDs can be very difficult to don when fully inflated. Partially deflate through the Oral Tube until enough gas has escaped to don. See DEFLATION INSTRUCTIONS below. Don as described on page 4 and re-inflate orally as described on page 5.

DEFLATION INSTRUCTIONS

Depress **Oral Valve** (located inside end of **Oral Tube**) using either the protective cap or tab provided by inserting into the end of **Oral Tube**, see drawing. Gently compress chamber to move air out of the inflatable chamber while depressing the **Oral Valve**.



DO NOT TWIST OR WRING INFLATABLE CHAMBER TO DEFLATE.

If for any reason the Oral Valve remains open, depress it several times. If it does not release, discontinue use of this PFD and take it to a certified repair station. (See page 12 and 20 for repair station locations/information.) In an emergency situation, hold thumb over the valve if it will not close, or fold the oral tube in half and squeeze together.

OTHER USE GUIDELINES

1. Always wear your PFD when underway unless you are inside a cabin. This is a requirement for commercial approval and is strongly advised for all users.
2. If you need to jump from any height always fold arms over your chest to keep the PFD in place when entering the water.
3. Avoid all unnecessary activities that will be abrasive to the device.
4. Use extreme caution around sharp objects.
5. Avoid unnecessary exposure to the sunlight. See Care and Cleaning Instructions for general product life expectancy on page 12.
6. CO₂ gas from the cylinder will permeate through the chamber fabric over time. If you are in the water for a long time, it may be necessary to top off the inflatable orally, by blowing air in through the oral tube.
7. Inflatable PFDs are not designed for activities in which the wearer expects to encounter impact with the water at a high speed such as water skiing, riding personal watercraft, etc.
8. Inflatable PFDs are not designed for white water activities.
9. Dropping this PFD into the water will result in an inadvertent inflation and exposing the inflation system to unnecessary water spray may inadvertently inflate it.

SERVICING INSTRUCTIONS

Federal Regulations require Coast Guard approved personal flotation devices (PFDs) that are legibly marked with the Coast Guard approval number, are in good and serviceable condition, and are the correct size for each person on board. It is the responsibility of the operator to be sure this PFD is in serviceable condition. To be considered serviceable, this PFD shall not exhibit deterioration that could diminish its performance, such as broken or deformed hardware, detached webbing, rotted structural components, air leaks or nonfunctional inflation tube. Unless worn inflated, this PFD must also be properly armed with a cylinder installed in the mechanism, a bobbin (water sensing element) installed, and service indicator showing Green. See pages 10-11 for rearming instructions.

MAINTENANCE SCHEDULE						
Each Outing	Every 2 Months*	After Each CO ₂ Inflation	Annually*	Every 2 Years	When Damaged	
X						Check for Green status indicator
X						Check Manual Pull Tab Access
X						Basic Visual Damage Examination (see item 1)
				X		Recommended Test Auto-Inflation (see item 4)
		X	X			Inspect Auto-Inflation Mechanism (see item 2)
	X		X			Test Oral-Inflation (see item 3 & 5)
	X		X			Leak Check - 16 Hours (see item 3)
			X			Clean (see page 11)
		X	X			Rearm - Replace CO ₂ and Bobbin (see page 10-11)
	X		X			Thorough Visual Examination (see item 1)
			X			Record and date inspection log on PFD
				X	X	Recommended return to Stearns Authorized Servicing/Repair Facility

* More often if exposed to potential damage or used in extreme conditions

1. Physical Inspection of Cover and Straps - Examine outer shell fabric, seams, webbing attachments, buckles, slides, etc. Fabric fading can indicate a loss of strength. Check for strength by pulling seams and attachments snugly. Make sure that the PFD is free from rips, tears or punctures. This type of damage on the outside covering indicates that the inflatable chamber may have been exposed to potentially damaging conditions. If device shows any signs of damage, leak test it or return it to a certified Stearns Repair Facility or replace the entire device. This inspection should be performed each outing.

2. How to Inspect the CO₂ Inflation Mechanism - Before inspecting the mechanism remove the CO₂ cylinder to prevent unnecessary discharge.

The CO₂ cylinder contains the gas charge that will inflate your PFD when the inflation mechanism is fired either automatically or manually. You must verify that the CO₂ cylinder installed is of the correct size (gram charge) and has not been previously fired.

Check the bobbin to be sure that it is not cracked or otherwise damaged. To do this, first remove the CO₂ cylinder, and remove the bobbin from the housing. If the bobbin is cracked or damaged, replace with a bobbin as shown in rearming instructions on pages 10-11.

***If a new BOBBIN is not available, your inflatable
CAN ONLY be activated by Oral Inflation.***

Additional Notes on CO₂ Cylinders:

- FAILURE to properly rearm the inflation mechanism prior to installing the CO₂ Cylinder will result in premature activation of the cylinder.
 - CO₂ Cylinders are only good for one (1) inflation and cannot be recharged.
 - CO₂ Cylinders are made with a protective coating that may wear off after a period of use or exposure to the environment. When this coating is worn off, the CO₂ Cylinder may start to show some signs of rusting. If this occurs, replace the CO₂ Cylinder.
 - If a gram scale (such as a postal scale) is available, it is recommended to weigh the cylinder to verify that it meets the minimum weight imprinted on the cylinder with attached bayonet.
3. **Oral Inflation Leak Test** - This test should be performed every two months and at the start of each season. Inflate buoyancy chamber using the oral inflation valve and leave to rest for 16 hours. When buoyancy chamber remains firm and full of air, there is no leakage and chamber is operational. If the chamber deflates during this leak test, immediately return to a certified Stearns Repair Facility for repair. The device is no longer in operational condition.
 4. **Automatic Inflation System** – This test should be performed at least once to familiarize yourself with the function of the auto-inflator in a non-emergency. Re-testing is recommended every two years, or more often if exposed to potential damage or used in extreme conditions, and will expend your CO₂ cylinder and bobbin. So make sure you have a rearm kit before conducting this test. With device packed as normal, immerse the device into a tub of water and see if it inflates. DRY, REARM and REPACK as shown on pages 10, 11 and 13.
 5. **Function Test of Oral Valve** - With the PFD inflated, remove the dust protection cap, and test the valve by pushing it down using the tab provided on the cap (refer to page 6). The valve should depress easily, and when released it should automatically return to the closed position and reseal.

**HALKEY-ROBERTS V86000 PRO 1F MANUAL/AUTOMATIC
REARMING/STATUS INDICATOR INSTRUCTIONS**

DISASSEMBLY

(see figure)

- Step 1:** Unpack or open the life vest so that the manual/automatic inflator is visible.
- Step 2:** Remove gas CO₂ cylinder by rotating cylinder counterclockwise then pull out. **Discard cylinder.**
- Step 3:** Remove cap by turning counterclockwise.
- Step 4:** Remove bobbin from cap or housing unit. **Discard bobbin (yellow).** Check the housing to be sure it is clear and dry.

Note: The bobbin (yellow) body may remain in the housing or in the cap assembly when you remove the cap. The bobbin body must be removed prior to Rearming.

REARMING

Note: Rearming must follow the sequence below.

- Step 5:** A new bobbin must be used. The date on the bobbin should not be over three (3) years from the date of purchase.
- Step 6:** **IMPORTANT!**
Bobbin (yellow) must be installed into the HOUSING (**see figure), white side up, aligning the slots on the bobbin with the ridges inside the threaded housing. The bobbin will slide in easily if installed correctly.

- Step 7:** Install cap by screwing clockwise until it meets the housing shoulder.

Note: No gap between the cap and the housing shoulder.

- Step 8:** Check the new cylinder to be sure it has sensor ring attached.

IMPORTANT!

You will damage the sensor ring if bobbin and cap are not installed first.


- Step 9:** Install new cylinder by engaging bayonet tabs in housing, pushing in then turning clockwise 1/8 turn to a full stop.



**WARNING: PFD WILL ONLY INFLATE IF
CYLINDER IS TURNED TO FULL STOP.**

- Step 10:** Check to be sure service indicator is green.

Halkey-Roberts V86000 Pro 1F Manual/Automatic ReArming/Status Indicator Instructions



Service Indicator

- If green, unit is operable.
- ⬮ If red, stop and service unit.

III. CARE AND CLEANING INSTRUCTIONS

The reliability and service life of this PFD depends greatly upon how it is used and cared for. Avoid storing PFD in direct sunlight. Sunlight contains ultraviolet radiation that weakens synthetic materials. Prolonged exposures to high temperatures and high humidity may shorten service life of this PFD. While it is known that these elements degrade the materials, every use environment is unique so there is no sure way to estimate how long the PFD will last. It is for this reason that you must follow the care and cleaning instructions and perform the maintenance and service checks. This will assure that the PFD remains functional and will maximize the useful life of this PFD. Failure to follow these instructions rigorously could result in a non-functioning PFD causing injury or death.

Drying – If the device is wet, place on a coat hanger to allow thorough drying. Do not place in direct sunlight to dry. Do not use any heat source or place on radiator.

Cleaning – Damp wipe only with mild detergent recommended for synthetic fabrics. Remove grease and oil immediately. After every use, and before rinsing, first remove CO₂ cylinder and bobbin and rinse well with fresh water. Read instructions provided on the device.

- **DO NOT MACHINE WASH**
- **DO NOT MACHINE DRY**
- **DO NOT DRY CLEAN**
- **DO NOT USE SOLVENT BASED CLEANERS**
- **DO NOT BLEACH**

STORAGE


- Store your bobbin (water sensing elements) in a ventilated package, do not store in a sealed container.
- Store in clean, cool, dry area.
- Do not store bobbins in high humidity or high temperatures (over 100°F) for an extended time.
- Do not store bobbins for more than 18 months before use.

REPAIR


If you have any question about the condition or integrity of this product call 1-800-STEARN'S (1-800-783-2767). **A damaged device must be repaired by certified Stearn's Repair Facility or discarded.**

REPACKING INSTRUCTIONS


Always deflate the *PFD* and rearm the *Inflation Mechanism* — follow *REARMING* Instructions prior to *REPACKING*!




1. Lay device out flat with the yellow inflatable chamber up. Fold right inside edge over as shown, exposing Velcro® strip.



2. Fold right outside edge over, securing Velcro® strips. Fold left inside edge over, exposing Velcro® strip.



3. Fold left outside edge over, securing Velcro® strips. Fold right topside over, exposing Velcro® strip. Position **Jerk to Inflate** Tab below bottom of clear window pocket. Fold left topside over, securing Velcro® strips.



4. Snap back strap to shell. Secure Velcro® strap extensions. Examine all straps, belt keepers, adjustment slides and buckles to assure that they are free from twists. Check to see that the **Jerk to Inflate** Tab is hanging free and the green indicator is clearly visible through the plastic window.

IV. WHY ARE PFDs REQUIRED SAFETY EQUIPMENT?

Drownings are the leading cause of fatalities involving both commercial and recreational boating. A PFD provides flotation to help keep your head above water, help you to stay face up in the water, and increase your chances for survival and rescue. Most adults only need an extra 7 to 12 pounds (31 to 53 Newtons) of flotation to keep their heads above water. The proper size PFD will properly support the weight of the wearer. Since this inflatable PFD does not have inherent buoyancy, it provides flotation only when inflated. Familiarize yourself with the use of this PFD so that you will know what to do in an emergency.

V. HOW AND WHY TO TEST YOUR PFD?

Inflate your PFD and try it out in the water to:

- Make sure it floats you:
 - Comfortably* (When worn properly)
 - Adequately for expected wave conditions*
(Body shapes/densities affect performance)
- Make sure it works:
 - A flow of bubbles should not appear*
(See page 9 for leak test)
 - It should inflate quickly and easily*
- Learn how it works by:
 - Activating the CO₂ inflation system*
 - Rearming the CO₂ inflation system*
 - Using the Oral inflator tube*

The U.S. Coast Guard recommends that you purchase two automatic rearming kits; one to be used immediately in testing the automatic inflation system (see HOW DO YOU TEST YOUR PFD USING THE AUTOMATIC INFLATOR?) and the other to carry on board as a spare.

Since you should replace the bobbin each year, the U.S. Coast Guard recommends you test the automatic inflation system in-the-water at the beginning of each boating season. By doing this, you demonstrate that the automatic inflation system is still working properly and reduce the likelihood of premature inflation and its associated dangers.

HOW DO YOU TEST YOUR PFD USING THE AUTOMATIC INFLATOR?

1. To test your inflatable PFD, you will need:
 - Your **fully armed PFD**, and
 - **Rearming kit** approved for your PFD. (This kit contains a CO₂ cylinder and bobbin that you will need to use following this test.)
2. Put on the PFD.
3. Get into shallow water, just deep enough that you can stand with your head above the surface. Once the automatic inflator is under water the PFD should automatically, fully inflate within 10 seconds.
4. See if the PFD will float you on your back or just slightly back of vertical. In a relaxed floating position, verify that your mouth is well above the water's surface. Note the effect of where you hold your legs on how you float.
5. Get out of the water and remove the PFD. Remove the used CO₂ cylinder and the used bobbin from the PFD inflator. Deflate the PFD using the oral inflator.
6. Let the PFD dry thoroughly. **REARM** and **REPACK** (refer to pages 10, 11 and 13) the PFD in accordance with the manufacturer's instructions!



HOW DO YOU TEST YOUR PFD USING THE ORAL INFLATOR?

1. To test your inflatable PFD, you will **not need any spare parts or rearming kits.**
2. Remove the CO₂ cylinder and bobbin, to prevent inadvertent activation of the automatic inflation system, which could potentially damage the PFD.
3. Put on the PFD.
4. Get into shallow water, just deep enough that you can stand with your head above the surface.
5. If you are a weak swimmer or non-swimmer, inflate the PFD partially so that you are supported well enough to be able to complete inflation without touching bottom. Note this level of inflation because it is the minimum needed for you to safely use this inflatable PFD.
6. Fully inflate the PFD using the oral inflator.
7. See if the PFD will float you on your back or just slightly back of vertical. In a relaxed floating position, verify that your mouth is well above the water's surface. Note the effect of where you hold your legs on how you float.
8. Get out of the water and remove the PFD. Completely deflate the PFD using the oral inflator.
9. Let the PFD dry thoroughly. **REARM** and **REPACK** the PFD in accordance with the manufacturer's instructions! Refer to Pages 10 and 12-14.

VI. WEAR YOUR PFD

In approximately 80 percent of all boating fatalities, the victims were not wearing a PFD. Most fatal accidents happen on calm sunny days. This inflatable PFD is much more comfortable to wear than other PFD types. Get into the habit of wearing this PFD. Non-swimmers and children especially should wear a hybrid or non-inflatable PFD at all times when on or near the water.

VII. HYPOTHERMIA

Prolonged exposure to cold water causes a condition known as hypothermia - a substantial loss of body heat, which leads to exhaustion and unconsciousness. Most drowning victims first suffer from hypothermia. The following chart shows the effects of hypothermia:


HOW HYPOTHERMIA AFFECTS MOST ADULTS

Water Temperature ° C ° (F)	Exhaustion or Unconsciousness	Expected Time of Survival
0.3 (32.5)	UNDER 15 MIN	UNDER 15 TO 45 MIN
0.3 TO 4 (32.5 to 40)	15 TO 30 MIN	30 TO 90 MIN
4 TO 10 (40 to 50)	30 TO 60 MIN	1 TO 3 HOURS
10 TO 16 (50 to 60)	1 TO 2 HOURS	1 TO 6 HOURS
16 TO 21 (60 to 70)	2 TO 7 HOURS	2 TO 40 HOURS
21 TO 27 (70 to 80)	2 TO 12 HOURS	3 HOURS TO INDEFINITE
Over 27 (Over 80)	INDEFINITE	INDEFINITE

PFDs can increase survival time because they allow you to float without using energy treading water and because of their insulating properties. Naturally, the warmer the water, the less insulation you will require. When operating in cold waters [below 60° F (15.6° C)] you should consider using a coat or jacket style PFD or a Type V Thermal Protective PFD as they cover more of the body than the vest or belt style PFDs.

SOME POINTS TO REMEMBER ABOUT HYPOTHERMIA PROTECTION:

1. Always wear your PFD. Even if you become incapacitated due to hypothermia, the PFD will keep you afloat and greatly improve your chances of rescue.
2. Do not attempt to swim unless it is to reach a nearby craft, fellow survivor, or a floating object on which you can lean or climb. Swimming increases the rate of body heat loss. In cold water, drown-proofing methods that require putting your head in the water are not recommended. Keep your head out of the water. This will greatly lessen heat loss and increase your survival time.
3. Use the standard H.E.L.P. position when wearing an inflatable PFD. Wrap your arms around your torso, under the PFD, and draw your legs up to a seated position. Doing so will help you conserve body heat.



4. Keep a positive attitude about your survival and rescue. This will improve your chances of extending your survival time until rescued. Your will-to-live does make a difference!
5. If there is more than one person in the water, huddling is recommended while waiting to be rescued. This action tends to reduce the rate of heat loss and thus increase the survival time.

IIX. EACH OF THESE DEVICES IS INTENDED TO HELP YOU SAVE YOUR OWN LIFE

For your PFD to function properly follow these suggestions to verify that it fits, floats, and remains in good condition.

1. Check the status of the inflator and make sure that the service indicator is green. Check before each outing.
2. Get in the habit of rearming the inflation mechanism right after each CO₂ inflation.
3. This PFD requires rearming with a new cylinder, and bobbin after each CO₂ inflation. Always have rearming kits to service your inflatable PFDs.
4. Try your wearable PFD on and adjust it until it fits comfortably in and out of the water.
5. Mark your PFD with your name if you are the only wearer.
6. Do not alter your PFD. If it doesn't fit properly, get one that does. An altered device is no longer Coast Guard approved.
7. Your PFD is not intended for use as a fender or kneeling pad.
8. If your PFD is wet, allow it to dry thoroughly before storing it. Store it in a well-ventilated area.
9. Do not dry your PFD in front of a radiator or other source of direct heat.

NOTES

IX. ADDITIONAL INFORMATION

If you need more information about PFDs and safe boating, contact your state boating authority, U.S. Coast Guard Auxiliary, U.S. Power Squadron, Red Cross, or your nearest unit of the U.S. Coast Guard; or call the Coast Guard Customer Information Line at 1-800-368-5647 or the Free Boating Course number 1-800-336-BOAT (in VA, 1-800-245-BOAT) or see the USCG Boating Web Page at www.uscgboating.org.

DO NOT ATTACH PFD'S TO YOUR BOAT

Each PFD has straps, hooks, buckles, or other means for securing the device in place on the wearer. Some PFDs also incorporate decorative dee rings or tabs. Such items are not to be used to attach the device to the boat. Attaching the device to the boat will not permit it to perform as intended.

CO₂ PERMEATION LOSS

CO₂ gas will permeate the chamber fabric over time. Oral Inflation may be necessary to maintain full buoyancy.

BUDDY LINE INFORMATION

Buddy lines, when provided, are to be used by people adrift in the water, to attach themselves to one another and aid in staying together. *Buddy lines are not designed for lifting.*

IF YOU HAVE ANY QUESTIONS ABOUT THE INITIAL ARMING, REARMING, REPACKING, OR NEAREST AUTHORIZED STEARNS REPAIR FACILITY CALL 1-800-STEARN (1-800-783-2767).

PRODUCT REGISTRATION:

PLEASE MAIL REGISTRATION CARD OR CALL

1-800-STEARN (1-800-783-2767)

IN ORDER TO RECEIVE IMPORTANT UPDATES ON THIS PFD.



CRP 1105