



- | | | | | | |
|---|---|---|---|---|---|
| R89-1GLC Finish(C) <input type="checkbox"/> | R89-1GLK Finish(K) <input type="checkbox"/> | R89-7GLC Finish(C) <input type="checkbox"/> | R89-7GLK Finish(K) <input type="checkbox"/> | R89-8GLC Finish(C) <input type="checkbox"/> | R89-8GLK Finish(K) <input type="checkbox"/> |
| R89-1GLY Finish(Y) <input type="checkbox"/> | R89-7GLY Finish(Y) <input type="checkbox"/> | R89-8GLY Finish(Y) <input type="checkbox"/> | | | |

Specifications

- Secure Pfit Trim
- Trim Only, Valve Not Included

Features

- 2.5 GPM Flow Rate (Showerhead)
- Secure Pfit Trim
- Complete Collection with Coordinating Lavatory and Roman Tub Options
- Quick Trim Installations- Attaches Without Tools, No Exposed Screws
- Fits OX8 and JX8 Valve Bodies
- EZ Clean™
- Brass Ball Joints
- IP Tub Spout (8GL Only)
- Pforever Warranty®
- Valve only trim. No shower head or shower flange included.

Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified
- CSA B125 Certified
- ASME A112.18.1
- ASSE 1016
- ADA Compliant-ANSI A117.1 (Lever handles only)



Dimensions

