



1. PRODUCT NAME

Superior Flexible Grout Admixture

2. MANUFACTURER

SUPERIOR ADHESIVES & TOOLS
8515 Brown St. Ottawa Lake, MI 49267
CUSTOMER SERVICE
1-888-398-6595
www.superioradhesivesandtools.com

3. PRODUCT DESCRIPTION

Superior Flexible Grout Admixture is the latest technology of acrylic polymers designed to give Superior Unsanded and Sanded grouts improved performance. This state-of-the-art additive reduces cracking of grout by absorbing substrate movement, and it also makes grout extremely dense to enhance color development, consistency and stain resistance. This admixture is created for exterior and interior installations and is especially suitable for heavy-use areas in residential, commercial and industrial applications (e.g. countertops, bathroom walls and floors, foyers, kitchens, locker rooms, etc.). Superior Flexible Grout Admixture can be used with all ceramic, porcelain and some natural stone in both vertical and horizontal installations.

DESCRIPTION

A. Uses

Designed for use with Superior Unsanded and Sanded grouts installed with ceramic, porcelain, and some natural stone in both vertical and horizontal installations.

B. Features

- Reduces grout cracking
- Enhances color development and consistency
- Increases stain resistance when mixed with grout
- Interior or Exterior
- Residential, commercial and industrial applications of grout

C. Packaging

1 qt. container
½ gal. container
1 gal. container

D. Shelf Life

6 months. Store off the ground and protect from the weather

E. Limitations

Shake well before using. Clean all tools with sponge and water while material is soft. Keep from freezing. Portland cement grouts are high alkaline – avoid contact with eyes and prolonged contact with skin. Flush contact areas thoroughly.



4. APPLICATION

Read entire label before using. Surface should be clean and dry. Use Flexible Grout Admixture in place of water when mixing grout.

A. Application of Product

1. For the best results, add grout powder to this liquid
2. Mix no more than what can be used within 25 minutes.
3. Allow mixed grout to slake for 10 minutes then remix prior to using. This waiting period allows the admixture to react with the grout powder. The consistency of grout should be that of toothpaste. Use recommended amount of liquid as indicated on the grout packaging.
4. For recommended natural stone installations, pre-seal the stone prior to grouting.

B. Cleaning

Clean excess grout from the face of the tile before it hardens using a slightly damp sponge.

C. Handling and Storage

Close container after each use. Store in original container only. Keep from freezing.

5. AVAILABILITY

Available exclusively at The Tile Shop. Visit www.tileshop.com to find your nearest location or call 1-888-398-6595 for more information.

6. MAINTENANCE

After grout has dried 48 to 72 hours, seal all grout joints with Superior Premium Gold or Superior Max-Seal solvent-based sealer to prevent grout porosity and to retain the grout color. Superior Premium Gold or Superior Max-Seal solvent-based sealer is designed for interior and exterior applications. For weekly cleaning of tile and grout, use Superior Grout and Tile Neutral Cleaner. This is a neutral pH cleaner and will not strip or remove the sealer from the grout joint. Because it is not a soap, it is equally effective in hard or soft and hot or cold water.

7. TECHNICAL SERVICES

1-888-398-6595