



1. PRODUCT NAME

Max-Seal Solvent Based Sealer

2. MANUFACTURER

SUPERIOR ADHESIVES & TOOLS
8515 Brown St. Ottawa Lake, MI 49267
CUSTOMER SERVICE
1-888-398-6595
www.superioradhesivesandtools.com

3. PRODUCT DESCRIPTION

Max-Seal Solvent-Based Sealer is a solvent-based mixture of silane, siloxane and fluoropolymer (< C8). In diluted form, it serves to render inorganic substrates such as mineral construction materials water-repellent and oil-repellent. Unlike conventional impregnating agents, which display only a hydrophobic, i.e. water-repellent, effect, Max-Seal Solvent-Based Sealer also exhibits an oleophobic, i.e. oil-repellent, effect. The pores of the substrate remain open, the water vapor diffusion is hardly affected, if at all. Oil, grease and paint, etc. can be more easily removed from surfaces that have been treated with Max-Seal Solvent-Based Sealer.

DESCRIPTION

A. Uses

Designed for use on unsealed stone such as marble, slate, limestone, quartzite, sandstone, and travertine. Effective for interior and exterior applications.

B. Features

- Interior and exterior use
- Hydrophobic characteristic protects surface from water soluble stains
- Oleophobic characteristic protects surface from fat soluble stains
- No sheen sealer
- Allows moisture-vapor transmission

C. Packaging

16 oz. container
32 oz. container

D. Shelf Life

Refer to "Best use before end" on package. Storage beyond the date specified does not necessarily mean that the product is no longer usable. In this case however, the properties required for the intended use must be checked for quality assurance reasons.

E. Limitations

Do not allow Max-Seal Solvent-Based Sealer to come in contact with any non-recommended surface as product is not completely removable. Sealers and finishes should not be used before or after use. If Max-Seal Solvent-Based Sealer is not wiped completely dry within 5 minutes, a residue may form. If residue occurs, use a scrub brush or floor machine with Superior Stone Deep Clean to remove. Keep floor surfaces dry and clean to reduce possibility of slip-fall accidents. Routine pressure washing will effect expected wear. Sealer will not prevent surface wear or washing from acids or caustic chemicals.



4. APPLICATION

Read entire label before using. For new installations, sealer must be applied at least 2 hours before grouting and as soon as 48 hours after grouting. Surface must be clean, dry, and free of existing sealers or coatings.

A. Application of Product

1. Apply using a sponge, brush, and paint pad, cotton towel, or sprayer.

Note: Sure that any sealer that does not penetrate surface is polished dry off surface within 5 minutes of application using absorbent paper or cotton towels

2. If 2 or more coats are applied, allow a minimum of 30 minutes drying time between coats.
3. Read for surface traffic in 12 hours after final coat. Keep dry for 12 hours. Achieves full cure in 48 hours, some highly porous surfaces may require an additional coat after full cure.

B. Cleaning

Clean applicator tools with mineral spirits after each use

C. Handling and storage

Close container tightly after each use. Storage at temperatures below 8°C can result in Max-Seal Solvent-Based Sealer forming a gel. Storing in a heated area for several hours will allow for liquefaction. Unused, stored product is freeze-thaw stable. Dispose of residue or any unused leftover product in accordance with applicable federal, state, and local requirements.

5. AVAILABILITY

Available exclusively at The Tile Shop. Visit www.tileshop.com to find your nearest location or call 1-888-398-6595 for more information.

6. MAINTENANCE

Grout & Tile Neutral Cleaner or Superior Anti-Bacterial Natural Stone Cleaner is recommended for routine cleaning.

7. TECHNICAL SERVICES

1-888-398-6595