

1. PRODUCT NAME

Maxlite

2. MANUFACTURER

SUPERIOR ADHESIVES & TOOLS
8515 Brown St. Ottawa Lake, MI 49267
CUSTOMER SERVICE
1-888-398-6595
www.superioradhesivesandtools.com

3. PRODUCT DESCRIPTION

Superior Maxlite is a lightweight, high-performance, polymer-modified mortar with premium workability for a broad range of tile installations. This innovative formula offers an excellent non-slump characteristic for large and heavy tile, making Superior Maxlite an ideal choice for most installations. Lightweight 30 lb formula provides the same coverage as traditional 50 lb mortars.

DESCRIPTION**A. Uses**

Designed for ceramic, porcelain and natural stone tiles for both walls and floors in interior and exterior applications. Suitable for both residential and commercial construction.

B. Features

- Interior and exterior
- Freeze-thaw stable
- Non-sag for wall areas
- Bonds to most surfaces
- Lightweight and easy to install
- Thinset or medium bed performance
- Wall tile and large format
- Same coverage as traditional 50 lb mortar

C. Suitable Substrates

- Brick masonry
- Cement backer board
- Cement mortar beds
- Cement plaster
- Cement terrazzo
- Ceramic tile and stone
- Uncoupling membranes
- Blanke Permat
- Dural Backerlite

D. Packaging

30 lb bag. Colors: White and Grey.

E. Shelf Life

15 months. Store off the ground and protect from moisture and extreme temperatures.

F. Limitations

Use caution; do not allow mortar to freeze for the first 72 hours. Do not soak tiles prior to installation. Do not apply over asphalt sheeting, vinyl-covered wall board, Masonite, cement asbestos board, metal, glass, plastic or other unstable substrates. Improperly cured or wet plywood, particle board or strip wood are not suitable substrates. For installations that will be continually wet like swimming pools, fountains and gang showers, the completed installation should be cured a minimum of 14 days and allowed to dry before exposure to water. For white or light-colored marbles use white mortar. Dimensional stone tile like resin-backed black, green and red marbles may warp when installed with water-based setting materials. These water-sensitive stone tiles should be installed with Superior Pro-Epoxy.

4. TECHNICAL DATA**Applicable Standards**

ANSI 118.15 & 118.11

5. INSTALLATION

All surfaces must be structurally sound and free of contaminants including oil, dirt, grease, paint, sealers or other chemicals and must be between 40° F and 90° F. Remove any residue from your surface prior to installation. Concrete slabs must be cured 28 days, free of efflorescence and not subject to hydrostatic pressure. Cracks, depressions or imperfections must be addressed prior to installation. Dry, dusty concrete slabs should be dampened and excess water removed. All concrete slabs must be plumb and true and meet minimum standard of 1/4" in 10 feet. Follow TCNA guidelines detail EJ-171: Movement Joints—Vertical & Horizontal or ANSI specification A108.01-3.7: Requirements for Movement Joints. Do not cover substrate expansion joints with mortar. Prior to installation, verify that subfloor assembly meets or exceeds industry standards of L/360 for ceramic tile and brick or L/720 for stone installations under live and dead loads.

DESCRIPTION**A. Mixing Instructions**

Add 5.25 qts of clean water per 30 lb of powder. Mix by hand or with slow-speed mixer to smooth workable consistency. Allow mortar to slake for 10-15 minutes then remix to a fluffy consistency. Remix occasionally to keep mortar workable. DO NOT temper with water.

B. Application of Product

Refer to ANSI 108.5 and the TCNA Installation Handbook. Choose appropriate trowel size to ensure full mortar coverage under your tile. It may be necessary to back butter tile with mortar prior to setting tile into fresh mortar bed. Make sure to compress all trowel ridges for complete mortar coverage. Periodically check to make sure you are achieving full coverage.

C. Curing of Product

Allow 24 hours for thinset to cure. If mortar is skimmed over please replace with fresh mortar prior to setting tile.

D. Cleaning

Clean tools with fresh water when mortar is uncured.

6. AVAILABILITY

Available exclusively at The Tile Shop. Visit www.tileshop.com to find your nearest location or call 1-888-398-6595 for



more information.

7. WARRANTY

8. MAINTENANCE

Superior installation products require no long-term maintenance, but installation performance and durability may depend on proper maintenance of other products used during installation.

9. TECHNICAL SERVICES

1-888-398-6595

10. FILING SYSTEM