



1. PRODUCT NAME

Premium Gold Sealer

2. MANUFACTURER

SUPERIOR ADHESIVES & TOOLS
8515 Brown St. Ottawa Lake, MI 49267
CUSTOMER SERVICE
1-888-398-6595
superioradhesivesandtools.com

3. PRODUCT DESCRIPTION

Premium Gold is a water-based impregnating sealer specifically designed for porous surfaces such as natural stone, grout, tile, concrete, and other masonry surfaces. Premium Gold provides superior protection against moisture penetration, thereby reducing the formation of efflorescence; it is virtually invisible once dried leaving the surface with its original appearance and breathability.

DESCRIPTION

A. Uses

Designed for concrete, marble, travertine, granite, limestone, slate, tumbled stone tile, vitrified brick, exposed aggregate concrete, manufactured stone, and concrete roof tiles.

B. Features

- Solvent-free and low odor
- Water-based
- Interior and exterior use
- Deep penetration and long-lasting
- Easy application and fast drying
- No change of surface appearance

C. Suitable Substrates

- Concrete
- Natural stones
- Vitrified brick
- Tumbled stone tile
- Exposed aggregate concrete
- Manufactured stone

D. Packaging

Pint, Quart, and Gallon

E. Shelf Life

12 months. Store off the ground and protect from moisture and extreme temperatures.

F. Limitations

Use caution; will not resist moisture where hydrostatic pressure is active. Product is not removable once installed.



4. TECHNICAL DATA

Refer to Applicable Standards

5. INSTALLATION

All surfaces must be structurally sound and free of contaminants including oil, dirt, grease, paint, sealers or other chemicals that may interfere with the penetration of this sealer to the applied surface. Product must be applied between 40° F and 90° F. Remove any residue from your surface prior to installation. Thoroughly test this product on an inconspicuous area to assure performance and appearance. After cleaning, allow surface to dry 24 hours prior to sealer application. Concrete slabs must be cured 28 days, free of efflorescence and not subject to hydrostatic pressure. Cracks, depressions or imperfections must be addressed prior to installation. Dry, dusty concrete slabs should be dampened and excess water removed.

DESCRIPTION

A. Mixing Instructions

Thinning not required; use as is.

B. Application of Product

Can be applied with a brush, roller, or most types of low pressure hand pump, spray equipment. Do not aerosolize with airless spray equipment. On dense surface one coat is all that is required to seal and protect the surface. If a second coat is necessary due to extreme porosity, apply immediately after the first coat has soaked in. Do not apply product during wet weather or when surface temperature exceeds 80° F. Application to a damp surface or incompletely cured concrete may cause a hazy appearance or loss of adhesion. Air and surface temperature should be between 50° and 80° for 24 hours following application. Dry time ranges from 30 minutes to 3 hours.

C. Curing of Product

Allow 48-72 hours for sealer to cure.

D. Cleaning

Clean tools with fresh water when sealer is uncured.

6. AVAILABILITY

Available exclusively at The Tile Shop. Visit www.tileshop.com to find your nearest location or call 1-888-398-6595 for more information.

7. WARRANTY

8. MAINTENANCE

Superior installation products require no long-term maintenance, but installation performance and durability may depend on proper maintenance of other products used during installation.

9. TECHNICAL SERVICES

1-888-398-6595

10. FILING SYSTEM

CUSTOMER SERVICE 1-888-398-6595

Data Sheets are subject to change without notice. For latest revision, contact our customer service representatives or your local showroom.