



## 1. PRODUCT NAME

Pro-Color Grout Colorant

## 2. MANUFACTURER

SUPERIOR ADHESIVES & TOOLS  
8515 Brown St. Ottawa Lake, MI 49267  
CUSTOMER SERVICE  
1-888-398-6595  
superioradhesivesandtools.com

## 3. PRODUCT DESCRIPTION

Superior Pro-Color is a unique, easy-to-use water-based acrylic colorant and sealer that penetrates deep into grout to add a fresh, new appearance that will renew that look of any tile installation.

### DESCRIPTION

#### A. Uses

Designed to refresh grout joints to alter or enhance the look of a grout installation or resemble their original appearance. Pro-Color is used to seal grout joints resist stains, dirt and grime. It is NOT recommended for submerged applications, such as pools or fountains.

#### B. Features

- Interior and exterior
- Grout colorant and sealer
- Provides excellent stain resistance
- Rejuvenates grout color for up to 15 years
- Easy to apply
- Cleans up with water

#### C. Suitable Substrates

- Impervious porcelain and glass tile
- Brick and thin brick
- Natural stone
- Vitreous, semi-vitreous or non-vitreous tile

#### D. Packaging

8 oz. bottle. Colors: see current Superior Grout Chart

#### E. Shelf Life

36 months, unopened. Store off of the ground and protect from the weather conditions.

#### F. Limitations

Use caution; Use only when surface temperatures are between 50° F and 90° F. Store product in original container only. Pro-Colorant is not recommended for submerged applications, such as pools and fountains.

## 4. TECHNICAL DATA

**Refer to Applicable Standards**

**5. INSTALLATION**

Thoroughly clean and lightly etch all grout surfaces to be coated using a grout cleaner. Remove any residue from your surface prior to installation. If using more than 1 bottle of application, mix all material together in a larger container prior to use to ensure color is consistent. Sealing of porous tile may be required prior to application of grout colorant to ensure it is not absorbed into the tile.

**DESCRIPTION****A. Mixing Instructions**

If using more than 1 bottle of a single color for an application, mix all material together in a larger container prior to use to ensure color is consistent.

**B. Application of Product**

Thoroughly clean and lightly etch all grout surfaces to be coated. Always test strength on a small, inconspicuous area prior to use. Using a grout brush, scrub grout joint until clean. Thoroughly rinse grout joints with water, removing all residue. Use a clean sponge to aid in cleanup. Apply Pro-Colorant to grout joint and work it deeply into the surface using a back-and-forth motion. For best results, apply in two coats waiting 2-4 hours of drying time between coats.

**C. Curing of Product**

Cure times may vary due to temperature and humidity. Pro-Color dries tack-free after 30 minutes and is ready for a second coat after 2-4 hours (depending on climate conditions). Pro-Color is ready for light foot traffic after only 2-4 hours, normal foot traffic after 24 hours, and heavy (commercial) traffic after 72 hours. Allow up to 72 hours drying time

**D. Cleaning**

Clean tools with warm, soapy water and a sponge.

**6. AVAILABILITY**

Available exclusively at The Tile Shop. Visit [www.tileshop.com](http://www.tileshop.com) to find your nearest location or call 1-888-398-6595 for more information.

**7. WARRANTY****8. MAINTENANCE**

Clean with neutral pH cleaners including Superior Grout & Tile Neutral Cleaner and Superior Anti-Bacterial Natural Stone Cleaner.

**9. TECHNICAL SERVICES**

1-888-398-6595