

1. PRODUCT NAME

Pro-Siliconized Acrylic Caulk

2. MANUFACTURER

SUPERIOR ADHESIVES & TOOLS
8515 Brown St. Ottawa Lake, MI 49267
CUSTOMER SERVICE
1-888-398-6595
superioradhesivesandtools.com

3. PRODUCT DESCRIPTION

Superior Pro-Siliconized Acrylic Caulk is a premium, one-part formula with professional workability, flexural strength and resistance to a broad spectrum of fungal, algal and bacterial growth.

DESCRIPTION**A. Uses**

Designed for general sealing applications where painting, flexibility and adhesion are required. This is an excellent all-purpose sealant for cracks and joints and exhibits good adhesion to a full range of construction substrates such as wood, concrete, metal, glass, stone, brick, stucco and marble. Suitable for interior and exterior applications in both residential and commercial construction.

B. Features

- Interior and exterior
- Long-lasting and flexible
- Stain, mold and mildew resistant
- Easy water cleanup
- Available in a variety of colors

C. Suitable Substrates

- Impervious porcelain and glass tile
- Brick and thin brick
- Natural stone
- Vitreous, semi-vitreous or non-vitreous tile

D. Packaging

10.5 oz. Colors: see current Superior Grout Chart

E. Shelf Life

12 months. Store off of the ground and protect from the weather conditions.

F. Limitations

Use caution; do not use below grade or below waterline. Do not use on joints subject to heavy abrasion or wear. Do not "overtool" the applied caulk, leaving too little caulk to perform following cure. Install in an ambient temperature between 40° F and 90° F; do not apply when rain or freezing temperatures are expected. Protect from rain or exposure to water for 72 hours. Cooler weather and higher humidity will slow down cure time. Do not use for joints exceeding 3/8" x 3/8". For joints deeper than 3/8", use appropriate backer rod. Pro-Siliconized Acrylic Caulk will fill cracks and joints up to 1" wide by 1/2" deep in a single application.



4. TECHNICAL DATA

Applicable Standards

ASTM C-834-05

5. INSTALLATION

All surfaces must be structurally sound and free of contaminants including oil, dirt, grease, paint, sealers or other chemicals and must be between 40° F and 90° F. Remove any residue from your surface prior to installation. Use in well ventilated areas and avoid breathing vapors.

DESCRIPTION

A. Application of Product

Clean tile and joints prior to installation. Allow surface to dry completely before application of caulk. Use masking tape to areas around joint where caulk should not appear to give you a straight line of caulk improving final appearance. Cut the nozzle at a 45° angle to desired size. Load cartridge into caulking gun and apply using steady, even pressure to completely bridge joint. Smooth caulk bead using a damp cloth or sponge before surface skins over.

B. Curing of Product

Cure times may vary due to temperature and humidity. Protect from water until cured, usually within 24 - 72 hours.

C. Cleaning

Clean tools with fresh water when caulk is uncured.

6. AVAILABILITY

Available exclusively at The Tile Shop. Visit www.tileshop.com to find your nearest location or call 1-888-398-6595 for more information.

7. WARRANTY

8. MAINTENANCE

Clean with neutral pH cleaners including Superior Grout & Tile Neutral Cleaner and Superior Anti-Bacterial Natural Stone Cleaner.

9. TECHNICAL SERVICES

1-888-398-6595