

BOND LFT MORTAR

Superior Bond LFT Mortar is a best-in-class polymer-modified thinset with premium non-slump characteristics making it ideal for large and heavy tile with tile build-up to 3/4". Bond LFT Mortar offers a smooth, creamy formulation and has excellent non-sag performance that provides easy troweling.

Key Features

- Interior and exterior use; suitable for residential and commercial construction
- Premium multi-purpose thinset
- Smooth and easy to trowel and apply
- Meets or exceeds ANSI standards 118.4, 118.11 and 118.15

Installation

Sizes: 50 lb. bag

Colors: White

Mixing Ratio: 6.25 - 6.5 qts. of water per 50 lb.

Coverage: Approx. 90 sq. ft. per 50 lb.

- 1/4" sq. notch trowel: 90 - 100 sq. ft.
- 3/8" sq. notch trowel: 80 - 90 sq. ft.
- 1/2" sq. notch trowel: 30 - 40 sq. ft.

Related Products

- Spiral Mixer 24"
- Bucket 3.5 Gal | 6 Gal
- Margin Trowel

Performance

Open Time: 15 - 25 minutes

Pot Life: Approx. 3 hours

Working Time: 20 - 30 minutes

Shelf Life: 15 months. Store in cool, dry location.

Steps to Using Bond LFT Mortar

- 1 Use approx. 6.25-6.5 qts. of clean water per 50 lb. of powder.
- 2 Pour powder into the bucket of water until the water forms a ring around the powder.
- 3 Use a spiral mixer to mix the thinset to a "peanut butter" consistency. Let it slake for 5 minutes, then mix again.
- 4 Use product within pot life. Do not re-temper*. If thinset is no longer workable, discard the thinset and mix a new batch.

*Add additional water and re-mix after initially activating product.

[Always add powder into liquid when mixing.]

