



## 1. PRODUCT NAME

Superior Enhance and Seal

## 2. MANUFACTURER

SUPERIOR ADHESIVES & TOOLS  
8515 Brown St. Ottawa Lake, MI 49267  
CUSTOMER SERVICE  
1-888-398-6595  
www.superioradhesivesandtools.com

## 3. PRODUCT DESCRIPTION

Superior Enhance and Seal is an excellent, no-sheen, enhanced-look, penetrating sealer formulated to darken and highlight the character and beauty of unsealed natural stone. It rejuvenates the color and improves the appearance of worn and weathered stone. May also be used as a pre-grouting sealer. Allows moisture-vapor transmission.

### DESCRIPTION

#### A. Uses

Designed for use on unsealed stone such as marble, slate, limestone, quartzite, sandstone, and travertine. Effective for interior and exterior applications.

#### B. Features

- Interior and exterior use
- Freeze-thaw stable
- Gives stone a “wet” look
- No sheen sealer
- Allows moisture-vapor transmission
- Protects stone from staining

#### C. Packaging

16 oz. container  
32 oz. container

#### D. Shelf Life

12 months in unopened container at 70°F

#### E. Limitations

Do not allow Superior Enhance and Seal to come in contact with any non-recommended surface as product is not completely removable. Sealers and finishes should not be used before or after use. If Superior Enhance and Seal is not wiped completely dry within 5 minutes, a residue may form. If residue occurs, use a scrub brush or floor machine with Superior Stone Deep Clean to remove. Keep floor surfaces dry and clean to reduce possibility of slip-fall accidents. Routine pressure washing will effect expected wear. Sealer will not prevent surface wear or washing from acids or caustic chemicals.

#### 4. APPLICATION

Read entire label before using. For new installations, sealer can be applied as soon as 48 hours after grouting. Surface must be clean, dry, and free of existing sealers or coatings.

##### A. Application of Product

1. Apply using a sponge, brush, and pait pad, cotton towel, or sprayer.

**Note: Sure that any sealer that does not penetrate surface is polished dry off surface within 5 minutes of application using absorbent paper or cotton towels**

2. If 2 or more coats are applied, allow a minimum of 30 minutes drying time between coats.
3. Read for surface traffic in 12 hours after final coat. Keep dry for 12 hours. Achieves full cure in 48 hours, some highly porous surfaces may require an additional coat after full cure.

##### B. Cleaning

Clean applicator tools with mineral spirits after each use

##### C. Handling and storage

Close container tightly after each use. Store in original container only. Store and use in temperatures between 40° and 90°F (4 °C and 32°C). Unused, stored product is freeze-thaw stable. Dispose of residue or any unused leftover product in accordance with applicable federal, state, and local requirements.

#### 5. AVAILABILITY

Available exclusively at The Tile Shop. Visit [www.tileshop.com](http://www.tileshop.com) to find your nearest location or call 1-888-398-6595 for more information.

#### 6. MAINTENANCE

Grout & Tile Neutral Cleaner or Superior Anti-Bacterial Natural Stone Cleaner is recommended for routine cleaning.

#### 7. TECHNICAL SERVICES

1-888-398-6595