

EXCEL SANDED GROUT

Excel Sanded Grout is our premium grout featuring stain resistance, shrink resistance, and a non-efflorescence formula. This high performance sanded grout is highly durable and may be used on a variety of tile products.

Key Features

- Non-efflorescent
- Rapid setting; “walk-on” ready in 4 hours
- Recommend for joints 1/16” to 1/2”
- Meets or exceeds ANSI Standards 118.7

Related Products

- TruBlue Grout Float
- Spiral Mixer 24”
- Excel Sanded Grout Measuring Pail
- Pro-Sponge
- Bucket 3.5 Gal | 6 Gal

Installation

Sizes: 8 lb. and 25 lb. bags

Mix Ratio: 1.5–1.75 pints per every 8 lbs.

Colors: Antique White, Charcoal, Desert Sand, Dove Grey, Ivory, Linen, London Fog, Mobe Pearl, Mocha, Natural, Standard White, Terracotta, Tobacco, Umber, Whisper Grey

Coverage:

Tile Size	1/8" Joint	3/16" Joint
Mosaics	30 - 50	-
2" x 2"	50 - 60	-
3" x 6"	110	65
4" x 12"	180	110
6" x 24"	270	180
8" x 8"	225	155
8" x 20"	330	225
8" x 36"	360	250
8" x 48"	480	270
12" x 12"	330	225
12" x 24"	450	315
24" x 24"	675	450
Pebbles	Varies by sheet: 20-35	

Application Tips

- Be cautious when using Excel Sanded Grout with polished marble or limestone as Excel contains aggregate which may scratch the surface.
- Do not use Flexible Admixture or other latex products to mix Excel.

Steps to Using Excel Sanded Grout

- 1 Select grout color and add to specified volume of water. Mix until smooth.
- 2 Apply grout and use a grout float at a 45 degree angle to spread and remove excess grout from the face of the tile.
- 3 Use a lightly damp sponge to clean off excess grout from the tile; be sure to avoid watering down the grout which may change the color.
- 4 Let the grout cure for 4 hours. Excel grout is stain resistant without the need for sealing.
- 5 Apply caulk around fixtures, along terminating edges, and any inside corners between tile.

[Always add powder into liquid when mixing.]

