

# EXCEL UNSANDED GROUT

Excel Unsanded Grout is our premium grout featuring stain resistance, shrink resistance, and a non-efflorescence formula. This high performance unsanded grout is highly durable and may be used on a variety of tile products.

## Key Features

- Non-efflorescent
- Non-scratching to soft material such as polished marble, metal, or glass
- Rapid setting; “walk-on” ready in 4 hours
- Recommend for joints 1/16” to 1/2”
- Meets or exceeds ANSI Standards 118.7

## Related Products

- TruBlue Grout Float
- Spiral Mixer 24”
- Excel Unsanded Grout Measuring Pail
- Pro-Sponge
- Bucket 3.5 Gal | 6 Gal

## Installation

**Sizes:** 5 lb. and 20 lb. bags

**Mix Ratio:** 1.5 - 1.75 pints per every 5 lbs.

**Colors:** Antique White, Autumn Wheat, Black Onyx, Charcoal, Desert Sand, Dove Grey, Ivory, Linen, London Fog, Mobe Pearl, Mocha, Natural, Standard White, Terracotta, Tobacco, Umber, Whisper Grey

**Coverage:**

| Tile Size | 1/8" Joint              | 3/16" Joint |
|-----------|-------------------------|-------------|
| Mosaics   | 30 - 50                 | -           |
| 2" x 2"   | 50 - 60                 | -           |
| 3" x 6"   | 110                     | 65          |
| 4" x 12"  | 180                     | 110         |
| 6" x 24"  | 270                     | 180         |
| 8" x 8"   | 225                     | 155         |
| 8" x 20"  | 330                     | 225         |
| 8" x 36"  | 360                     | 250         |
| 8" x 48"  | 480                     | 270         |
| 12" x 12" | 330                     | 225         |
| 12" x 24" | 450                     | 315         |
| 24" x 24" | 675                     | 450         |
| Pebbles   | Varies by sheet: 20- 35 |             |

## Application Tips

- Do not use Flexible Admixture or other latex products to mix Excel.

## Steps to Using Excel Unsanded Grout

- ① Select grout color and mix with specified volume of water. Mix until smooth.
- ② Apply grout and use a grout float at a 45 degree angle to spread and remove excess grout from the face of the tile.
- ③ Use a lightly damp sponge to clean off excess grout from the tile; be sure to avoid watering down the grout which may change the color.
- ④ Let the grout cure for 4 hours. Excel grout is stain resistant without the need for sealing.
- ⑤ Apply caulk around fixtures, along terminating edges, and any inside corners between tile.

*[Always add powder into liquid when mixing.]*

