

LEVEL UNDERLAYMENT

Superior Level Underlayment is a self-leveling underlayment formulated with a blend of Portland and calcium aluminate cements and polymers. Level Underlayment is designed for fast leveling of substrates prior to installing flooring – on, above or below grade. Pourable, Level Underlayment seeks its own level and produces a durable, smooth and flat floor surface with minimum labor.

Key Features

- Single component systems provides a level interior surface
- Rapid setting, walk on ready in 4 hours
- Extended heal allows for raking
- Meets or exceeds ASTM C1708

Installation

Sizes: 55 lb. bag

Mixing Ratio: 5.25 qts. of water per 55 lb.

Coverage: 20-25 sq. ft. at 1/4"

Related Products

- Level Underlayment Measuring Pail
- Spiral Mixer 24"
- Pro-Primer Gallon

Installation Tips

- Level Underlayment is not specified as a structural component of the installation, therefore you must use the correct subfloor and underlayment requirements.
- Each pour should be made into the previous pour within 20 minutes to avoid creating uneven lippage.
- This product is self leveling. Block off or dam any vent, door jams, etc. Caulk or seal voids or cracks.

Steps to Using Level Underlayment

- 1 Apply Primer to floor and allow to dry for 1 hour prior to applying Level Underlayment.
- 2 Mix Level Underlayment 55 lb. bag with 5.25 quarts of water around 2 minutes or until lump free consistency. Using the Level Underlayment measuring pail provides pre-determined holes to assist with mixing.
- 3 Pour mixed Level Underlayment onto the floor starting from an edge or corner and working your way to the exit of the room.
- 4 As needed, mix additional bags of Level Underlayment and begin each successive pour into the existing pour within 20 minutes.
- 5 Allow the Level Underlayment to set for 24 hours prior to tiling or placing a non-breathable covering.

