



1. PRODUCT NAME

Superior Marble Poultice

2. MANUFACTURER

SUPERIOR ADHESIVES & TOOLS
8515 Brown St. Ottawa Lake, MI 49267
CUSTOMER SERVICE
1-888-398-6595
www.superioradhesivesandtools.com

3. PRODUCT DESCRIPTION

Superior Poultice Stain Remover is a dual-purpose, non-acidic problem solver. It is an absorptive clay that is designed to remove deep-set oil and grease stains without scrubbing and a fine abrasive cleaning powder that removes stubborn surface stains and light grout haze.

DESCRIPTION

A. Uses

Designed for use on all natural stone such as granite, marble, slate, limestone, travertine, and quartzite.

B. Features

- Thoroughly cleans without etching or bleaching polished and unpolished stone surfaces
- Non-acidic
- Odorless
- Harmless to most flooring and adjoining surfaces
- Interior and exterior use
- Compliant with all national, state and district VOC regulations

C. Packaging

0.75 lb. container

D. Shelf Life

12 months. Store off the ground and protect from the weather

E. Limitations

Should not be mixed or applied at subfreezing temperatures. Wet poultice will freeze. Cold temperatures adversely affect the cleaning properties of Superior Marble Poultice. Surface and air temperatures should be at least 50° F (10° C). Do not allow product to come in contact with non-recommended surface. Extreme care should be taken with dark marble (especially green) as it may be more sensitive to moisture. Light abrasive action or high RPMs on the surface of some marbles may dull the high-polish finish.

4. APPLICATION

Read entire label before using. Always test a small area of each surface to confirm suitability and desired results before beginning overall application. Let test area dry 3-7 days before inspection and approval.

A. Application of Product

For Removing Deep-Set Oil and Grease Stains:

1. Mix Superior Marble Poultice powder with water to form a thick, pliable paste. Plan for roughly 1 lb. of Superior Marble Poultice for every 3-4 sq. ft. to be cleaned.
2. Apply a ¼-inch-thick (6mm) layer of paste directly over stain with at least a 1-inch (25mm) overlap beyond edge of stain.
3. Cover with plastic or wax paper. Poke a few very small holes in selected cover to allow for minimal air exposure.
4. Allow paste to sit on stain for 24 to 48 hours.
5. Remove Superior Marble Poultice with a plastic spatula or plastic putty knife, and wash off residue with clean water.
6. Repeat procedure as needed.
7. If area darkens from absorbed moisture, it should dry completely in 2 to 4 days.

For Removing Deep-Set Oil and Grease Stains:

1. Protect surrounding areas from splattering to minimize cleanup.
2. Pre-wet a manageable area of the surface with water (approximately 10 sq. ft. or m²) and sprinkle Superior Marble Poultice onto the area, mixing into a thin slurry. If surface is vertical, mix slurry in a container, and apply to a pre-wet surface.
3. Agitate by hand or with a low-RPM buffer (300-750 RPM) using a white nylon scrub pad. Keep surface wet throughout buffing process.
4. Remove Superior Marble Poultice solution with clean towels or sponge, and rinse twice with clean water. A wet-dry vacuum may be used.
5. Polish surface dry with clean, dry towels, or buff with soft lamb's wool pad.
6. Rinse with clean water, and buff dry with clean towels.

B. Handling and Storage

Store in a cool, dry place. Always seal container after dispensing. Do not alter or mix with other chemicals. Published shelf life assumes upright storage of factory-sealed containers in a dry place. Maintain temperature of 45–100° F (7–38° C). Dispose of in accordance with local, state and federal regulations.

5. AVAILABILITY

Available exclusively at The Tile Shop. Visit www.tileshop.com to find your nearest location or call 1-888-398-6595 for more information.

6. MAINTENANCE

Natural stone needs to be cared for properly. Natural stone, tile, grout and masonry will maintain its beauty and last longer, repel stains and soils effectively, when treated with the proper stain protection. Seal stone and grout using Superior sealers and maintain surfaces with Superior cleaners.

7. TECHNICAL SERVICES

1-888-398-6595