

MAXLITE MORTAR

Superior Maxlite Mortar is a lightweight, high-performance polymer-modified thinset with premium workability for a broad range of tile installations. This innovative formula offers non-slump characteristics for large and heavy tile. Maxlite Mortar is an ideal choice for most installations due to its unique blend of advanced polymers and lightweight aggregate.

Key Features

- Interior and exterior use; suitable for residential and commercial construction
- Excellent non-sag properties
- Lightweight thinset exceeding industry standards
- Easy to mix and apply, smooth and easy to install
- Meets or exceeds ANSI standards 118.4 & 118.11

Installation

Sizes: 30 lb. bag

Colors: White

Mixing Ratio: 5 - 5.25 qts. of water per 30 lb.

Coverage: Approx. 80 sq. ft. per 30 lb.

- 1/4" sq. notch trowel: 75 sq. ft.
- 3/8" sq. notch trowel: 60 sq. ft.
- 1/2" sq. notch trowel: 30 sq. ft.

Performance

Open Time: 30 minutes

Working Time: 30 minutes

Pot Life: Approx. 3 hours

Shelf Life: 15 months. Store in cool, dry location.

Related Products

- Spiral Mixer 24"
- Bucket 3.5 Gal | 6 Gal
- Margin Trowel

Steps to Using Maxlite Mortar

- ① Use approx. 5 - 5.25 qts. of clean water per 30 lb. of powder.
- ② Pour powder into the bucket of water until the water forms a ring around the powder.
- ③ Use a spiral mixer to mix the thinset to a "whip cream" consistency. Let it slake for 5 minutes, then mix again.
- ④ Use product within pot life. Do not re-temper*. If thinset is no longer workable, discard the thinset and mix a new batch.

*Add additional water and re-mix after initially activating product.

[Always add powder into liquid when mixing.]



SUPERIOR
ADHESIVES & TOOLS

03.19.2024

<https://www.tileshop.com/superior-adhesives-and-tools>