PLATINUM MORTAR

Superior Platinum Mortar is a premium, latex-modified thinset ideal for installation of ceramic, porcelain, and natural stone. The naturally smooth and creamy formulation enables exceptional open time and installed tile adjustability, plus is great for large bodied tiles for floors.

Key Features

- Interior and exterior use; suitable for residential and commercial construction
- Full contact mortar perfect for flooring applications
- Premium multi-purpose thinset
- Consistent high performance
- Easy to mix and apply; smooth and easy to install
- Meets or exceeds ANSI standards 118.4 & 118.11

Installation

Sizes: 50 lb. bag

Colors: White

Mixing Ratio: 5 - 6 qts. of water per 50 lb.

Coverage: Approx. 80 sq. ft. per 50 lb.

1/4" sq. notch trowel: 75 sq. ft.
3/8" sq. notch trowel: 60 sq. ft.
1/2" sq. notch trowel: 30 sq. ft.

Related Products

- Spiral Mixer 24"
- Bucket 3.5 Gal | 6 Gal
- Margin Trowel

Performance

Open Time: 20 - 30 minutes Pot Life: Approx. 3 hours

Working Time: 20 - 30 minutes Shelf Life: 15 months. Store in cool, dry location.

Steps to Using Platinum Mortar

- 1 Use approx. 5 6 qts. of clean water per 50 lb. of powder.
- Pour powder into the bucket of water until the water forms a ring around the powder.
- Use a spiral mixer to mix the thinset to a "cake batter" consistency. Let it slake for 5 minutes, then mix again.
- Use product within pot life. Do not re-temper*. If thinset is no longer workable, discard the thinset and mix a new batch.

*Add additional water and re-mix after initially activating product.

[Always add powder into liquid when mixing]



