1. PRODUCT NAME

Superior Pro-Primer

2. MANUFACTURER

SUPERIOR ADHESIVES & TOOLS 8515 Brown St. Ottawa Lake, MI 49267 CUSTOMER SERVICE 1-888-398-6595 www.superioradhesivesandtools.com

3. PRODUCT DESCRIPTION

Superior Pro-Primer is a premium blend of acrylic co-polymers designed to give maximum adhesion when used with the Superior Pro-Level system. Superior Pro-Primer is designed to improve the bond of underlayments.

DESCRIPTION

- A. Uses
 - Designed for use with Superior thinsets and Superior Pro Level.
- B. Features
 - Improved bond
 - Protects underlayment from absorbing excess moisture from substrates
 - Interior or Exterior applications
- C. Packaging

1 gal. container

- D. Shelf Life
 - 6 months. Store off the ground and protect from the weather
- E. Limitations

Shake well before using. Clean all tools with soap and water. Keep from freezing. Portland cement is high alkaline – avoid contact with eyes and prolonged contact with skin. Flush contact areas thoroughly.

4. APPLICATION

Read entire label before using. All surfaces must be structurally sound, clean, dry and free of surface contaminates such as dirt, grease, oil, curing compounds, sealers, adhesives and/or any contaminates that can impede bonding of Pro-Primer to substrate.

A. Application of Product

- 1. Apply Superior Pro-Primer with a stiff broom, roll or brush evenly over substrate. Do not allow puddling.
- 2. Allow to dry to a clear film (approximately 1-3 hours depending on conditions).
- 3. 2 coats are recommended, however, when using Superior Pro-Primer over highly porous substrates like concrete, a second coat is necessary.
- 4. Approximate coverage is 400 sq ft (37m²) per coat depending on porosity.

B. Cleaning

Clean all tools with soap and water while still wet.

C. Handling and Storage

Close container after each use. Store in original container only. Keep from freezing.



SUPERIOR

 $\label{eq:stable} A vailable \, exclusively at The Tile \, Shop. Visit \, www.tileshop.com \, to \, find \, your \, nearest \, location \, or \, call \, 1-888-398-6595 \, for more \, information.$

6. MAINTENANCE

Superior installation products require no long-term maintenance, but installation performance and durability may depend on proper maintenance of other products used during installation.

7. TECHNICAL SERVICES

1-888-398-6595