



1. PRODUCT NAME

Superior Pro Strip

2. MANUFACTURER

SUPERIOR ADHESIVES & TOOLS
8515 Brown St. Ottawa Lake, MI 49267
CUSTOMER SERVICE
1-888-398-6595
www.superioradhesivesandtools.com

3. PRODUCT DESCRIPTION

Superior Pro Strip is a concentrated, environmentally friendly, water-based, multi-purpose coating and sealer remover formulated to strip most topical sealers, urethane coatings, acrylic finishes, wax coatings, paints, adhesives, graffiti and epoxy grout haze. Pro Strip GR stays wet longer, resulting in increased dwell times to remove coatings.

DESCRIPTION

A. Uses

Designed for ceramic, porcelain, unpolished natural stone, grout, concrete, masonry and metal horizontal and vertical surfaces.

B. Features

- Used for stone, masonry, and grout
- Quick acting
- Long lasting
- Environmentally friendly
- Deep Cleans
- Highly Concentrated
- VOC compliant in all 50 states
- Interior and exterior use

C. Packaging

32 oz. container

D. Shelf Life

12 months. Store off the ground and protect from the weather

E. Limitations

Do not spray, use on synthetic agglomerates or polished marble or allow remover to come in contact with any surrounding surfaces.



4. APPLICATION

SHAKE WELL. Read entire label before using. Always pre-test this product in an inconspicuous area to ensure product performance and satisfaction. Users must determine suitability of product for their intended use. Always cover and protect surfaces not intended to be cleaned.

A. Application of Product

1. Sweep or vacuum surface.
2. Apply a liberal amount of Superior Pro-Strip to a small manageable area of up to 20 sq. ft.
3. Allow Superior Pro Strip to dwell up to 2 hours on the surface without drying or until coating or residue softens. Prevent drying by adding more stripper if needed.
4. Agitate with a scrub brush or a floor scrubbing machine.
5. Wipe up residue with clean white absorbent towels, sponges or wet vacuum.
6. Rinse thoroughly with clean water.
7. Removal of thicker coatings may require several applications. Repeat steps 1 through 6 as needed.
8. Allow 24 hours before applying Superior sealers and floor finishes.

B. Handling and Storage

Close container after each use and store in original container only. Store between 50°F and 80°F and out of direct sunlight. In case of spillage, absorb with sawdust, sand or clay litter. Dispose of residue or any unused leftover product in accordance with applicable federal, state and local regulations. Unused, stored product is freeze-thaw stable

5. AVAILABILITY

Available exclusively at The Tile Shop. Visit www.tileshop.com to find your nearest location or call 1-888-398-6595 for more information.

6. MAINTENANCE

Natural stone needs to be cared for properly. Natural stone, tile, grout and masonry will maintain its beauty and last longer, repel stains and soils effectively, when treated with the proper stain protection. Seal stone and grout using Superior sealers and maintain surfaces with Superior cleaners.

7. TECHNICAL SERVICES

1-888-398-6595