

# UNSANDED GROUT

Superior Unsanded Grout is a durable, easy-to-use formula that is crack resistant. As this grout does not include an aggregate, it is recommended for grout joints 1/8" and less as well as surfaces prone to scratches such as glass and metal.

## Key Features

- Polymer-modified shrink resistant formula
- Smooth grout lines
- Non-scratching to soft materials such as polished marble, metal or glass
- Meets or exceeds ANSI Standards 118.6

## Related Products

- TruBlue Grout Float
- Spiral Mixer 24"
- Grout Admixture
- Pro-Sponge
- Bucket 3.5 Gal | 6 Gal

## Installation

**Sizes:** 5lb. and 20lb. bags

**Mix Ratio:** 1 - 1.5 pints per every 5 lbs.

**Colors:** Almond, Antique White, Autumn Wheat, Black Onyx, Brilliant White, Charcoal, Desert Bloom, Desert Sand, Dove Grey, Ivory, Kahlua Cream, Linen, London Fog, Milk Chocolate, Mobe Pearl, Mocha, Sand Beige, Standard White, Tobacco, Whisper Grey

### Coverage:

Tile Size	1/8" Joint
Mosaics	30 - 50
2" x 2"	50 - 60
3" x 6"	110
4" x 12"	180
6" x 24"	270
8" x 20"	330
8" x 36"	360
8" x 48"	480
12" x 12"	330
12" x 24"	450

## Application Tips

- Flexible Admixture is recommended with Unsanded Grout to reduce cure time from 30 days to 48-72 hours.
- Admixture will also help maintain color consistency and increase resistance to movement.

## Steps to Using Unsanded Grout

- 1 Select grout color and add to specified volume of Flexible Admixture using a margin trowel or spiral mixer to avoid over-mixing.
- 2 Apply grout and use a grout float at a 45 degree angle to spread and remove excess grout from the face of the tile.
- 3 Use a damp sponge to clean off excess grout from the tile; be sure to avoid watering down the grout which may change the color.
- 4 Let the grout cure for 48–72 hours (if using Admixture) prior to applying sealer to the grout. Seal stone tile depending on customer selections.
- 5 Apply caulk around fixtures, along terminating edges, and any inside corners between tile.

*[Always add powder into liquid when mixing.]*

