

MSI

Making Dream Surfaces Attainable

The Tile Shop



UNDERLAYERMENT

for Floating Vinyl Flooring

AbaTec™


Underlayment for Floating Vinyl Flooring

1.5 mm
200 sq.ft.



The Tile Shop

1. 3X SIMPLER TO INSTALL



2. LAY FLAT



3. CUT



2. PROTECTS THE FLOOR

Supports the floor locking system



Helps smooth out minor subfloor imperfections



AbaTec™ surface helps prevent planks from sliding



3. IMPROVES COMFORT

Reduces walking noise in room



Reduces impact sound in room below



Shock-absorbing flooring structure



Dimensions	1.19 m x 7.83 m / 3.9 ft x 25.7 ft.	Compression Strength	> 64 PSI
Moisture Protection	< 0.16 pounds / 24 hr / 1,000 sq.ft.	Safety	Odorless, non toxic
Impact Sound Insulation	IIC ~ 72 / STC ~ 66/DELTA 26	Compatibility with underfloor heating	Yes
Thermal Insulation	R-Value 6.6 per inch	Item number	73631-US
Smoothing	1.0 mm	Don't forget the moisture resistant tape (not included)	

INSTALLATION INSTRUCTIONS:

Step 1: Ensure the floor is clean and dry before installing underlayment.

Step 2: Starting in a corner, install the first row of underlayment with moisture barrier facing upward. Install the underlayment to the wall and trim around any obstacles.

Step 3: Align the second row of underlayment to the first row ensuring there are no gaps or overlapping seams. Secure all underlayment seams with an aggressive moisture resistant tape. (not included).

Step 4: Repeat this process until the entire floor is covered.

Step 5: Install the flooring per the manufacturer's instructions.

TECHNICAL SPECIFICATIONS:

Moisture Protection	<0.16 pounds/24 hr/1,000 sq.ft.
Impact Sound Insulation	IIC ~ 72 / STC ~ 66 / DELTA 26
Thermal Insulation	R-Value 6.6 per inch
Smoothing	1.0 mm
Compression strength CS	>65 PSI

PRODUCT DATA:

Thickness	1.5 mm
Dimensions	1.19m x 7.83m / 3.9 ft. x 25.7 ft.
Package Contents	100. sq.ft.

INSTRUCCIONES DE INSTALACIÓN:

Paso 1: Asegúrese de que el piso esté limpio y seco antes de instalar el contrapiso.

Paso 2: Comenzando en una esquina, instale la primera fila de contrapiso con la barrera contra la humedad hacia arriba. Instale el contrapiso en la pared y recorte alrededor de los obstáculos.

Paso 3: Alinee la segunda fila de contrapiso con la primera fila asegurándose de que no haya espacios o costuras superpuestas. Asegure todas las costuras del contrapiso con una cinta adhesiva resistente a la humedad agresiva. (no incluida).

Paso 4: Repita este proceso hasta que se cubra todo el piso.

Paso 5: Instale el piso según las instrucciones del fabricante.

ESPECIFICACIONES TÉCNICAS:

Protección contra la humedad	<0.16 libras/24 hr/1,000 sq.ft.
Aislamiento de sonido de impacto	IIC ~ 72 / STC ~ 66 / DELTA 26
Aislamiento térmico	R-Valor 6.6 por pulgada
Suavizado	1.0 mm
Resistencia a la compresión CS	>65 PSI

DATOS DEL PRODUCTO:

Espesor	1.5 mm
Dimensiones	1.19m x 7.83m / 3.9 ft. x 25.7 ft.
Contenidos del paquete	100. sq.ft.

