



Purpose: To remove adhesive or tile mastic from tile or stone surfaces

Product Recommendation: Superior Pro-Strip®

Equipment: Black Scrub brush or nylon scrub pad, scraper and white cotton towels

Coverage: Approximately 75 - 100 sq. ft. (7 m² - 10 m²) per gallon (3.785 L)

Procedure:

1. **Always test a small area first to ensure satisfactory results.**
2. Sweep or vacuum surface.
3. Apply **Sealer & Coating Remover** to a small manageable area up to 25 sq. ft. (2.5 m²)
4. Allow to dwell up to 2 hours without drying or until coating or residue softens.
5. Agitate with scrub brush or nylon scrub pad. A scraper may be used for removal of thick residue.
6. If necessary, apply additional remover or sprinkle with hot water and agitate with a scrub brush.
7. Remove residue and wipe surface dry using clean, absorbent white cotton towels.
8. Rinse thoroughly with clean water.
9. Repeat procedures if necessary.

Note A: Do not use on synthetic agglomerate or other resinous surfaces.

Note B: Sealer & Coating Remover will remove sealers and wax-type coatings.

Technical Assistance:

1. Call 888-398-6595 Monday through Friday, 7:00 a.m. to 4:30 p.m. CST Time.
2. E-mail technical questions to Customerhelp@tileshop.com; Visit our website at www.tileshop.com

