

## Method A

## For removal of Superior® <u>Enhance 'N' Seal</u> residue within 48 hours of application Product Recommendation: Superior® Stone Deep Clean

**Equipment:** Black Nylon scrub brush, mop and bucket with wringer or wet/dry vacuum *Optional*: For large installations a low RPM (150-350 RPM) floor machine may be used fitted with a soft to medium bristle brush or hogs hair pad

**Coverage:** Approximately 150 - 300 sq. ft.  $(14 \text{ m}^2 - 28 \text{ m}^2)$  per gallon (3.785 L) of diluted product

#### **Procedure:**

#### 1. Always test a small area first.

- 2. Mix one part Stone Deep Clean to two parts water.
- 3. Apply solution onto surface and allow to dwell for 5 to 10 minutes.

4. Agitate by hand with scrub brush or with floor machine. Keep surface wet throughout process.

5. Remove solution with mop or wet/dry vacuum.

6. Rinse several times with clean water and allow to dry.

#### Method B

### For removal of Aqua Mix <u>Enhance 'N' Seal</u> or <u>Seal</u> residue after 48 hours of application Product Recommendation: Superior® Pro-Strip (NOTE C)

**Equipment:** Black Nylon scrub pad or natural-bristle scrub brush, mop and bucket with wringer or wet/dry vacuum

*Optional*: For large installations a low RPM (150-350 RPM) floor machine may be used fitted with a soft to medium bristle brush or hogs hair pad

**Coverage:** Approximately 75 - 200 sq. ft.  $(7 \text{ m}^2 - 19 \text{ m}^2)$  per gallon (3.785 L)

#### **Procedure:**

#### 1. Always test a small area first.

- 2. Apply a liberal amount of **Pro Strip** to a small, manageable area of up to 25 sq. ft. (2 m<sup>2</sup>)
- 3. Allow to dwell for up to 2 hours for residue to soften.
- 4. Agitate by hand with scrub brush or with floor machine.
- 5. If necessary, apply small amounts of additional remover or apply more water.
- 6. Remove solution with mop or wet/dry vacuum.
- 7. Rinse several times with clean water and allow to dry.

**NOTE C:** Do not use Pro Strip on synthetic agglomerate or other resinous surfaces.

This recommendation is intended as a guideline for the removal of **Enhance 'N' Seal** or **Sealer** residue. The actual cleaning requirements may vary depending on type of tile, method of application, texture of stone and amount of residue.

#### READ PRODUCT DIRECTIONS THOROUGHLY PRIOR TO USE.

# TTS: 2008 Removal of Enhance-N-Seal



# **Technical Assistance:**

1. Call 888-398-6595 Monday through Friday, 7:00 a.m. to 4:30 p.m. CST Time.

2. E-mail technical questions to <u>Customerhelp@tileshop.com</u>; Visit our website at <u>www.tileshop.com.com</u>.