



Purpose: To remove sealers on tile or stone surfaces

Product Recommendation: Superior Pro-Strip®

Equipment: Rubber gloves, scrub brush, black nylon scrub pad or scrub machine and white cotton towels or sponges

Coverage: Approximately 75 - 200 sq. ft. (7 m² - 20 m²) per gallon (3.785 L)

Procedure:

1. **Always test a small area first to ensure satisfactory results.**
2. Sweep or vacuum surface.
3. Apply a liberal amount of undiluted **Pro-Strip** to a small, manageable area of up to 25 sq. ft. (2.5 m²).
4. Allow to dwell up to 2 hours without drying or until coating or residue softens. Reapply if necessary until sealer softens and can be removed.
5. If necessary, apply additional remover or sprinkle with hot water and agitate with a scrub brush.
6. If scrub machine is used, apply hot water to surface immediately prior to scrubbing.
7. Wipe up residue with absorbent white cotton towels or sponge.
8. Rinse thoroughly with clean water.

Technical Assistance:

1. Call 888-398-6595 Monday through Friday, 7:00 a.m. to 4:30 p.m. CST Time.
2. E-mail technical questions to Customerhelp@tileshop.com; Visit our website at www.tileshop.com



Nylon Scrub Brush



Nylon Scrub Pad



Rubber Gloves



Sponge

