



# THINSET RECOMMENDATION

 		ARDEX WA™	ARDEX X 77™	SUPERIOR MAXLITE	SUPERIOR PRO BOND LFT	SUPERIOR PRO-LASTIC A & B	SUPERIOR PRO-FLEX ACCELERATED	ARDEX X 5™	ARDEX X 4™	SUPERIOR PRO-BOND	SUPERIOR PRO-FLEX PLATINUM	ARDEX X 3™	SUPERIOR PRO-FLEX
MATERIAL	Natural Stone	√	√	√	√	√	√	√	√	√	√	√	√
	Ceramic, Cement Encaustic & Quarry	√	√	√	√	√	√	√	√	√	√	√	√
	Porcelain	√	√	√	√	√	√	√	√	√	√	√	
	Glass	√	√	√	√	√	√						
	Large Format and Heavy Tile		√	√	√			√	√				
	Green & Black Marble, Resin Backed Stone	√											
	Large Format Glass	√	√*										
INSTALL	Concrete Subfloor, Cement Board, In-Floor Heat, Over Drywall, Uncoupling Membrane	√	√	√	√	√	√	√	√	√	√	√	√
	Tile Over Tile	√	√*	√	√	√	√	√*	√*			√*	
LOCATION	Wet Area	√	√	√	√	√	√	√	√	√	√	√	
	Exterior	√	√	√	√	√	√	√	√			√	
	Pool/Fully Submerged, Steam Shower	√	√*	√	√	√							
	Commercial/High Traffic	√	√	√	√		√	√	√			√	
CV	Est. Coverage with ¼"×¼" Trowel (In Square Feet)	19.5	110	80	100	80	40	90	90	80	80	80	80
	Package Size	8.8	40 LBS	30 LBS	50 LBS	50 LBS	25 LBS	40 LBS	40 LBS	50 LBS	50 LBS	40 LBS	50 LBS

Pro-Mastic available for wall installations in dry areas.

\*Install using Ardex's installation guidelines

# TROWEL RECOMMENDATION

APPLICATION	Mesh Mosaics	4 inch - 11 inch	12 inch - 15 inch	16 inch or larger	Tile thicker than 3/8 inch	Ungauged Tile	Underlayment
TROWEL SIZE (Based on largest dimension)	3/16 inch V-notch	1/4 inch square	3/8 inch square	1/2 inch square or U-notch	1/2 inch square or U-notch	1/2 inch square or U-notch	1/4 inch square