

Section 1 – Identification

SUPPLIER:	Superior Adhesives & Tools	NOTE: Blank spaces are not permitted. If no relevant information is found for any given subheading within a section, the SDS shall clearly indicate that no applicable information is available.	
ADDRESS:	14000 Carlson Parkway Plymouth, MN 55441	Emergency Telephone Number (CHEMTREC)	(800) 424-9300
		Telephone Number for Information	(888) 398-6595
TELEPHONE:	888-398-6595	Recommended use of the chemical and restrictions on use: This product consists of silica sand, finely ground Portland cement, cement alumina, ground limestone, gypsum and other fillers. This product is used to fill in the spaces between the tiles. Avoid dust formation. Do not breathe dust. Avoid contact with acids.	
Product Identifier (as used on Label, SDS and list) Pro Grout Unsanded is available in several colors with only minor differences in constituents. Therefore, this SDS is the same for all colors. Also known as Pro Grout Unsanded 25# bag, and Pro Grout Excel 5# bag Other means of identification: none			

Section 2 – Hazard Identification

Acute inhalation toxicity	Category: 2	Signal Word: DANGER
Known or presumed human carcinogen	Category: 1A	Signal Word: DANGER
Skin irritation, Category	Category: 2	Signal Word: WARNING
Eye irritation, Category	Category: 2A	Signal Word: WARNING
Target Organ Toxicity, Category	Category: 2	Signal word: WARNING



Hazard Statements: FATAL IF INHALED; CAUSES SERIOUS EYE IRRITATION; CAUSES SKIN IRRITATION; MAY CAUSE CANCER; MAY CAUSE DAMAGE TO ORGANS

Precautionary Statements:

PREVENTION: Do not breathe dusts; use only outdoors or in a well-ventilated area
Wash thoroughly after handling
Obtain special instructions before use
Do not eat, drink or smoke when using this product
Do not handle until all safety precautions have been read and understood
Wear protective gloves/protective clothing/eye protection/face protection
In case of inadequate ventilation wear respiratory protection.

RESPONSE: If inhaled: Remove person to fresh air and keep comfortable for breathing
Immediately call a poison control center or doctor
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Specific treatment is urgent. (See First Aid Measures)
If on skin: Wash with plenty of water. If skin or eye irritation occurs/persists: Get medical advice/attention
If exposed or concerned: Call a poison center/doctor.
Take off contaminated clothing and wash it before reuse

STORAGE: Store locked up in a well-ventilated place with container tightly closed.

DISPOSAL: Do not dispose of in compactors or any other trash bins where compression is possible. Dispose of per federal, state, and local regulations.

Section 3 – Composition/Ingredients (*= trade secret)

Chemical Name	Common Name and synonyms	CAS No.	Percentage
Portland Cement	Hydraulic cement binder	65997-15-1	20-50
Crystalline Silica	Silica sand, ground silica, quartz	14808-60-7	30-50
Calcium Carbonate	Ground limestone	1317-65-3	1-15
Titanium Dioxide	Tioxide	12188-41-9	0.1-1
Lithium Carbonate	Carbonic acid, dilithium salt, dilithium carbonate	554-13-2	0.1-1
Other components below reportable levels.	Not applicable	Not applicable	1-35

May contain trace amounts of the following substances: Pro Grout unsanded contains no more than 3.5% crystalline silica of which a portion is natural sand.

Section 4 – First Aid Measures

INHALATION: If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor. Inhalation of large amounts of Pro Grout unsanded requires immediate medical attention.

SKIN CONTACT: If on skin, wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Seek medical treatment in all cases of prolonged wet skin exposure to Pro Grout unsanded. Take off contaminated clothing and wash it before reuse.

EYE CONTACT: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

INGESTION: If swallowed: Call a poison center/doctor. Do not induce vomiting. Rinse mouth. May cause burns to mouth, throat and stomach.

MOST IMPORTANT SYMPTOMS/EFFECTS: Acute: May cause mild or severe irritation. Exposure to airborne dust may cause immediate or delayed irritation or inflammation.

Delayed: Prolonged exposure can cause severe skin damage in the form of caustic chemical burn. An allergic response is possible.

IMMEDIATE MEDICAL ATTENTION/SPECIAL TREATMENT: Emergency Medical Services/Poison Control Center

Section 5 – Fire-Fighting Measures

SUITABLE EXTINGUISHING MEDIA: Pro Grout unsanded does not pose a fire hazard, however normal fires can be extinguished using water mist, CO₂, or Dry Chemical (AB, BC, ABC) extinguishers

SPECIAL FIRE-FIGHTING PROCEDURES: Wear self-contained breathing apparatus with full-face mask and fire-fighter protective clothing when fighting fires.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

Pro Grout unsanded	
HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARDS	0

NFPA Rating: Health: 3 Flammability: 0 Reactivity: 0

Section 6 – Accidental Release Measures

PERSONAL PRECAUTIONS: Avoid actions that cause dust to become airborne. Avoid inhalation of dust and contact with skin.

PROTECTIVE EQUIPMENT: In case of exposure to dust above the PEL, wear appropriate respiratory protection. If eye contact while using this product is anticipated, wear ANSI Z87 approved goggles or safety glasses. Wear chemical resistant gloves (such as nitrile or neoprene) and protective clothing to minimize skin contact.

EMERGENCY PROCEDURES: None

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP: Collect dry material using a scoop. Scrape up wet material and place in an appropriate container. Allow the material to dry before disposing. **DO NOT** attempt to wash Pro Grout unsanded down drains.

Section 10 – Stability and Reactivity	
REACTIVITY: None	
CHEMICAL STABILITY: Stable under normal conditions	
POSSIBILITY OF HAZARDOUS REACTIONS: Avoid mixing with acids	
CONDITIONS TO AVOID: Releasing dust. Unintentional mixing with water	
INCOMPATIBLE MATERIALS: Acids, ammonium salts and aluminum metal. Pro Grout unsanded will dissolve in hydrofluoric acid producing toxic and corrosive silicon tetrafluoride gas. Contact with acids may also produce carbon dioxide gas.	
HAZARDOUS DECOMPOSITION PRODUCTS: Will not spontaneously occur. Calcium sulfate decomposes to Calcium Oxide and (CaO) and Sulfur Dioxide (SO ₂) above 1340°C	

Section 11 – Toxicological Information	
Routes of Entry: Inhalation: YES Ingestion: YES Eye: YES Skin: YES	
SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS: May cause mild or severe irritation. Prolonged exposure can cause severe skin damage in the form of caustic chemical burn. An allergic response is possible. Pro Grout unsanded may cause abrasion of the cornea.	
IMMEDIATE AND DELAYED EFFECTS: Exposure to airborne dust may cause immediate or delayed irritation or inflammation. Small quantities of dust are not known to be harmful, however ill effects are possible if large quantities are consumed. Pro Grout unsanded should not be eaten.	
CHRONIC EFFECTS FROM SHORT-TERM AND LONG-TERM EXPOSURE: May cause mild or severe irritation. Prolonged exposure can cause severe skin damage in the form of caustic chemical burn. An allergic response is possible. Silicosis. A major concern is inhalation of silicon dioxide. Chronic or Ordinary Silicosis (often referred to as Simple Silicosis) is the most common form of silicosis and can occur after many years of exposure to relatively low levels of airborne respirable crystalline silica dust. Simple silicosis is characterized by lung lesions (shown as radiographic opacities) less than 1 cm in diameter, primarily in the upper lung zones. Often, simple silicosis is not associated with symptoms, detectable changes in lung function or disability. Simple silicosis may be progressive and may develop into complicated silicosis or progressive massive fibrosis (PMF). Although there may be no symptoms associated with PMF, the symptoms, if present, are shortness of breath, wheezing, cough and sputum production. PMF may be associated with decreased lung function and may be disabling. Advanced complicated silicosis or PMF may result in heart disease secondary to the lung disease. Autoimmune diseases. Several studies have reported excess cases of several autoimmune disorders – scleroderma, systemic lupus erythematosus, rheumatoid arthritis – among silica-exposed workers.	
LC50/LD50: Oral LD50, rat: Not determined Oral LD50, rabbit: Not determined Inhalation LC50, mouse: Not determined Dermal LD50, rat: Not determined	
Carcinogenicity: YES. The International Agency for Research on Cancer (IARC) concluded that there was “sufficient evidence” in humans for the carcinogenicity of crystalline silica (Group 1) in the forms of quartz or cristobalite from occupational sources. The overall IARC evaluation was that “crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1). The IARC evaluation noted that carcinogenicity was not detected in all industrial circumstances. The National Toxicology Program (NTP) classifies respirable crystalline silica as Known to be a Human Carcinogen.	

Section 12 – Ecological Information (Non-mandatory)		
ECOTOXICITY: No recognized unusual toxicity to plants or animals	BIO ACCUMULATIVE POTENTIAL: None	OTHER ADVERSE EFFECTS (such as hazardous to the ozone layer): None known
PERSISTENCE AND DEGRADABILITY: Stable under normal conditions	MOBILITY IN SOIL: Minimal to low	

Section 13 – Disposal Considerations (Non-mandatory)

WASTE DISPOSAL OF SUBSTANCE: Do not discharge into waterways, drains, or sewer systems.

CONTAINER DISPOSAL: Dispose of in accordance with federal, state and local regulations.

RCRA: None listed

Section 14 – Transport Information (Non-mandatory)

DOT, IATA, IMO/IMDG SHIPPING INFORMATION

UN Identification Number: N/A

DOT Shipping Name: N/a

Hazard Class: N/A

IMDG-P.S.N.: N/A

IATA-P.S.N.: N/A

IMDG-Class: N/A

IATA-CLASS: N/A

IMDG-Marine Pollutant: No

IATA-Packing Group: N/A

IMDG-Packing Group: N/A

Section 15 – Regulatory Information (Non-mandatory)

U.S. SARA REPORTING REQUIREMENTS: The components of this mixture are not subject to the reporting requirements of Sections 302, 304 and 313 of Title II of the Superfund Amendments and Reauthorization Act.

SARA 311/312: Immediate and Delayed Health effects; Yes Fire Hazard; No Pressure; No

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for the components of this product. The default Federal SDS submission and inventory requirement filing threshold of 10,000 lbs (4,540 kg) therefore applies, per 40 CFR 370.20

U.S. CERCLA REPORTABLE QUANTITY (RQ): None

U.S. TSCA INVENTORY STATUS: Crystalline silica (quartz), CAS# 14808-60-7; lithium carbonate, CAS# 554-13-2; limestone, CAS# 1317-65-3 are listed on the TSCA inventory

TSCA SIGNIFICANT NEW USE RULE: None of the chemicals in this mixture have a SNUR under TSCA.

CLEAN AIR ACT: This material does not contain any hazardous air pollutants
This material does not contain any Class 1 Ozone depletors
This material does not contain any Class 2 Ozone depletors

CLEAN WATER ACT: None of the chemicals in this mixture are listed as Hazardous Substances under the CWA
None of the chemicals in this mixture are listed as Priority Pollutants under the CWA
None of the chemicals in this mixture are listed as Toxic Pollutants under the CWA

OSHA: None of the chemicals in this mixture are considered highly hazardous by OSHA

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): This product contains 3.5% a chemical, crystalline silica (airborne particles of respirable size), classified as a substance known to the state of California to be a carcinogen.

California No Significant Risk Level: None of the chemicals in this product are listed.

California Inhalation Reference Exposure Level (REL): California established a chronic REL of 3 ug for silica (crystalline, respirable). A chronic REL is an airborne level of a substance at or below which no adverse health effects are anticipated in individuals indefinitely exposed to the substance at that level.

OTHER STATE SPECIFIC REGULATIONS:

Massachusetts Toxic Use Reduction Act: Silica, crystalline (respirable size, <10 microns) is "toxic" for purposes of the Massachusetts Toxic Use Reduction Act.

Pennsylvania Worker and Community Right to Know Act: Quartz is a hazardous substance under the Act but it is not a special hazardous substance or an environmental hazardous substance.

Section 16 – Other Information

PREPARED BY: Bryan Cleavenger

DATE PREPARED: May 26, 2015

LAST UPDATED: 2018, November 18

EMAIL ADDRESS: Bryan@Cleavengercompliance.com

TRAINING NECESSARY:	Yes. Training under the OSHA HazCom GHS requirements (29 CFR 1910.1200) must be completed upon initial assignment for new employees.
INTENDED USE OF THIS PRODUCT:	This product is intended for use by skilled individuals at their own risk. The information contained herein is based on data considered accurate based on current state of knowledge and experience. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Superior Adhesives & Tools. The data on this sheet is only related to the specific material designated herein. Superior Adhesives & Tools assumes no legal responsibility for use or reliance on this data.