

ARDEX WA™

Epoxy Grout and Adhesive

A revolutionary solvent-free, two-component epoxy grout and adhesive with a unique creamy consistency. It is particularly suited for installations in swimming pools, hot tubs, showers, bathrooms, breweries, food processing facilities, industrial, restaurant kitchens, hospitals or any installation requiring high standards of hygiene and chemical resistance. Use for setting all types of tile including glass tile.

So easy to apply and clean you won't believe it's an epoxy!

Key Features

- Two-components
- Clean with water only
- Interior and exterior floor and wall applications
- Waterproof and frost resistant
- Available in 35 ARDEX colors
- 100% solids


Installation

- **Packaging:** Approx. 9 lb. (4.08 kg) net weight tub
- **Open Time:** Approx. 1 hour
- **Pot Life:** Approx. 40 minutes
- **Working Time:** Approx. 1 hour
- **Time to Grout:** 12 hours
- **Open to Traffic:**
 - 12 hours: Light foot traffic
 - 2 days: Full traffic loads
 - 7 days: ARDEX WA can be submerged and is resistant to aqueous salt solutions, chlorine water, swimming pool detergents, standard commercial and domestic cleaning agents, alkalis and a wide range of dilute mineral acids.

- For grout joints up to 1/2" (12 mm) wide



Performance



SystemOne



AMERICAS

888-512-7339
www.ardexamericas.com

AF 104 E (09/2014)

ARDEX GROUTS