ENHANCE AND SEAL

Enhance & Seal is a matte enhancer that penetrates deep into porous materials to give a "wet" look. This sealer can be used on all unsealed natural stones, where a deeper or higher contrast color is desired.

Key Features

- Provides a non-slip "wetlook"
- Seals stone from moisture absorption and staining
- Traffic-ready in 24 to 72 hours

Installation

Packaging: 16 oz. and 32 oz.

Coverage: 1 pint will cover 30 – 125 sq. ft. A quart will cover 75 – 200 sq. ft. A gallon will cover 300 – 1000 sq. ft

Related Products

- Sealer Sponge
- Tile & Grout Maintenance Kit

Application Tips

- Use heavy duty cleaner to remove waxes or coatings
- Seal stone with Enhance & Seal prior to grouting
- If a wax or film forms, apply more sealer to re-activate and be sure to buff completely dry
- Apply "wet-on-wet" with a sponge, apply 2nd coat before 1st dries
- Test a small area and allow to cure 24 hours to ensure desired result is achieved

Steps to Apply Sealer

Prepare a clean dry surface free of any dirt, dust, waxes, or coatings.

(2)

์ 3 Apply 1 - 2 coats using a Sealer Sponge.

Use an absorbent towel to remove and polish any sealer that does not penetrate within 5 – 10 minutes.



Apply "wet-on-wet" with a sponge, apply second coat before first coat dries.

5 After a minimum of 2 hours, test to determine if the surface is completely sealed.





UPERIOR

*=