

MAXLITE

MAXLITE is a lightweight, high-performance polymer-modified thinset with premium workability for a broad range of tile installations. This innovative formula offers non-s slump characteristics for large and heavy tile. MAXLITE is an ideal choice for most installations due to its unique blend of advanced polymers and lightweight aggregate.

Key Features

- Interior and Exterior use; suitable for residential and commercial construction
- Excellent non-sag properties
- Lightweight thinset exceeding industry standards
- Easy to mix and apply; smooth and easy to install
- Meets or exceeds ANSI Standards 118.4 & 118.11

Installation

- Packaging:** 30lb bag
- Colors:** White
- Mixing Ratio:** 5.25 qts. of water per 30lb
- Coverage:** Approx. 80 sq. ft. per 30lb.
1/4" Sq. Notch Trowel: 75 sq. ft.
3/8" Sq. Notch Trowel; 60 sq. ft.
1/2" Sq. Notch Trowel; 40 sq. ft.

Related Products

- Spiral Mixer 24"
- Bucket 3.5 Gal | 6 Gal
- Margin Trowel

Performance

- Open time:** 30 minutes
- Working time:** 30 minutes
- Pot life:** Approx. 3 hours
- Shelf Life:** 15 months. Store in a cool, dry location

Steps to Mix Thinset

- ① Add approx. 5.25 qts. of clean water per 30lb of powder
- ② Pour powder into the bucket of water until the water forms a ring around the powder.
- ③ Use a spiral mixer to mix the thinset to a "peanut butter" consistency. Let it slake for 10-15 minutes, then mix again.
- ④ Use product within Pot Life. Do not re-temper*.
If thinset is no longer workable, discard the thinset and mix a new batch.
* Add additional water and remix after initially activating product.

