

PENETRATING SEALER

Penetrating Sealer can be used on porous materials such as grout, tile, concrete, clay, and other masonry surfaces. It will not change the appearance of the material or leave a glossy finish.

Key Features

- Provides protection with a natural look for stone, tile and grout
- Interior and exterior use
- Provides premium water resistance; water sheets off in vertical applications
- Traffic-ready in 24 to 72 hours

Installation

Packaging: Pint and Quart

Coverage: 1 Pint will cover 30 - 125 sq. ft.
1 Quart will cover 75 - 250 sq. ft.

Related Products

- Sealer Sponge
- Tile & Grout Maintenance

Application Tips

- It is not recommended to apply sealer to the surface of a glazed ceramic or porcelain tile
- Use heavy duty cleaner to remove waxes or coatings
- Apply 72 hours after grouting
- Test a small area and allow to cure 24 hours to ensure achieving your desired result
- Store and apply between 40° and 90° F

Steps to Apply Sealer

- ① Prepare a clean and dry surface free of any dirt, dust, waxes, or coatings.
- ② Apply 1-2 coats using a Sealer Sponge.
- ③ Use an absorbent towel to remove and polish any sealer that does not penetrate within 5 - 10 minutes.
- ④ Allow a minimum of 30 minutes between coats.
- ⑤ After a minimum of 2 hours, test to determine if the surface is completely sealed.

