

PRO-BOND LFT

Pro-Bond LFT is a best-in-class polymer-modified thinset with premium non-slump characteristics making it ideal for large and heavy tile with tile build-up to 3/4". Pro-Bond LFT offers a smooth, creamy formulation and has excellent non-sag performance that provides easy troweling.

Key Features

- Interior and Exterior use; suitable for residential and commercial construction
- Excellent non-sag properties
- Smooth and easy to trowel and apply
- Meets or exceeds ANSI Standards 118.4 & 118.11

Installation

- Packaging:** 50lb bag
Colors: White and Grey
Mixing Ratio: 6.25 - 6.5 qts. of water per 50lb
Coverage: Approx. 90 sq. ft. per 50lb.
1/4" Sq. Notch Trowel: 90 - 100 sq. ft.
3/8" Sq. Notch Trowel; 80 - 90 sq. ft.
1/2" Sq. Notch Trowel; 65 - 75 sq. ft.

Related Products

- Spiral Mixer 24"
- Bucket 3.5 Gal | 6 Gal
- Margin Trowel

Performance

- Open time:** 15 - 25 minutes
Working time: 20 - 30 minutes
Pot life: Approx. 3 hours
Shelf Life: 15 months. Store in a cool, dry location

Steps to Mix Thinset

- ① Add approx. 6.25 - 6.5 qts. of clean water per 50lb of powder
- ② Pour powder into the bucket of water until the water forms a ring around the powder.
- ③ Use a spiral mixer to mix the thinset to a "peanut butter" consistency. Let it slake for 10-15 minutes, then mix again.
- ④ Use product within Pot Life. Do not re-temper*. If thinset is no longer workable, discard the thinset and mix a new batch.
* Add additional water and remix after initially activating product.

