

PRO-BOND

Pro-Bond is a premium non-sag thinset with high latex content designed to prevent tile slippage when used on a vertical or horizontal surfaces. Pro-Bond is ideal for use with heavy or large walls tiles, and is great with large bodied tiles for floors.

Key Features

- Interior use only; suitable for residential and commercial construction
- Excellent non-sag properties
- Great for installation over exterior grade plywood or masonry surfaces
- Easy to mix and apply; smooth and easy to install
- Meets or exceeds ANSI Standards 118.4 & 118.11

Installation

- Packaging:** 25lb and 50lb bags
- Colors:** White and Grey
- Mixing Ratio:** 2.5 - 3 qts. of water per 25lb
5 - 5.5 qts. of water per 50lb
- Coverage:** Approx. 80 sq. ft. per 50lb.
1/4" Sq. Notch Trowel: 75 sq. ft.
3/8" Sq. Notch Trowel; 60 sq. ft.
1/2" Sq. Notch Trowel; 40 sq. ft.

Related Products

- Spiral Mixer 24"
- Bucket 3.5 Gal | 6 Gal
- Margin Trowel

Performance

- Open time:** 20 - 30 minutes
- Working time:** 20 - 30 minutes
- Pot life:** Approx. 3 hours
- Shelf Life:** 15 months. Store in a cool, dry location

Steps to Mix Thinset

- ① Add approx. 2.5 - 2.75 qts. of clean water per 25lb of powder
Add approx. 5 - 5.5 qts. of clean water per 50lb of powder
- ② Pour powder into the bucket of water until the water forms a ring around the powder.
- ③ Use a spiral mixer to mix the thinset to a "peanut butter" consistency. Let it slake for 10-15 minutes, then mix again.
- ④ Use product within Pot Life. Do not re-temper*.
If thinset is no longer workable, discard the thinset and mix a new batch.
* Add additional water and remix after initially activating product.

