

PRO-EPOXY ADHESIVE & GROUT

Pro-Epoxy Adhesive and Grout is a chemical resistant epoxy adhesive that will bond to most sound, clean surfaces. This 3-part system consists of 100% epoxy resin, hardener and chemical resistant silica filler that spreads easily and cleans with water.

Key Features

- Smooth formula with easy water cleanup
- Three-part system
- Premium durability and stain resistant
- ANSI Standards 118.3

Installation

Packaging: 1 Gallon - Part A & B
10 lb. bag - Part C

Parts: Part A - Liquid Epoxy Resin
Part B - Liquid Hardener
Part C - Dry Colored Aggregate

Related Products

- Spiral Mixer 24"
- Margin Trowel
- Bucket 3.5 Gal | 6 Gal

Mixing Ratio: Pour Part A & B into bucket and mix.
Add Part C until completely mixed.

Application Tips

Pro-Epoxy is perfect for setting and grouting ceramic, porcelain, stone, and mosaics on horizontal and vertical surfaces. Epoxy is the industry standard for the installation of resin-backed tile, stone, and mosaics, as well as moisture sensitive stones like black, red, and green marbles.

Steps to Mix Adhesive & Grout

- 1 Pour Part A & B into a clean mixing pail and mix thoroughly.
- 2 Add the entire contents of Part C and mix until uniform. Do not over-mix, as this will cause the epoxy to flash set. Do not add water to your mix.
- 3 With flat side of the trowel, key-in Pro-Epoxy to substrate. Additional thinset can be added to prepare setting bed with notched trowel.
- 4 Remove all excess epoxy from the surface tile with the edge of a rubber float before it begins to set. After 15 minutes, clean the remaining grout off the surface of the tile using clean water and sponge.
- 5 After application, protect setting and grouting material for 1-day against foot traffic; protect grout from chemical cleaners for first 14 days; wait 10 days prior to submerging.

