

PRO-FLEX PLATINUM

Pro-Flex Platinum is a premium, latex-modified thinset ideal for installation of ceramic, porcelain, and natural stone. The naturally smooth and creamy formulation enables exceptional open time and installed tile adjustability.

Key Features

- Interior use only; suitable for residential and commercial construction
- Premium multi-purpose thinset
- Consistent high performance
- Easy to mix and apply; smooth and easy to install
- Meets or exceeds ANSI Standards 118.4 & 118.11

Installation

Packaging: 25lb and 50lb bags
Colors: White and Grey
Mixing Ratio: 2.5 – 3 qts. of water per 25lb
5 – 5.5 qts. of water per 50lb
Coverage: Approx. 80 sq. ft. per 50lb.
1/4" Sq. Notch Trowel: 75 sq. ft.
3/8" Sq. Notch Trowel; 60 sq. ft.
1/2" Sq. Notch Trowel; 40 sq. ft.

Related Products

- Spiral Mixer 24"
- Bucket 3.5 Gal | 6 Gal
- Margin Trowel

Performance

Open time: 20 – 30 minutes
Working time: 20 – 30 minutes
Pot life: Approx. 3 hours
Shelf Life: 15 months. Store in a cool, dry location

Steps to Mix Thinset

- ① Add approx. 2.5 – 2.75 qts. of clean water per 25lb of powder
Add approx. 5 – 5.5 qts. of clean water per 50lb of powder
- ② Pour powder into the bucket of water until the water forms a ring around the powder.
- ③ Use a spiral mixer to mix the thinset to a "peanut butter" consistency. Let it slake for 10–15 minutes, then mix again.
- ④ Use product within Pot Life. Do not re-temper*.
If thinset is no longer workable, discard the thinset and mix a new batch.
* Add additional water and remix after initially activating product.

