

PRO-FLEX

Pro-Flex is our entry level modified thinset, providing exceptional performance for interior use with ceramic and stone in floor applications.

Key Features

- Interior use only; suitable for residential and commercial construction
- Great multi-purpose thinset; multiple substrates such as concrete and backer board
- Extended open time
- Easy to mix and apply; smooth and easy to install
- Meets or exceeds ANSI Standards 118.4 & 118.11

Installation

Packaging: 50lb bags
Colors: White and Grey
Mixing Ratio: 5 - 5.5 qts. of water per 50lb

Coverage: Approx. 80 sq. ft. per 50lb.
1/4" Sq. Notch Trowel: 80 sq. ft.
3/8" Sq. Notch Trowel; 60 sq. ft.
1/2" Sq. Notch Trowel; 40 sq. ft.

Performance

Open time: 20 - 30 minutes
Working time: 20 - 30 minutes
Pot life: Approx. 2.5 hours
Shelf Life: 15 months. Store in a cool, dry location

Related Products

- Spiral Mixer 24"
- Bucket 3.5 Gal | 6 Gal
- Margin Trowel

Steps to Mix Thinset

- ① Add approx. 5 - 5.5 qts. of clean water per 50lb of powder
- ② Pour powder into the bucket of water until the water forms a ring around the powder.
- ③ Use a spiral mixer to mix the thinset to a "peanut butter" consistency. Let it slake for 10-15 minutes, then mix again.
- ④ Use product within Pot Life. Do not re-temper*. If thinset is no longer workable, discard the thinset and mix a new batch.
* Add additional water and remix after initially activating product.

