

# PRO-GROUT EXCEL

Pro-Grout Excel is our premium grout featuring stain resistance, shrink resistance, and a non-efflorescence formula. This high performance sanded grout is highly durable and may be used on a variety of tile products.

## Key Features

- Non-efflorescent
- Rapid setting, walk-on ready in 4 hours
- Recommend for joints 1/16" to 1/2"
- Meets or exceeds ANSI Standards 118.7

## Installation

**Packaging:** 8lb and 25lb bags

**Colors:**



**Coverage:**

TILE SIZE	1/8" Joint	3/16" Joint
Mosaics	30 - 50	NOT RECOMMENDED
2" x 2"	50 - 60	NOT RECOMMENDED
3" x 6"	110	65
4" x 12"	180	110
6" x 24"	270	180
8" x 8"	225	155
8" x 20"	330	225
8" x 36"	360	250
8" x 48"	480	270
12" x 12"	330	225
12" x 24"	450	315
24" x 24"	675	450
Pebbles	Varies by Sheet: 20 - 35	

## Related Products

- TruBlue Grout Float
- Spiral Mixer 24"
- Pro-Grout Excel Measuring Pail
- Pro-Sponge
- Bucket 3.5 Gal | 6 Gal

## Application Tips

- Be cautious when using Pro-Grout Excel with polished marble or limestone as Excel contains aggregate which may scratch the surface.
- Do not use Flexible Admixture or other latex products to mix Excel.

## Steps to Grout Tile

- ① Select grout color and mix with specified water - do not add too much water to the mixture. Mix until smooth.
- ② Apply grout and use a grout float at a 45 deg. angle to spread and remove excess grout from the face of the tile.
- ③ Use a damp sponge to clean off excess grout from the tile; be sure to avoid watering down the grout which may change the color.
- ④ Let the grout cure for 24 hours. Excel grout is stain resistant without the need for sealing.
- ⑤ Apply caulk around fixtures, along terminating edges, and any inside corners between tile.

