

PRO-GROUT SANDED

Pro-Grout Sanded is a durable, easy-to-use formula that is crack resistant. This grout includes fine silica sand to provide filler for the grout and is recommended for grout joints 1/8" and greater but use caution on surfaces prone to scratches.

Key Features

- Durable, easy-to-use formula
- Great for floor and wall installation
- Recommend for joints sizes greater than 1/8"
- Meets or exceeds ANSI Standards 118.6

Installation

Packaging: 8lb and 25lb bags

Colors:



Coverage:

TILE SIZE	1/8" Joint	TILE SIZE	1/8" Joint
Mosaics	30 - 50	8" x 20"	330
2" x 2"	50 - 60	8" x 36"	360
3" x 6"	110	8" x 48"	480
4" x 12"	180	12" x 12"	330
6" x 24"	270	12" x 24"	450

Related Products

- TruBlue Grout Float
- Spiral Mixer 24"
- Grout Admixture
- Pro-Sponge
- Margin Trowel
- Bucket 3.5 Gal | 6 Gal

Application Tips

- Flexible Admixture is recommended with Pro-Grout Sanded to reduce cure time from 30 days to 48 - 72 hours. Admixture will also help maintain color consistency and increase resistance to movement.

Steps to Grout Tile

- ① Select grout color and mix with Flexible Admixture using a margin trowel or spiral mixer to avoid over-mixing.
- ② Apply grout and use a grout float at a 45 deg. angle to spread and remove excess grout from the face of the tile.
- ③ Use a damp sponge to clean off excess grout from the tile; be sure to avoid watering down the grout which may change the color.
- ④ Let the grout cure for 48 - 72 hours (if using Admix) prior to applying sealer to the grout. Seal stone tile depending on customer selections. If using water, wait 30 days.
- ⑤ Apply caulk around fixtures, along terminating edges, and any inside corners between tile.

