

PRO-LEVEL

Superior Pro-Level is a self-leveling underlayment formulated with a blend of Portland and calcium aluminate cements and polymers. Pro-Level is designed for fast leveling of substrates prior to installing flooring – on, above or below grade. Pourable, Pro-Level seeks its own level and produces a durable, smooth and flat floor surface with minimum labor.

Key Features

- Single component systems provides a level interior surface
- Rapid setting, walk on ready in 4 hours
- Extended heal allows for raking
- Meets or exceeds ASTM C1708

Installation

Sizes: 55lb bag
Mixing Ratio: 5.25 qts. of water per 55lb
Coverage: 20 -25 sq. ft. at 1/4"

Related Products

- Pro-Level Measuring Pail
- Spiral Mixer 24"
- Pro-Primer Gallon

Installation Tips

- Pro-Level is not specified as a structural component of the installation, therefore you must use the correct subfloor and underlayment requirements.
- Each pour should be made into the previous pour within 10 minutes to avoid creating uneven lippage.

Steps to Using Pro-Level

- ① Apply Pro-Primer to floor and allow to dry for 2 hours prior to applying Pro-Level
- ② Mix Pro-Level 55lb bag with 5.25 quarts of water for 2 minutes. Using the Pro-Level Measuring Pail provides pre-determined holes to assist with mixing.
- ③ Pour mixed Pro-Level onto the floor starting from an edge or corner and working your way to the exit of the room.
- ④ As needed, mix additional bags of Pro-Level and begin each successive pour into the existing pour within 10 minutes.
- ⑤ Allow the Pro-Level to set for 24 hours prior to tiling or placing a non-breathable covering.

