

PRO-MASTIC

Pro-Mastic is a pre-mixed adhesive that is ready to use right out of the container. It offers a non-slip high performance formula best used for interior wall installation of all types of ceramic tile.

Key Features

- Interior vertical surfaces in non-wet area use only
- No mixing required; easy troweling
- Made with an antimicrobial agent that protects from fungal growth
- Meets or exceeds ANSI 136.1 Type 1

Installation

Packaging: 1 gallon and 3.5 gallon

Mixing Ratio: No mixing required

Related Products

- Pro Series Trowel

Coverage: Ceramic Mosaics and Gauged Slate up to 80 sq. ft./gal
Glazed Wall Tile - up to 60 sq. ft./gal
Heavy Tile and Pavers - up to 40 sq. ft./gal
Quarry Tile - up to 30 sq. ft./gal

Performance

Open time: 30 - 45 minutes

Working time: Up to 25 minutes

Shelf Life: 12 months. Store in a cool, dry location

Steps to Apply Adhesive

- ① Apply adhesive using the recommended size trowel for your size tile. Apply at a 45 degree angle and trowel in straight lines.
- ② Only trowel out an area that can be tiled within 25 minutes.
- ③ Wipe off any mastic that is on the surface of the tile while it is still wet. If it dries on the surface, it can be removed with Superior Pro Strip. Tightly seal cover when not in use.

