

TABLE B — METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

SPEED SYMBOL	MAX. SPEED
A8	25 mph
B	30 mph
D	40 mph

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

ENGLISH UNITS OF MEASURE (lbs@psi)

TIRE SIZE	INFLATION		LOAD LIMITS (LBS) AT VARIOUS COLD INFLATION PRESSURES													
	psi	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
230/95R32		LI													128	
	SINGLES			1390	1610	1820	2090	2340	2540	2680	2760	3000	3200	3520	3740	3960
	DUALS		1030	1220	1410	1600	1840	2060	2230	2360	2430	2650	2820	3100	3300	3480
	TRIPLES		960	1140	1320	1490	1720	1920	2080	2190	2270	2470	2620	2890	3060	3260
230/95R36		LI													130	
	SINGLES			1480	1710	1980	2200	2470	2680	2830	3000	3200	3420	3740	3960	4180
	DUALS		1090	1300	1500	1740	1940	2170	2360	2490	2650	2820	3000	3300	3480	3680
	TRIPLES		1010	1210	1400	1630	1810	2030	2190	2310	2470	2620	2800	3060	3260	3440
230/95R44		LI													134	
	SINGLES			1650	1930	2200	2470	2760	3000	3200	3300	3520	3860	4180	4400	4680
	DUALS		1190	1460	1700	1940	2170	2430	2650	2820	2910	3100	3400	3680	3880	4120
	TRIPLES		1110	1360	1590	1810	2030	2270	2470	2620	2710	2890	3180	3440	3620	3840
230/95R48		LI													134	136
	SINGLES			1710	2040	2270	2600	2910	3200	3300	3420	3740	4080	4400	4680	4940
	DUALS		1260	1500	1800	2000	2290	2560	2820	2900	3010	3290	3590	3870	4120	4340
	TRIPLES		1170	1400	1670	1860	2130	2390	2620	2710	2800	3070	3350	3610	3840	4060
260/70R16		LI										109				
	SINGLES			1060	1230	1420	1590	1730	1870	2000	2110	2270				
	DUALS		770	925	1090	1260	1400	1520	1650	1750	1850	2000				
	TRIPLES		730	870	1010	1170	1300	1420	1530	1630	1730	1860				
270/95R48		LI														144
	SINGLES			2150	2540	2910	3300	3640	3960	4180	4400	4680	5080	5520	5840	6150
	DUALS		1600	1900	2230	2560	2910	3200	3480	3680	3880	4120	4460	4860	5140	5420
	TRIPLES		1490	1760	2080	2380	2710	2980	3260	3440	3620	3840	4160	4520	4780	5080
280/70R16		LI										112				
	SINGLES			1020	1200	1360	1520	1710	1870	2040	2200	2470				
	DUALS		750	900	1060	1200	1340	1500	1650	1800	1940	2170				
	TRIPLES		700	840	980	1120	1250	1400	1530	1670	1800	2030				
280/70R18		LI										114				
	SINGLES			1070	1280	1430	1610	1820	1980	2150	2340	2600				
	DUALS		800	940	1130	1260	1420	1600	1740	1890	2060	2290				
	TRIPLES		750	880	1050	1170	1320	1490	1620	1760	1920	2130				
280/85R24		LI							115							
	SINGLES			1480	1710	1930	2200	2470	2680							
	DUALS		1080	1300	1500	1700	1940	2170	2360							
	TRIPLES		1010	1210	1400	1580	1800	2030	2200							
290/95R34		LI										131				
	SINGLES			2040	2340	2680	3000	3300	3640	3860	4080	4300				
	DUALS		1450	1800	2060	2360	2640	2900	3200	3400	3590	3780				
	TRIPLES		1350	1670	1920	2200	2460	2710	2980	3170	3350	3530				

TABLE B — METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

SPEED SYMBOL	MAX. SPEED
A8	40 km/h
B	50 km/h
D	65 km/h

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

METRIC UNITS OF MEASURE (kg@kPa)

TIRE SIZE	INFLATION			LOAD LIMITS (KG) AT VARIOUS COLD INFLATION PRESSURES														
		kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440	
		bar	0.4	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.4	2.8	3.2	3.6	4.0	4.4	
230/95R32		LI														128		
	SINGLES			630	730	825	950	1060	1150	1215	1250	1360	1450	1600	1700	1800		
	DUALS		465	555	640	725	835	935	1010	1070	1100	1200	1280	1410	1500	1580		
	TRIPLES		435	515	600	675	780	870	945	995	1030	1120	1190	1310	1390	1480		
230/95R36		LI														130		
	SINGLES			670	775	900	1000	1120	1215	1285	1360	1450	1550	1700	1800	1900		
	DUALS		495	590	680	790	880	985	1070	1130	1200	1280	1360	1500	1580	1670		
	TRIPLES		460	550	635	740	820	920	995	1050	1120	1190	1270	1390	1480	1560		
230/95R44		LI														134		
	SINGLES			750	875	1000	1120	1250	1360	1450	1500	1600	1750	1900	2000	2120		
	DUALS		540	660	770	880	985	1100	1200	1280	1320	1410	1540	1670	1760	1870		
	TRIPLES		505	615	720	820	920	1030	1120	1190	1230	1310	1440	1560	1640	1740		
230/95R48		LI													134	136		
	SINGLES			775	925	1030	1180	1320	1450	1500	1550	1700	1850	2000	2120	2240		
	DUALS		570	680	810	910	1040	1160	1280	1320	1360	1500	1630	1760	1870	1970		
	TRIPLES		530	640	760	840	970	1080	1190	1230	1270	1390	1520	1640	1740	1840		
260/70R16		LI										109						
	SINGLES			480	560	645	720	785	850	905	955	1030						
	DUALS		350	420	495	570	635	690	750	795	840	905						
	TRIPLES		330	395	460	530	590	645	695	740	785	845						
270/95R48		LI														144		
	SINGLES			975	1150	1320	1500	1650	1800	1900	2000	2120	2300	2500	2650	2800		
	DUALS		725	860	1010	1160	1320	1450	1580	1670	1760	1870	2020	2200	2330	2460		
	TRIPLES		675	800	945	1080	1230	1350	1480	1560	1640	1740	1890	2050	2170	2300		
280/70R16		LI										112						
	SINGLES			462	545	615	690	775	850	925	1000	1120						
	DUALS		340	410	480	540	610	680	750	810	880	990						
	TRIPLES		320	380	450	500	570	640	700	760	820	920						
280/70R18		LI										114						
	SINGLES			487	580	650	730	825	900	975	1060	1180						
	DUALS		360	430	510	570	640	730	790	860	930	1040						
	TRIPLES		340	400	480	530	600	680	740	800	870	970						
280/85R24		LI							115									
	SINGLES			670	775	875	1000	1120	1215									
	DUALS		490	590	680	770	880	990	1070									
	TRIPLES		460	550	640	720	820	920	1000									
290/95R34		LI										131						
	SINGLES			925	1060	1215	1360	1500	1650	1750	1850	1950						
	DUALS		660	810	930	1070	1200	1320	1450	1540	1630	1720						
	TRIPLES		620	760	870	1000	1120	1230	1350	1440	1520	1600						

TABLE B — METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

ENGLISH UNITS OF MEASURE (lbs@psi)

TIRE SIZE	INFLATION			LOAD LIMITS (LBS) AT VARIOUS COLD INFLATION PRESSURES														
		psi	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64	
320/85R24		LI							122									
	SINGLES			1820	2090	2400	2680	3000	3300									
	DUALS		1300	1600	1840	2110	2360	2640	2900									
	TRIPLES		1210	1490	1710	1970	2200	2460	2710									
320/85R28		LI							124									
	SINGLES			1930	2270	2600	2910	3200	3520									
	DUALS		1420	1700	2000	2290	2560	2820	3100									
	TRIPLES		1320	1580	1860	2130	2390	2620	2890									
320/85R34		LI										133						
	SINGLES			2150	2470	2830	3200	3520	3860	4080	4300	4540						
	DUALS		1550	1890	2170	2490	2820	3100	3400	3590	3780	4000						
	TRIPLES		1440	1760	2030	2320	2620	2890	3170	3350	3530	3720						
320/85R36		LI							128									
	SINGLES			2200	2540	2910	3300	3640	3960									
	DUALS		1600	1940	2230	2560	2910	3200	3480									
	TRIPLES		1490	1810	2080	2380	2710	2980	3260									
320/85R38		LI										135	138		143			
	SINGLES			2270	2600	3000	3420	3740	4080	4300	4540	4800	5200	5680	6000			
	DUALS		1650	2000	2290	2640	3010	3290	3590	3780	4000	4220	4580	5000	5280			
	TRIPLES		1530	1860	2130	2460	2800	3070	3350	3530	3720	3940	4260	4660	4920			
320/90R42		LI										139						
	SINGLES			2470	2910	3300	3740	4180	4540	4800	4940	5360						
	DUALS		1840	2170	2560	2900	3290	3680	4000	4220	4350	4720						
	TRIPLES		1710	2030	2390	2710	3070	3430	3720	3940	4050	4400						
320/90R46		LI													148			
	SINGLES			2600	3000	3420	3860	4300	4800	5080	5200	5520	6150	6600	6950			
	DUALS		1890	2290	2640	3010	3400	3780	4220	4470	4580	4860	5410	5810	6120			
	TRIPLES		1760	2130	2460	2800	3170	3530	3940	4170	4260	4530	5040	5410	5700			
320/90R50		LI												148				
	SINGLES			2760	3200	3640	4080	4540	4940	5200	5520	5840	6400	6950				
	DUALS		2000	2430	2820	3200	3590	4000	4350	4580	4860	5140	5630	6120				
	TRIPLES		1860	2260	2620	2980	3350	3720	4050	4260	4530	4790	5250	5700				
320/90R54		LI												149				
	SINGLES			2830	3300	3740	4300	4680	5200	5520	5680	6000	6600	7150				
	DUALS		2060	2490	2900	3290	3780	4120	4580	4860	5000	5280	5810	6290				
	TRIPLES		1920	2320	2710	3070	3530	3840	4260	4530	4660	4920	5410	5860				
340/85R24		LI							125									
	SINGLES			1980	2270	2600	3000	3300	3640									
	DUALS		1450	1740	2000	2290	2640	2900	3200									
	TRIPLES		1350	1620	1860	2130	2460	2710	2980									
340/85R28		LI							127			133						
	SINGLES			2090	2470	2830	3200	3520	3860	4080	4300	4540						
	DUALS		1550	1840	2170	2490	2820	3100	3400	3600	3800	4000						
	TRIPLES		1440	1720	2030	2310	2620	2890	3180	3360	3520	3720						

TABLE B — METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

METRIC UNITS OF MEASURE (kg@kPa)

INFLATION			LOAD LIMITS (KG) AT VARIOUS COLD INFLATION PRESSURES														
TIRE SIZE		kPa bar	40 0.4	60 0.6	80 0.8	100 1.0	120 1.2	140 1.4	160 1.6	180 1.8	200 2.0	240 2.4	280 2.8	320 3.2	360 3.6	400 4.0	440 4.4
320/85R24		LI							122								
	SINGLES			825	950	1090	1215	1360	1500								
	DUALS		590	730	840	960	1070	1200	1320								
	TRIPLES		550	680	780	890	1000	1120	1230								
320/85R28		LI							124								
	SINGLES			875	1030	1180	1320	1450	1600								
	DUALS		640	770	910	1040	1160	1280	1410								
	TRIPLES		600	720	840	970	1080	1190	1310								
320/85R34		LI										133					
	SINGLES			975	1120	1285	1450	1600	1750	1850	1950	2060					
	DUALS		700	860	990	1130	1280	1410	1540	1630	1720	1810					
	TRIPLES		660	800	920	1050	1190	1310	1440	1520	1600	1690					
320/85R36		LI							128								
	SINGLES			1000	1150	1320	1500	1650	1800								
	DUALS		725	880	1010	1160	1320	1450	1580								
	TRIPLES		675	820	945	1080	1230	1350	1480								
320/85R38		LI										135	138		143		
	SINGLES			1030	1180	1360	1550	1700	1850	1950	2060	2180	2360	2575	2725		
	DUALS		750	910	1040	1200	1360	1500	1630	1720	1810	1920	2080	2270	2400		
	TRIPLES		700	840	970	1120	1270	1390	1520	1600	1690	1790	1940	2110	2230		
320/90R42		LI										139					
	SINGLES			1120	1320	1500	1700	1900	2060	2180	2240	2430					
	DUALS		840	990	1160	1320	1500	1670	1810	1920	1970	2140					
	TRIPLES		780	920	1080	1230	1390	1560	1690	1790	1840	1990					
320/90R46		LI													148		
	SINGLES			1180	1360	1550	1750	1950	2180	2300	2360	2500	2800	3000	3150		
	DUALS		860	1040	1200	1360	1540	1720	1920	2020	2080	2200	2460	2640	2770		
	TRIPLES		800	970	1120	1270	1440	1600	1790	1890	1940	2050	2300	2460	2580		
320/90R50		LI													148		
	SINGLES			1250	1450	1650	1850	2060	2240	2360	2500	2650	2900	3150			
	DUALS		910	1100	1280	1450	1630	1810	1970	2080	2200	2330	2550	2770			
	TRIPLES		840	1030	1190	1350	1520	1690	1840	1940	2050	2170	2380	2580			
320/90R54		LI													149		
	SINGLES			1285	1500	1700	1950	2120	2360	2500	2575	2725	3000	3250			
	DUALS		930	1130	1320	1500	1720	1870	2080	2200	2270	2400	2640	2860			
	TRIPLES		870	1050	1230	1390	1600	1740	1940	2050	2110	2230	2460	2670			
340/85R24		LI							125								
	SINGLES			900	1030	1180	1360	1500	1650								
	DUALS		660	790	910	1040	1200	1320	1450								
	TRIPLES		620	740	840	970	1120	1230	1350								
340/85R28		LI							127			133					
	SINGLES			950	1120	1285	1450	1600	1750	1850	1950	2060					
	DUALS		705	835	985	1130	1280	1410	1540	1630	1720	1810					
	TRIPLES		655	780	920	1050	1190	1310	1440	1520	1600	1690					

TABLE B — METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

ENGLISH UNITS OF MEASURE (*lbs@psi*)

TIRE SIZE		INFLATION		LOAD LIMITS (LBS) AT VARIOUS COLD INFLATION PRESSURES													
		psi	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
360/70R20		LI										129					
	SINGLES			1650	1930	2200	2540	2760	3080	3300	3640	4080					
	DUALS		1220	1450	1700	1940	2240	2430	2710	2900	3200	3590					
	TRIPLES		1140	1350	1580	1800	2080	2260	2530	2710	2980	3350					
360/70R24		LI							122								
	SINGLES			1820	2090	2400	2760	3000	3300								
	DUALS		1330	1600	1840	2120	2430	2650	2910								
	TRIPLES		1250	1490	1720	1970	2270	2470	2710								
360/70R28		LI							125								
	SINGLES			1930	2270	2600	2910	3300	3640								
	DUALS		1420	1700	2000	2290	2560	2900	3200								
	TRIPLES		1320	1580	1860	2130	2390	2710	2990								
380/70R24		LI							125								
	SINGLES			1980	2270	2600	3000	3300	3640								
	DUALS		1450	1740	2000	2290	2640	2900	3200								
	TRIPLES		1350	1620	1860	2130	2460	2710	2980								
380/70R28		LI							127								
	SINGLES			2090	2470	2830	3200	3520	3860								
	DUALS		1550	1840	2170	2490	2820	3100	3400								
	TRIPLES		1440	1710	2030	2320	2620	2890	3170								
380/80R38		LI										142					
	SINGLES			2760	3200	3640	4180	4540	5080	5360	5520	5840					
	DUALS		2000	2430	2820	3200	3680	4000	4470	4720	4860	5140					
	TRIPLES		1860	2260	2620	2980	3430	3720	4170	4400	4530	4790					
380/85R24		LI							131								
	SINGLES			2340	2760	3080	3520	3860	4300								
	DUALS		1700	2060	2430	2710	3100	3400	3780								
	TRIPLES		1580	1920	2260	2530	2890	3170	3530								
380/85R26		LI							132			138					
	SINGLES			2400	2830	3200	3640	4080	4400	4680	4940	5200					
	DUALS		1800	2120	2490	2820	3200	3600	3880	4120	4340	4580					
	TRIPLES		1680	1970	2310	2620	2980	3360	3620	3840	4060	4280					
380/85R28		LI							133			139					
	SINGLES			2540	2910	3300	3740	4180	4540	4800	5080	5360					
	DUALS		1840	2230	2560	2910	3300	3680	4000	4240	4460	4720					
	TRIPLES		1720	2080	2380	2710	3060	3440	3720	3940	4160	4380					
380/85R30		LI							135			140					
	SINGLES			2600	3000	3420	3860	4300	4800	4940	5200	5520					
	DUALS		1900	2290	2650	3000	3400	3800	4240	4340	4580	4860					
	TRIPLES		1760	2140	2470	2800	3180	3520	3940	4060	4280	4520					
380/85R34		LI							137			142	145				
	SINGLES			2760	3200	3640	4080	4540	5080	5360	5520	5840	6400				
	DUALS		2000	2430	2820	3200	3590	4000	4470	4720	5860	5140	5630				
	TRIPLES		1860	2260	2620	2980	3350	3720	4170	4400	4530	4790	5250				
380/90R46		LI										152				159	
	SINGLES			3300	3860	4400	5080	5520	6150	6400	6800	7150	7850	8550	9100	9650	
	DUALS		2490	2910	3400	3880	4460	4860	5420	5620	5980	6300	6900	7550	8000	8500	
	TRIPLES		2310	2710	3180	3620	4160	4520	5080	5240	5560	5880	6400	7000	7450	7900	

TABLE B — METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

METRIC UNITS OF MEASURE (kg@kPa)

TIRE SIZE		INFLATION		LOAD LIMITS (KG) AT VARIOUS COLD INFLATION PRESSURES														
		kPa		40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
		bar		0.4	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.4	2.8	3.2	3.6	4.0	4.4
360/70R20		LI											129					
	SINGLES				750	875	1000	1150	1250	1400	1500	1650	1850					
	DUALS			550	660	770	880	1010	1100	1230	1320	1450	1630					
	TRIPLES			520	620	720	820	940	1030	1150	1230	1350	1520					
360/70R24		LI								122								
	SINGLES				825	950	1090	1250	1360	1500								
	DUALS			605	725	835	960	1100	1200	1320								
	TRIPLES			565	675	780	895	1030	1120	1230								
360/70R28		LI								125								
	SINGLES				875	1030	1180	1320	1500	1650								
	DUALS			640	770	910	1040	1160	1320	1450								
	TRIPLES			600	720	850	970	1080	1230	1350								
380/70R24		LI								125								
	SINGLES				900	1030	1180	1360	1500	1650								
	DUALS			660	790	910	1040	1200	1320	1450								
	TRIPLES			620	740	840	970	1120	1230	1350								
380/70R28		LI								127								
	SINGLES				950	1120	1285	1450	1600	1750								
	DUALS			700	840	990	1130	1280	1410	1540								
	TRIPLES			660	780	920	1050	1190	1310	1440								
380/80R38		LI											142					
	SINGLES				1250	1450	1650	1900	2060	2300	2430	2500	2650					
	DUALS			910	1100	1280	1450	1670	1810	2020	2140	2200	2330					
	TRIPLES			840	1030	1190	1350	1560	1690	1890	1990	2050	2170					
380/85R24		LI								131								
	SINGLES				1060	1250	1400	1600	1750	1950								
	DUALS			770	930	1100	1230	1410	1540	1720								
	TRIPLES			720	870	1030	1150	1310	1440	1600								
380/85R26		LI								132			138					
	SINGLES				1090	1285	1450	1650	1850	2000	2120	2240	2360					
	DUALS			815	960	1130	1280	1450	1630	1760	1870	1970	2080					
	TRIPLES			760	895	1050	1190	1350	1520	1640	1740	1840	1940					
380/85R28		LI								133			139					
	SINGLES				1150	1320	1500	1700	1900	2060	2180	2300	2430					
	DUALS			835	1010	1160	1320	1500	1670	1810	1920	2020	2140					
	TRIPLES			780	945	1080	1230	1390	1560	1690	1790	1890	1990					
380/85R30		LI								135			140					
	SINGLES				1180	1360	1550	1750	1950	2180	2240	2360	2500					
	DUALS			860	1040	1200	1360	1540	1720	1920	1970	2080	2200					
	TRIPLES			800	970	1120	1270	1440	1600	1790	1840	1940	2050					
380/85R34		LI								137			142	145				
	SINGLES				1250	1450	1650	1850	2060	2300	2430	2500	2650	2900				
	DUALS			910	1100	1280	1450	1630	1810	2020	2140	2200	2330	2550				
	TRIPLES			840	1030	1190	1350	1520	1690	1890	1990	2050	2170	2380				
380/90R46		LI												152			159	
	SINGLES				1500	1750	2000	2300	2500	2800	2900	3075	3250	3550	3875	4125	4375	
	DUALS			1130	1320	1540	1760	2020	2200	2460	2550	2710	2860	3120	3420	3640	3860	
	TRIPLES			1050	1230	1440	1640	1890	2050	2300	2380	2520	2670	2910	3180	3380	3580	

TABLE B — METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

ENGLISH UNITS OF MEASURE (*lbs@psi*)

TIRE SIZE		INFLATION		LOAD LIMITS (LBS) AT VARIOUS COLD INFLATION PRESSURES													
		psi	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
380/90R50		LI										151					
	SINGLES			3520	4080	4680	5200	5840	6400	6800	6950	7600					
	DUALS		2560	3100	3590	4120	4580	5140	5630	5980	6120	6690					
	TRIPLES		2390	2890	3350	3840	4260	4790	5250	5580	5700	6230					
380/90R54		LI										152					
	SINGLES			3640	4300	4800	5520	6000	6600	6950	7400	7850					
	DUALS		2640	3200	3780	4220	4860	5280	5810	6120	6510	6910					
	TRIPLES		2460	2980	3530	3940	4530	4920	5410	5700	6070	6440					
380/105R50		LI															168
	SINGLES			3960	4680	5360	6000	6600	7400	7600	8050	8550	9350	10200	10700	11400	12300
	DUALS		2900	3480	4120	4720	5280	5810	6510	6690	7080	7520	8230	8980	9420	10030	10825
	TRIPLES		2710	3250	3840	4400	4920	5410	6070	6230	6600	7010	7670	8360	8770	9350	10085
385/85R34		LI											146				
	SINGLES			2830	3300	3740	4180	4680	5200	5360	5680	6000	6600				
	DUALS		2060	2490	2900	3290	3680	4120	4580	4720	5000	5280	5810				
	TRIPLES		1920	2320	2710	3070	3430	3840	4260	4400	4660	4920	5410				
400/75R38		LI							138								
	SINGLES			2830	3300	3740	4180	4680	5200								
	DUALS		2060	2490	2900	3290	3670	4120	4580								
	TRIPLES		1920	2320	2700	3070	3430	3840	4260								
420/70R24		LI							130								
	SINGLES			2270	2680	3080	3420	3860	4180								
	DUALS		1700	2000	2360	2710	3010	3400	3680								
	TRIPLES		1580	1860	2200	2530	2800	3170	3430								
420/70R28		LI							133								
	SINGLES			2470	2910	3300	3740	4080	4540								
	DUALS		1800	2170	2560	2910	3300	3600	4000								
	TRIPLES		1680	2030	2380	2710	3060	3360	3720								
420/80R46		LI										151				161	
	SINGLES			3520	4080	4680	5360	5840	6400	6800	7150	7600	8250	8800	9650	10200	
	DUALS		2560	3100	3590	4120	4720	5140	5630	5980	6290	6690	7300	7750	8500	9000	
	TRIPLES		2390	2890	3350	3840	4400	4790	5250	5580	5860	6230	6800	7250	7900	8400	
420/85R24		LI							137								
	SINGLES			2760	3200	3640	4080	4540	5080								
	DUALS		2000	2430	2820	3200	3590	4000	4470								
	TRIPLES		1860	2260	2620	2980	3350	3720	4170								
420/85R26		LI							138			143					
	SINGLES			2830	3300	3740	4300	4680	5200	5520	5680	6000					
	DUALS		2060	2490	2910	3300	3800	4120	4580	4860	5000	5300					
	TRIPLES		1920	2310	2710	3060	3520	3840	4280	4520	4660	4920					
420/85R28		LI							139			144					
	SINGLES			2910	3420	3860	4400	4940	5360	5680	5840	6150					
	DUALS		2170	2560	3000	3400	3880	4340	4720	5000	5140	5420					
	TRIPLES		2030	2380	2800	3180	3620	4060	4380	4660	4780	5080					

TABLE B — METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

METRIC UNITS OF MEASURE (kg@kPa)

TIRE SIZE	INFLATION		LOAD LIMITS (KG) AT VARIOUS COLD INFLATION PRESSURES														
		kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
		bar	0.4	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.4	2.8	3.2	3.6	4.0	4.4
380/90R50		LI										151					
	SINGLES			1600	1850	2120	2360	2650	2900	3075	3150	3450					
	DUALS		1160	1410	1630	1870	2080	2330	2550	2710	2770	3040					
	TRIPLES		1080	1310	1520	1740	1940	2170	2380	2520	2580	2830					
380/90R54		LI										152					
	SINGLES			1650	1950	2180	2500	2725	3000	3150	3350	3550					
	DUALS		1200	1450	1720	1920	2200	2400	2640	2770	2950	3120					
	TRIPLES		1120	1350	1600	1790	2050	2230	2460	2580	2750	2910					
380/105R50		LI															168
	SINGLES			1800	2120	2430	2725	3000	3350	3450	3650	3875	4250	4625	4875	5150	5600
	DUALS		1320	1580	1870	2140	2400	2640	2950	3040	3210	3410	3740	4070	4290	4530	4930
	TRIPLES		1230	1480	1740	1990	2230	2460	2750	2830	2990	3180	3490	3790	4000	4220	4590
385/85R34		LI											146				
	SINGLES			1285	1500	1700	1900	2120	2360	2430	2575	2725	3000				
	DUALS		930	1130	1320	1500	1670	1870	2080	2140	2270	2400	2640				
	TRIPLES		870	1050	1230	1390	1560	1740	1940	1990	2110	2230	2460				
400/75R38		LI							138								
	SINGLES			1285	1500	1700	1900	2120	2360								
	DUALS		930	1130	1320	1500	1670	1870	2080								
	TRIPLES		870	1050	1230	1390	1620	1740	1940								
420/70R24		LI							130								
	SINGLES			1030	1215	1400	1550	1750	1900								
	DUALS		770	910	1070	1230	1360	1540	1670								
	TRIPLES		720	840	1000	1150	1270	1440	1560								
420/70R28		LI							133								
	SINGLES			1120	1320	1500	1700	1850	2060								
	DUALS		815	985	1160	1320	1500	1630	1810								
	TRIPLES		760	920	1080	1230	1390	1520	1690								
420/80R46		LI										151				161	
	SINGLES			1600	1850	2120	2430	2650	2900	3075	3250	3450	3750	4000	4375	4625	
	DUALS		1160	1410	1630	1870	2140	2330	2550	2710	2860	3040	3300	3520	3860	4080	
	TRIPLES		1080	1310	1520	1740	1990	2170	2380	2520	2670	2830	3080	3280	3580	3800	
420/85R24		LI							137								
	SINGLES			1250	1450	1650	1850	2060	2300								
	DUALS		910	1100	1280	1450	1630	1810	2020								
	TRIPLES		840	1030	1190	1350	1520	1690	1890								
420/85R26		LI							138			143					
	SINGLES			1285	1500	1700	1950	2120	2360	2500	2575	2725					
	DUALS		935	1130	1320	1500	1720	1870	2080	2200	2270	2400					
	TRIPLES		870	1050	1230	1390	1600	1740	1940	2050	2110	2230					
420/85R28		LI							139			144					
	SINGLES			1320	1550	1750	2000	2240	2430	2575	2650	2800					
	DUALS		985	1160	1360	1540	1760	1970	2140	2270	2330	2460					
	TRIPLES		920	1080	1270	1440	1640	1840	1990	2110	2170	2300					

TABLE B — METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

ENGLISH UNITS OF MEASURE (lbs@psi)

TIRE SIZE		INFLATION		LOAD LIMITS (LBS) AT VARIOUS COLD INFLATION PRESSURES													
		psi	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
420/85R30		LI							140								
	SINGLES			3000	3520	4080	4540	5080	5520								
	DUALS		2240	2640	3100	3590	4000	4470	4860								
	TRIPLES		2080	2460	2890	3350	3720	4170	4530								
420/85R34		LI							142			147					
	SINGLES			3200	3740	4300	4800	5360	5840	6150	6400	6800					
	DUALS		2360	2820	3290	3780	4220	4720	5140	5410	5630	5980					
	TRIPLES		2200	2620	3070	3530	3940	4400	4790	5040	5250	5580					
420/85R38		LI							144			149					
	SINGLES			3420	3960	4540	5080	5680	6150	6600	6800	7150					
	DUALS		2490	3010	3480	4000	4470	5000	5410	5820	5980	6300					
	TRIPLES		2320	2800	3250	3720	4170	4660	5040	5420	5560	5880					
420/90R30		LI							142		145	147					
	SINGLES			3200	3740	4180	4800	5360	5840	6150	6400	6800					
	DUALS		2360	2820	3300	3680	4240	4720	5140	5420	5620	5980					
	TRIPLES		2190	2620	3060	3440	3940	4380	4780	5080	5240	5560					
440/65R24		LI							128								
	SINGLES			2270	2600	3000	3420	3740	3960								
	DUALS		1650	2000	2290	2640	3010	3290	3480								
	TRIPLES		1530	1860	2130	2460	2800	3070	3250								
440/65R28		LI							131								
	SINGLES			2400	2830	3200	3640	3960	4300								
	DUALS		1800	2110	2490	2820	3200	3490	3780								
	TRIPLES		1670	1970	2320	2620	2990	3250	3530								
460/85R30		LI							145								
	SINGLES			3520	4080	4680	5200	5840	6400								
	DUALS		2560	3100	3590	4120	4580	5140	5630								
	TRIPLES		2390	2890	3350	3840	4260	4790	5250								
460/85R34		LI							147		150						
	SINGLES			3640	4300	4940	5520	6150	6800	7150	7400						
	DUALS		2710	3200	3780	4350	4860	5410	5980	6300	6500						
	TRIPLES		2530	2980	3530	4050	4530	5040	5580	5880	6050						
460/85R38		LI							149			154					
	SINGLES			3860	4540	5200	5840	6400	7150	7400	7850	8250					
	DUALS		2820	3400	4000	4580	5140	5630	6290	6500	6900	7300					
	TRIPLES		2620	3170	3720	4260	4790	5250	5860	6050	6400	6800					
460/85R42		LI							150			156					
	SINGLES			4080	4800	5360	6150	6800	7400	7850	8250	8800					
	DUALS		3010	3590	4220	4720	5410	5980	6510	6900	7300	7750					
	TRIPLES		2800	3350	3940	4400	5040	5580	6070	6400	6800	7250					
480/65R24		LI							133			140					
	SINGLES			2600	3000	3420	3860	4180	4540	4800	5080	5520					
	DUALS		1890	2290	2640	3010	3400	3680	4000	4240	4460	4860					
	TRIPLES		1760	2130	2460	2800	3170	3430	3720	3940	4160	4520					

TABLE B — METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

METRIC UNITS OF MEASURE (kg@kPa)

TIRE SIZE		INFLATION		LOAD LIMITS (KG) AT VARIOUS COLD INFLATION PRESSURES													
		kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
		bar	0.4	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.4	2.8	3.2	3.6	4.0	4.4
420/85R30		LI							140								
	SINGLES			1360	1600	1850	2060	2300	2500								
	DUALS		1010	1200	1410	1630	1810	2020	2200								
	TRIPLES		940	1120	1310	1520	1690	1890	2050								
420/85R34		LI							142			147					
	SINGLES			1450	1700	1950	2180	2430	2650	2800	2900	3075					
	DUALS		1070	1280	1500	1720	1920	2140	2330	2460	2550	2710					
	TRIPLES		1000	1190	1390	1600	1790	1990	2170	2300	2380	2520					
420/85R38		LI							144			149					
	SINGLES			1550	1800	2060	2300	2575	2800	3000	3075	3250					
	DUALS		1130	1360	1580	1810	2020	2270	2460	2640	2710	2860					
	TRIPLES		1050	1270	1480	1690	1890	2110	2300	2460	2520	2670					
420/90R30		LI							142		145	147					
	SINGLES			1450	1700	1900	2180	2430	2650	2800	2900	3075					
	DUALS		1070	1280	1500	1670	1920	2140	2330	2460	2550	2710					
	TRIPLES		995	1190	1390	1560	1790	1990	2170	2300	2380	2520					
440/65R24		LI							128								
	SINGLES			1030	1180	1360	1550	1700	1800								
	DUALS		750	910	1040	1200	1360	1500	1580								
	TRIPLES		700	850	970	1120	1270	1390	1480								
440/65R28		LI							131								
	SINGLES			1090	1285	1450	1650	1800	1950								
	DUALS		810	960	1130	1280	1450	1580	1720								
	TRIPLES		760	890	1050	1190	1350	1480	1600								
460/85R30		LI							145								
	SINGLES			1600	1850	2120	2360	2650	2900								
	DUALS		1160	1410	1630	1870	2080	2330	2550								
	TRIPLES		1080	1310	1520	1740	1940	2170	2380								
460/85R34		LI							147		150						
	SINGLES			1650	1950	2240	2500	2800	3075	3250	3350						
	DUALS		1230	1450	1720	1970	2200	2460	2710	2860	2950						
	TRIPLES		1150	1350	1600	1840	2050	2300	2520	2670	2750						
460/85R38		LI							149			154					
	SINGLES			1750	2060	2360	2650	2900	3250	3350	3550	3750					
	DUALS		1280	1540	1810	2080	2330	2550	2860	2950	3120	3300					
	TRIPLES		1190	1440	1690	1940	2170	2380	2670	2750	2910	3080					
460/85R42		LI							150			156					
	SINGLES			1850	2180	2430	2800	3075	3350	3550	3750	4000					
	DUALS		1360	1630	1920	2140	2460	2710	2950	3120	3300	3520					
	TRIPLES		1270	1520	1790	1990	2300	2520	2750	2910	3080	3280					
480/65R24		LI							133			140					
	SINGLES			1180	1360	1550	1750	1900	2060	2180	2300	2500					
	DUALS		860	1040	1200	1360	1540	1670	1810	1920	2020	2200					
	TRIPLES		800	970	1120	1270	1440	1560	1690	1790	1890	2050					

TABLE B — METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

ENGLISH UNITS OF MEASURE (lbs@psi)

TIRE SIZE		INFLATION		LOAD LIMITS (LBS) AT VARIOUS COLD INFLATION PRESSURES													
		psi	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
480/65R28		LI							136								
	SINGLES			2760	3200	3640	4180	4540	4940								
	DUALS		2000	2430	2820	3200	3680	4000	4350								
	TRIPLES		1860	2260	2620	2990	3430	3720	4051								
480/70R24		LI							138								
	SINGLES			2830	3300	3740	4300	4680	5200								
	DUALS		2060	2490	2900	3290	3780	4120	4580								
	TRIPLES		1920	2320	2710	3070	3530	3840	4260								
480/70R28		LI							140								
	SINGLES			3000	3520	4080	4540	5080	5520								
	DUALS		2240	2640	3100	3590	4000	4470	4860								
	TRIPLES		2080	2460	2890	3350	3720	4170	4530								
480/70R30		LI							141			147		152			
	SINGLES			3080	3640	4180	4680	5200	5680	6000	6400	6800	7400	7850			
	DUALS		2290	2710	3200	3680	4120	4580	5000	5280	5630	5980	6510	6910			
	TRIPLES		2130	2530	2980	3430	3840	4260	4660	4920	5250	5580	6070	6440			
480/70R34		LI							143		146	149		155			
	SINGLES			3300	3860	4400	4940	5520	6000	6400	6600	7150	7850	8550			
	DUALS		2430	2900	3400	3870	4350	4860	5280	5630	5810	6290	6910	7520			
	TRIPLES		2260	2710	3170	3610	4050	4530	4920	5250	5410	5860	6440	7010			
480/70R38		LI							145								
	SINGLES			3520	4080	4680	5200	5840	6400								
	DUALS		2560	3100	3590	4120	4580	5140	5630								
	TRIPLES		2390	2890	3350	3840	4260	4790	5250								
480/80R30		LI							145								
	SINGLES			3520	4080	4680	5360	5840	6400								
	DUALS		2560	3100	3590	4120	4720	5140	5630								
	TRIPLES		2390	2890	3350	3840	4400	4790	5250								
480/80R38		LI							149								
	SINGLES			3960	4540	5200	5840	6600	7150								
	DUALS		2900	3480	4000	4580	5140	5810	6290								
	TRIPLES		2710	3250	3720	4260	4790	5410	5860								
480/80R42		LI							151		154	156					
	SINGLES			4080	4800	5520	6150	6950	7600	8050	8250	8800					
	DUALS		3000	3600	4240	4860	5420	6100	6700	7100	7300	7750					
	TRIPLES		2800	3360	3940	4520	5080	5680	6250	6600	6800	7250					
480/80R46		LI										158					
	SINGLES			4300	5080	5680	6400	7150	7850	8250	8550	9350					
	DUALS		3200	3780	4470	5000	5630	6290	6910	7260	7520	8230					
	TRIPLES		2980	3530	4170	4660	5250	5860	6440	6770	7010	7670					
480/80R50		LI										159					
	SINGLES			4540	5200	6000	6800	7600	8250	8550	9100	9650					
	DUALS		3290	4000	4580	5280	5980	6690	7260	7520	8010	8490					
	TRIPLES		3070	3720	4260	4920	5580	6230	6770	7010	7460	7910					

TABLE B — METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

METRIC UNITS OF MEASURE (kg@kPa)

TIRE SIZE	INFLATION			LOAD LIMITS (KG) AT VARIOUS COLD INFLATION PRESSURES													
		kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
		bar	0.4	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.4	2.8	3.2	3.6	4.0	4.4
480/65R28		LI							136								
	SINGLES			1250	1450	1650	1900	2060	2240								
	DUALS		910	1100	1280	1450	1670	1810	1970								
	TRIPLES		850	1030	1190	1350	1560	1690	1840								
480/70R24		LI							138								
	SINGLES			1285	1500	1700	1950	2120	2360								
	DUALS		930	1130	1320	1500	1720	1870	2080								
	TRIPLES		870	1050	1230	1390	1600	1740	1940								
480/70R28		LI							140								
	SINGLES			1360	1600	1850	2060	2300	2500								
	DUALS		1010	1200	1410	1630	1810	2020	2200								
	TRIPLES		940	1120	1310	1520	1690	1890	2050								
480/70R30		LI							141			147		152			
	SINGLES			1400	1650	1900	2120	2360	2575	2725	2900	3075	3350	3550			
	DUALS		1040	1230	1450	1670	1870	2080	2270	2400	2550	2710	2950	3120			
	TRIPLES		970	1150	1350	1560	1740	1940	2110	2230	2380	2520	2750	2910			
480/70R34		LI							143		146	149		155			
	SINGLES			1500	1750	2000	2240	2500	2725	2900	3000	3250	3550	3875			
	DUALS		1100	1320	1540	1760	1970	2200	2400	2550	2640	2860	3120	3410			
	TRIPLES		1030	1230	1440	1640	1840	2050	2240	2380	2460	2670	2910	3180			
480/70R38		LI							145								
	SINGLES			1600	1850	2120	2360	2650	2900								
	DUALS		1160	1410	1630	1870	2080	2330	2550								
	TRIPLES		1080	1310	1520	1740	1940	2170	2380								
480/80R30		LI							145								
	SINGLES			1600	1850	2120	2430	2650	2900								
	DUALS		1160	1410	1630	1870	2140	2330	2550								
	TRIPLES		1080	1310	1520	1740	1990	2170	2380								
480/80R38		LI							149								
	SINGLES			1800	2060	2360	2650	3000	3250								
	DUALS		1320	1580	1810	2080	2330	2640	2860								
	TRIPLES		1230	1480	1690	1940	2170	2460	2670								
480/80R42		LI							151		154	156					
	SINGLES			1850	2180	2500	2800	3150	3450	3650	3750	4000					
	DUALS		1360	1630	1920	2200	2460	2770	3040	3220	3300	3520					
	TRIPLES		1270	1520	1790	2050	2300	2580	2830	2990	3080	3280					
480/80R46		LI										158					
	SINGLES			1950	2300	2575	2900	3250	3550	3750	3875	4250					
	DUALS		1450	1720	2020	2270	2550	2860	3120	3300	3410	3740					
	TRIPLES		1350	1600	1890	2110	2380	2670	2910	3080	3180	3490					
480/80R50		LI										159					
	SINGLES			2060	2360	2725	3075	3450	3750	3875	4125	4375					
	DUALS		1500	1810	2080	2400	2710	3040	3300	3410	3630	3850					
	TRIPLES		1390	1690	1940	2230	2520	2830	3080	3180	3380	3590					

TABLE B — METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

ENGLISH UNITS OF MEASURE (lbs@psi)

TIRE SIZE		INFLATION		LOAD LIMITS (LBS) AT VARIOUS COLD INFLATION PRESSURES													
		psi	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
480/85R34		LI							149								
	SINGLES			3960	4540	5200	5840	6600	7150								
	DUALS		2900	3480	4000	4580	5140	5810	6290								
	TRIPLES		2710	3250	3720	4260	4790	5410	5860								
520/70R34		LI							148								
	SINGLES			3740	4400	5080	5680	6150	6950								
	DUALS		2710	3300	3880	4460	5000	5420	6100								
	TRIPLES		2540	3060	3620	4160	4660	5080	5680								
520/70R38		LI							150								
	SINGLES			3960	4680	5200	6000	6600	7400								
	DUALS		2900	3480	4120	4580	5280	5810	6510								
	TRIPLES		2710	3250	3840	4260	4920	5410	6070								
520/85R38		LI							155			160					
	SINGLES			4680	5520	6150	6950	7850	8550	9100	9350	9900					
	DUALS		3400	4120	4860	5410	6120	6910	7520	8000	8250	8750					
	TRIPLES		3170	3840	4530	5040	5700	6440	7010	7450	7650	8150					
520/85R42		LI							157			162	165				
	SINGLES			4940	5680	6600	7400	8250	9100	9350	9900	10500	11400				
	DUALS		3590	4350	5000	5810	6510	7260	8010	8230	8710	9240	10030				
	TRIPLES		3350	4050	4660	5410	6070	6770	7460	7670	8120	8610	9350				
520/85R46		LI							158								
	SINGLES			5080	6000	6800	7600	8550	9350								
	DUALS		3780	4470	5280	5980	6690	7520	8230								
	TRIPLES		3530	4170	4920	5580	6230	7010	7670								
540/65R24		LI							140			146					
	SINGLES			3080	3640	4080	4680	5080	5520	5840	6150	6600					
	DUALS		2290	2710	3200	3590	4120	4470	4860	5140	5420	5820					
	TRIPLES		2130	2530	2980	3350	3840	4170	4530	4780	5080	5420					
540/65R28		LI							142			149					
	SINGLES			3300	3860	4400	4940	5520	5840	6150	6600	7150					
	DUALS		2430	2900	3400	3870	4350	4860	5140	5420	5820	6300					
	TRIPLES		2260	2710	3170	3610	4050	4530	4790	5080	5420	5880					
540/65R30		LI							143			150					
	SINGLES			3420	3960	4540	5080	5680	6000	6400	6800	7400					
	DUALS		2490	3010	3480	4000	4470	5000	5280	5630	5980	6510					
	TRIPLES		2320	2800	3250	3720	4170	4660	4920	5250	5580	6070					
540/65R34		LI							145			152					
	SINGLES			3640	4180	4800	5520	6000	6400	6800	7150	7850					
	DUALS		2640	3200	3680	4220	4860	5280	5630	5980	6290	6910					
	TRIPLES		2460	2980	3430	3940	4530	4920	5250	5580	5860	6440					
540/65R38		LI							147								
	SINGLES			3860	4400	5080	5680	6150	6800								
	DUALS		2820	3400	3870	4470	5000	5410	5980								
	TRIPLES		2620	3170	3610	4170	4660	5040	5580								

TABLE B — METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

METRIC UNITS OF MEASURE (kg@kPa)

TIRE SIZE	INFLATION		LOAD LIMITS (KG) AT VARIOUS COLD INFLATION PRESSURES														
		kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
		bar	0.4	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.4	2.8	3.2	3.6	4.0	4.4
480/85R34		LI							149								
	SINGLES			1800	2060	2360	2650	3000	3250								
	DUALS		1320	1580	1810	2080	2330	2640	2860								
	TRIPLES		1230	1480	1690	1940	2170	2460	2670								
520/70R34		LI							148								
	SINGLES			1700	2000	2300	2575	2800	3150								
	DUALS		1230	1500	1760	2020	2270	2460	2770								
	TRIPLES		1150	1390	1640	1890	2110	2300	2580								
520/70R38		LI							150								
	SINGLES			1800	2120	2360	2725	3000	3350								
	DUALS		1320	1580	1870	2080	2400	2640	2950								
	TRIPLES		1230	1480	1740	1940	2240	2460	2750								
520/85R38		LI							155			160					
	SINGLES			2120	2500	2800	3150	3550	3875	4125	4250	4500					
	DUALS		1540	1870	2200	2460	2770	3120	3410	3640	3740	3960					
	TRIPLES		1440	1740	2050	2300	2580	2910	3180	3380	3480	3700					
520/85R42		LI							157			162	165				
	SINGLES			2240	2575	3000	3350	3750	4125	4250	4500	4750	5150				
	DUALS		1630	1970	2270	2640	2950	3300	3630	3740	3960	4180	4530				
	TRIPLES		1520	1840	2110	2460	2750	3080	3380	3490	3690	3900	4220				
520/85R46		LI							158								
	SINGLES			2300	2725	3075	3450	3875	4250								
	DUALS		1720	2020	2400	2710	3040	3410	3740								
	TRIPLES		1600	1890	2230	2520	2830	3180	3490								
540/65R24		LI							140			146					
	SINGLES			1400	1650	1850	2120	2300	2500	2650	2800	3000					
	DUALS		1040	1230	1450	1630	1870	2020	2200	2330	2460	2640					
	TRIPLES		970	1150	1350	1520	1740	1890	2050	2170	2300	2460					
540/65R28		LI							142			149					
	SINGLES			1500	1750	2000	2240	2500	2650	2800	3000	3250					
	DUALS		1100	1320	1540	1760	1970	2200	2330	2460	2640	2860					
	TRIPLES		1030	1230	1440	1640	1840	2050	2170	2300	2460	2670					
540/65R30		LI							143			150					
	SINGLES			1550	1800	2060	2300	2575	2725	2900	3075	3350					
	DUALS		1130	1360	1580	1810	2020	2270	2400	2550	2710	2950					
	TRIPLES		1050	1270	1480	1690	1890	2110	2230	2380	2520	2750					
540/65R34		LI							145			152					
	SINGLES			1650	1900	2180	2500	2725	2900	3075	3250	3550					
	DUALS		1200	1450	1670	1920	2200	2400	2550	2710	2860	3120					
	TRIPLES		1120	1350	1560	1790	2050	2230	2380	2520	2670	2910					
540/65R38		LI							147								
	SINGLES			1750	2000	2300	2575	2800	3075								
	DUALS		1280	1540	1760	2020	2270	2460	2710								
	TRIPLES		1190	1440	1640	1890	2110	2300	2520								

TABLE B — METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

ENGLISH UNITS OF MEASURE (lbs@psi)

TIRE SIZE		INFLATION		LOAD LIMITS (LBS) AT VARIOUS COLD INFLATION PRESSURES													
		psi	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
580/70R38		LI							155								
	SINGLES			4680	5520	6150	6950	7850	8550								
	DUALS		3400	4120	4860	5420	6100	6900	7550								
	TRIPLES		3180	3840	4520	5080	5680	6400	7000								
580/70R42		LI							158								
	SINGLES			4940	5680	6600	7400	8250	9350								
	DUALS		3600	4340	5000	5820	6500	7300	8250								
	TRIPLES		3360	4060	4660	5420	6050	6800	7650								
580/85R42		LI									166	168					
	SINGLES			5840	6800	7850	8800	9650	10700	11000	11700	12300					
	DUALS		4220	5140	5980	6910	7740	8490	9420	9680	10300	10800					
	TRIPLES		3940	4790	5580	6440	7220	7910	8770	9020	9590	10100					
600/65R28		LI							147			154					
	SINGLES			3860	4540	5200	5840	6400	6800	7400	7850	8250					
	DUALS		2900	3400	4000	4580	5140	5630	5980	6510	6910	7260					
	TRIPLES		2710	3170	3720	4260	4790	5250	5560	6070	6440	6770					
600/65R34		LI							151			157					
	SINGLES			4300	4940	5680	6400	6950	7600	8050	8550	9100					
	DUALS		3100	3780	4350	5000	5630	6120	6690	7100	7550	8000					
	TRIPLES		2890	3530	4050	4660	5250	5700	6230	6600	7000	7450					
600/65R38		LI							153			159					
	SINGLES			4540	5200	6000	6800	7400	8050	8550	8800	9650					
	DUALS		3290	4000	4580	5280	5980	6510	7080	7550	7750	8500					
	TRIPLES		3070	3720	4260	4920	5580	6070	6600	7000	7250	7900					
600/70R28		LI												164			
	SINGLES			4300	5080	5680	6400	7150	7850	8250	8550	9100	10200	11000			
	DUALS		3200	3780	4470	5000	5630	6290	6910	7260	7520	8000	8980	9680			
	TRIPLES		2980	3530	4170	4660	5250	5860	6440	6770	7010	7460	8360	9020			
600/70R30		LI							152			158	162				
	SINGLES			4400	5200	5840	6600	7400	7850	8550	8800	9350	10500				
	DUALS		3200	3880	4580	5140	5820	6500	6900	7550	7750	8250	9200				
	TRIPLES		2980	3620	4280	4780	5420	6050	6400	7000	7250	7650	8600				
620/70R42		LI							160			166					
	SINGLES			5360	6400	7150	8050	9100	9900	10500	11000	11700					
	DUALS		4000	4720	5630	6290	7080	8010	8710	9240	9680	10300					
	TRIPLES		3720	4400	5250	5860	6600	7460	8120	8610	9020	9590					
620/70R46		LI										167					
	SINGLES			5680	6600	7600	8550	9350	10500	11000	11400	12000					
	DUALS		4120	5000	5800	6700	7500	8250	9250	9700	10000	10600					
	TRIPLES		3840	4660	5420	6250	7000	7650	8600	9000	9350	9850					
620/75R30		LI										163					
	SINGLES			4940	5840	6600	7400	8250	9100	9650	9900	10700					
	DUALS		3680	4350	5140	5810	6510	7260	8010	8490	8710	9420					
	TRIPLES		3430	4050	4790	5410	6070	6770	7460	7910	8120	8770					

TABLE B — METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

METRIC UNITS OF MEASURE (kg@kPa)

TIRE SIZE	INFLATION			LOAD LIMITS (KG) AT VARIOUS COLD INFLATION PRESSURES													
	kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440	
	bar	0.4	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.4	2.8	3.2	3.6	4.0	4.4	
580/70R38		LI							155								
	SINGLES			2120	2500	2800	3150	3550	3875								
	DUALS		1540	1870	2200	2460	2770	3120	3420								
	TRIPLES		1440	1740	2050	2300	2580	2910	3180								
580/70R42		LI							158								
	SINGLES			2240	2575	3000	3350	3750	4250								
	DUALS		1630	1970	2270	2640	2950	3300	3740								
	TRIPLES		1520	1840	2110	2460	2750	3080	3480								
580/85R42		LI								166	168						
	SINGLES			2650	3075	3550	4000	4375	4875	5000	5300	5600					
	DUALS		1920	2330	2710	3120	3520	3850	4290	4400	4660	4920					
	TRIPLES		1790	2170	2520	2910	3280	3590	4000	4100	4350	4600					
600/65R28		LI							147			154					
	SINGLES			1750	2060	2360	2650	2900	3075	3350	3550	3750					
	DUALS		1320	1540	1810	2080	2330	2550	2710	2950	3120	3300					
	TRIPLES		1230	1440	1690	1940	2170	2380	2520	2750	2910	3080					
600/65R34		LI							151			157					
	SINGLES			1950	2240	2575	2900	3150	3450	3650	3875	4125					
	DUALS		1410	1720	1970	2270	2550	2770	3040	3220	3420	3640					
	TRIPLES		1310	1600	1840	2110	2380	2580	2830	2990	3180	3380					
600/65R38		LI							153			159					
	SINGLES			2060	2360	2725	3075	3350	3650	3875	4000	4375					
	DUALS		1500	1810	2080	2400	2710	2950	3210	3420	3520	3860					
	TRIPLES		1390	1690	1940	2230	2520	2750	2990	3180	3280	3580					
600/70R28		LI											164				
	SINGLES			1950	2300	2575	2900	3250	3550	3750	3875	4125	4625	5000			
	DUALS		1450	1720	2020	2270	2550	2860	3120	3300	3410	3630	4070	4400			
	TRIPLES		1350	1600	1890	2110	2380	2670	2910	3080	3180	3380	3800	4100			
600/70R30		LI							152			158	162				
	SINGLES			2000	2360	2650	3000	3350	3550	3875	4000	4250	4750				
	DUALS		1450	1760	2080	2330	2640	2950	3120	3420	3520	3740	4180				
	TRIPLES		1350	1640	1940	2170	2460	2750	2910	3180	3280	3480	3900				
620/70R42		LI							160			166					
	SINGLES			2430	2900	3250	3650	4125	4500	4750	5000	5300					
	DUALS		1810	2140	2550	2860	3210	3630	3960	4180	4400	4660					
	TRIPLES		1690	1990	2380	2670	2990	3380	3690	3900	4100	4350					
620/70R46		LI										167					
	SINGLES			2575	3000	3450	3875	4250	4750	5000	5150	5450					
	DUALS		1870	2270	2640	3040	3420	3740	4180	4400	4540	4800					
	TRIPLES		1740	2110	2460	2830	3180	3480	3900	4100	4220	4460					
620/75R30		LI										163					
	SINGLES			2240	2650	3000	3350	3750	4125	4375	4500	4875					
	DUALS		1670	1970	2330	2640	2950	3300	3630	3850	3960	4290					
	TRIPLES		1560	1840	2170	2460	2750	3080	3380	3590	3690	4000					

TABLE B — METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

ENGLISH UNITS OF MEASURE (lbs@psi)

TIRE SIZE		INFLATION		LOAD LIMITS (LBS) AT VARIOUS COLD INFLATION PRESSURES													
		psi	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
650/65R38		LI							157			163	166				
	SINGLES			5080	5840	6800	7600	8250	9100	9650	9900	10700	11700				
	DUALS		3680	4460	5140	5980	6700	7300	8000	8500	8750	9500	10300				
	TRIPLES		3440	4160	4780	5560	6250	6800	7450	7900	8150	8800	9550				
650/65R42		LI							158			165					
	SINGLES			5360	6150	7150	8050	8800	9350	9900	10500	11400					
	DUALS		3870	4720	5410	6290	7080	7740	8230	8750	9200	10000					
	TRIPLES		3610	4400	5040	5860	6600	7220	7670	8150	8600	9300					
650/75R32		LI												172			
	SINGLES			5520	6400	7400	8250	9100	9900	10700	11000	12000	12800	13900			
	DUALS		4000	4860	5630	6510	7260	8010	8700	9420	9680	10600	11260	12230			
	TRIPLES		3720	4530	5250	6070	6770	7460	8100	8770	9020	9850	10500	11400			
650/85R38		LI										173					
	SINGLES			6600	7850	8800	9900	11000	12000	12800	13200	14300					
	DUALS		4860	5810	6910	7740	8710	9680	10560	11260	11620	12580					
	TRIPLES		4530	5410	6440	7220	8120	9020	9840	10500	10820	11730					
710/70R38		LI							166			171					
	SINGLES			6400	7400	8550	9650	10700	11700	12300	12800	13600					
	DUALS		4720	5630	6510	7520	8490	9420	10300	10800	11200	11900					
	TRIPLES		4400	5250	6070	7010	7910	8770	9590	10100	10500	11100					
710/70R42		LI							168			173					
	SINGLES			6600	7850	8800	9900	11000	12300	12800	13600	14300					
	DUALS		4860	5810	6910	7740	8710	9680	10820	11260	11970	12580					
	TRIPLES		4530	5410	6440	7220	8120	9020	10090	10500	11150	11730					
710/75R42		LI										175					
	SINGLES			7150	8250	9350	10700	11700	13200	13600	14300	15200					
	DUALS		5140	6300	7300	8250	9500	10300	11600	11900	12600	13300					
	TRIPLES		4780	5880	6800	7650	8800	9550	10800	11100	11800	12500					
750/65R26		LI										166	169				
	SINGLES			5360	6400	7150	8050	8800	9650	10200	10700	11700	12800				
	DUALS		4000	4720	5630	6290	7080	7740	8490	8980	9420	10300	11260				
	TRIPLES		3720	4400	5250	5860	6600	7220	7910	8360	8770	9590	10500				
800/65R32		LI										172					
	SINGLES			6600	7600	8800	9650	10700	11700	12300	12800	13900					
	DUALS		4720	5810	6690	7740	8490	9420	10300	10820	11260	12230					
	TRIPLES		4400	5410	6230	7220	7910	8770	9590	10090	10500	11400					
800/70R38		LI							173				181				
	SINGLES			7600	9100	10200	11700	12800	14300	14800	15700	16500	18200				
	DUALS		5630	6690	8010	8980	10300	11260	12580	13020	13820	14520	16020				
	TRIPLES		5250	6230	7460	8360	9590	10500	11730	12140	12870	13530	14920				
900/50R42		LI							168								
	SINGLES			6800	7850	9100	10200	11400	12300								
	DUALS		5000	5980	6910	8010	8980	10030	10820								
	TRIPLES		4660	5580	6440	7460	8360	9350	10090								
900/60R32		LI										176					
	SINGLES			7150	8250	9350	10700	11700	12800	13900	14300	15700					
	DUALS		5140	6290	7260	8230	9420	10300	11260	12230	12580	13820					
	TRIPLES		4790	5860	6770	7670	8770	9590	10500	11400	11730	12870					

TABLE B — METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

METRIC UNITS OF MEASURE (kg@kPa)

TIRE SIZE		INFLATION		LOAD LIMITS (KG) AT VARIOUS COLD INFLATION PRESSURES													
		kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
		bar	0.4	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.4	2.8	3.2	3.6	4.0	4.4
650/65R38		LI							157			163	166				
	SINGLES			2300	2650	3075	3450	3750	4125	4375	4500	4875	5300				
	DUALS		1670	2020	2330	2710	3040	3300	3630	3850	3960	4290	4660				
	TRIPLES		1560	1890	2170	2520	2830	3080	3380	3590	3690	4000	4350				
650/65R42		LI							158			165					
	SINGLES			2430	2800	3250	3650	4000	4250	4500	4750	5150					
	DUALS		1760	2140	2460	2860	3210	3520	3740	3960	4180	4540					
	TRIPLES		1640	1990	2300	2670	2990	3280	3470	3700	3900	4220					
650/75R32		LI												172			
	SINGLES			2500	2900	3350	3750	4125	4500	4875	5000	5450	5800	6300			
	DUALS		1810	2200	2550	2950	3300	3630	3960	4290	4400	4800	5100	5540			
	TRIPLES		1690	2050	2380	2750	3080	3380	3700	4000	4100	4460	4760	5170			
650/85R38		LI										173					
	SINGLES			3000	3550	4000	4500	5000	5450	5800	6000	6500					
	DUALS		2200	2640	3120	3520	3960	4400	4800	5100	5280	5720					
	TRIPLES		2050	2460	2910	3280	3690	4100	4470	4760	4920	5330					
710/70R38		LI							166			171					
	SINGLES			2900	3350	3875	4375	4875	5300	5600	5800	6150					
	DUALS		2140	2550	2950	3410	3850	4290	4660	4920	5100	5420					
	TRIPLES		1990	2380	2750	3180	3590	4000	4350	4600	4760	5040					
710/75R42		LI										175					
	SINGLES			3250	3750	4250	4875	5300	6000	6150	6500	6900					
	DUALS		2330	2860	3300	3740	4300	4660	5280	5420	5720	6050					
	TRIPLES		2170	2670	3080	3480	4000	4340	4920	5040	5340	5660					
710/70R42		LI							168			173					
	SINGLES			3000	3550	4000	4500	5000	5600	5800	6150	6500					
	DUALS		2200	2640	3120	3520	3960	4400	4930	5100	5410	5720					
	TRIPLES		2050	2460	2910	3280	3690	4100	4590	4760	5040	5330					
750/65R26		LI										166	169				
	SINGLES			2430	2900	3250	3650	4000	4375	4625	4875	5300	5800				
	DUALS		1810	2140	2550	2860	3210	3520	3850	4070	4290	4660	5100				
	TRIPLES		1690	1990	2380	2670	2990	3280	3590	3790	4000	4350	4760				
800/65R32		LI										172					
	SINGLES			3000	3450	4000	4375	4875	5300	5600	5800	6300					
	DUALS		2140	2640	3040	3520	3850	4290	4660	4930	5100	5540					
	TRIPLES		1990	2460	2830	3280	3590	4000	4350	4590	4760	5170					
800/70R38		LI							173				181				
	SINGLES			3450	4125	4625	5300	5800	6500	6700	7100	7500	8250				
	DUALS		2550	3040	3630	4070	4660	5100	5720	5900	6250	6600	7260				
	TRIPLES		2380	2830	3380	3790	4350	4760	5330	5490	5820	6150	6770				
900/50R42		LI							168								
	SINGLES			3075	3550	4125	4625	5150	5600								
	DUALS		2270	2710	3120	3630	4070	4530	4930								
	TRIPLES		2110	2520	2910	3380	3790	4220	4590								
900/60R32		LI									176						
	SINGLES			3550	4125	4750	5300	5800	6300	6700	7100						
	DUALS		2640	3120	3630	4180	4660	5100	5540	5900	6250						
	TRIPLES		2460	2910	3380	3900	4350	4760	5170	5490	5820						

TABLE B — METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

ENGLISH UNITS OF MEASURE (*lbs@psi*)

TIRE SIZE	INFLATION		LOAD LIMITS (LBS) AT VARIOUS COLD INFLATION PRESSURES														
		psi	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
900/65R32		LI										178					
	SINGLES			7850	9100	10500	11700	12800	13900	14800	15700	16500					
	DUALS		5810	6910	8010	9240	10300	11260	12230	13020	13820	14520					
	TRIPLES		5410	6440	7460	8610	9590	10500	11400	12140	12870	13530					
900/75R32		LI										184					
	SINGLES			9350	10700	12300	13900	15700	17100	17600	18700	19800					
	DUALS		6910	8230	9420	10820	12230	13820	15050	15490	16460	17420					
	TRIPLES		6440	7670	8770	10090	11400	12870	14020	14430	15330	16240					

NOTES:

- For tires used in cyclic loading field service, refer to Table F1 on pages 120-137.
- Loads above are applicable at speeds up to and including the rated speed capability of the tire.
- Boldface loads are maximum for the corresponding Load Index number.
- The minimum permissible inflation pressure for tires used as Singles is 9 psi.
- The minimum permissible inflation pressure for tires used as Duals or Triples is 6 psi.
- For hillside operations and single drive tires in the furrow while moldboard plowing, add 4 psi.
- For operations that do not require sustained high torque transmission and do not traverse slopes over 11° (20% grade), the load limit adjustments shown at right at various speeds apply with no change in inflation pressure.
- When running lower inflation pressures, it is extremely important to use an accurate air pressure gauge.
- For shipping purposes, tire inflation pressures may be increased to 30 psi. Inflation pressure must be adjusted to the correct operating pressure before the machine is removed from the carrier.

Maximum Service Speed	Change to loads in above table at service speed		
	A8	B	D
Stationary	+130%	+130%	+130%
2.5 mph	+70%	+70%	+70%
5 mph	+50%	+50%	+50%
10 mph	+34%	+34%	+34%
12.5 mph	+23%	+23%	+23%
15 mph	+11%	+11%	+18.5%
20 mph	+7%	+7%	+15%
22.5 mph	+3%	+3%	+12%
25 mph	None	None	+9.5%
27.5 mph	--	None	+7%
30 mph	--	None	+5%
32.5 mph	--	--	+3%
35 mph	--	--	+1.5%
40 mph	--	--	None
***43 mph	--	--	-9%

***Tires must be stamped with a secondary service description containing an "E" speed symbol (e.g. 189D / **186E**) in order to utilize this condition

TABLE B — METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

METRIC UNITS OF MEASURE (kg@kPa)

INFLATION			LOAD LIMITS (KG) AT VARIOUS COLD INFLATION PRESSURES														
TIRE SIZE		kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
		bar	0.4	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.4	2.8	3.2	3.6	4.0	4.4
900/65R32	LI											178					
	SINGLES			3550	4125	4750	5300	5800	6300	6700	7100	7500					
	DUALS		2640	3120	3640	4180	4660	5100	5540	5900	6250	6600					
	TRIPLES		2460	2910	3380	3900	4340	4760	5160	5500	5820	6150					
900/75R32	LI											184					
	SINGLES			4250	4875	5600	6300	7100	7750	8000	8500	9000					
	DUALS		3120	3740	4290	4930	5540	6250	6820	7040	7480	7920					
	TRIPLES		2910	3490	4000	4590	5170	5820	6360	6560	6970	7380					

NOTES:

- For tires used in cyclic loading field service, refer to Table F1 on pages 120-137.
- Loads above are applicable at speeds up to and including the rated speed capability of the tire.
- Boldface loads are maximum for the corresponding Load Index number.
- The minimum permissible inflation pressure for tires used as Singles is 60 kPa (0.60 bar).
- The minimum permissible inflation pressure for tires used as Duals or Triples is 40 kPa (0.40 bar).
- For hillside operations and single drive tires in the furrow while moldboard plowing, add 25 kPa (0.25 bar).
- For operations that do not require sustained high torque transmission and do not traverse slopes over 11° (20% grade), the load limit adjustments shown at right at various speeds apply with no change in inflation pressure.
- When running lower inflation pressures, it is extremely important to use an accurate air pressure gauge.
- For shipping purposes, tire inflation pressures may be increased to 210 kPa (2.10 bar). Inflation pressure must be adjusted to the correct operating pressure before the machine is removed from the carrier.

Maximum Service Speed	Change to loads in above table at service speed		
	A8	B	D
Stationary	+130%	+130%	+130%
5 km/h	+70%	+70%	+70%
10 km/h	+50%	+50%	+50%
15 km/h	+34%	+34%	+34%
20 km/h	+23%	+23%	+23%
25 km/h	+11%	+11%	+18.5%
30 km/h	+7%	+7%	+15%
35 km/h	+3%	+3%	+12%
40 km/h	None	None	+9.5%
45 km/h	--	None	+7%
50 km/h	--	None	+5%
55 km/h	--	--	+3%
60 km/h	--	--	+1.5%
65 km/h	--	--	None
***70 km/h	--	--	-9%

***Tires must be stamped with a secondary service description containing an "E" speed symbol (e.g. 189D / **186E**) in order to utilize this condition