



imageFORCE C1333F shown with optional cassette.

## SPECIFICATIONS

### Main Unit

Technology/Type	C1333F: Color A4 Laser Multifunctional C1333P: Color A4 Laser Printer
Core Functions	C1333F: Print, Copy, Scan, Send and Fax C1333P: Print
Control Panel	5" TFT LCD WVGA Color Touch panel
Memory	1.0 GB RAM
Processor	Single-Core 1.2GHz
Interface Connections	NETWORK Standard: 1000Base-T/100Base-T/10-Base-T, Wireless LAN (IEEE 802.11 b/g/n)  OTHERS Standard: USB 2.0 (Host) x2, USB 2.0 (Device) x1
Paper Sources (Letter, 20 lb. Bond)	Standard: 250-Sheet Paper Cassette, 50-Sheet Multi-Purpose Tray  Optional: 550-Sheet Paper Cassettes (PAPER FEEDER PF-K1)
Paper Capacity (Letter, 20 lb. Bond)	Standard: 250 Sheets Maximum: 850 Sheets
Output Capacity (Letter, 20 lb. Bond)	Standard: 75 Sheets
Supported Media Types	Cassettes: Thin, Plain, Thick, Color, Recycled, Coated, Label (Standard Cassette Only), Pre-punched, Letterhead, Postcard, Envelope  Multi-Purpose Tray: Thin, Plain, Thick, Color, Recycled, Coated, Label, Pre-punched, Letterhead, Postcard, Envelope
Supported Media Sizes	Cassettes: Letter, Legal, Statement, Executive, Government Letter, Government Legal, Custom size (3-7/8" x 5-7/8" to 8-1/2" x 14")  Multi-Purpose Tray: Letter, Legal, Statement, Executive, Government Letter, Government Legal, Index Card, Envelopes [No. 10(COM10), Monarch, ISO-C5, DL], Custom Size (3" x 5" to 8-1/2" x 14")
Supported Media Weights	Cassettes: 16 lb. Bond to 74.0 lb. Cover (60 to 200 gsm)  Multi-Purpose Tray: 16 lb. Bond to 74.0 lb. Cover (60 to 200 gsm)  Duplex: 16 lb. Bond to 74 lb. Cover (60 to 200 gsm)

Warm-up Time	From Power On: 14 Seconds or Less <sup>1</sup>  From Sleep Mode: 5.3 Seconds or Less
Dimensions (W x D x H)	C1333F: 16-3/4" x 18-1/8" x 17" (425 x 461 x 430 mm) C1333P: 16-3/4" x 16-7/8" x 15" (425 x 427 x 380 mm)
Installation Space (W x D)	C1333F: Fully Configured: 16-3/4" x 36-1/8" (425 x 917 mm) (Cassette and Back Door Opened)  C1333P: 16-3/4" x 36-1/8" (425 x 917 mm) (Cassette and Back Door Opened)
Weight	C1333F: Standard: Approx. 48.5 lb. (22.0 kg) <sup>2</sup>  C1333P: Standard: Approx. 35.5 lb. (16.1 kg) <sup>2</sup>
<b>Print Specifications</b>	
Print Speed (Color)	Up to 35 ppm (Letter) <sup>3</sup>
First-Print-Out Time (Letter, Color/BW)	Approx. 7 Seconds
Print Resolution (dpi)	Up to 1200 x 1200 (equivalent)
Standard Page Description Languages	Standard: UFR II, PCL5, PCL5, Adobe® PostScript®3™
Direct Print Supported File Types	Available from USB Memory (TIFF, JPEG, PDF)
Printing from Mobile and Cloud	A range of software solutions (Apple AirPrint, Canon PRINT, Mopria, and uniFLOW Online, Universal Print) are available to provide printing from mobile devices and services <sup>4</sup> depending on your requirements. Please contact your sales representative for further information.
Operating System Standard Printing	Android/Windows® 10/Windows® 11/Chrome OS/macOS (11.2.2)/iOS/iPadOS
Print Feature	Secure Watermark, Header/Footer, Page Layout, Two-Sided Printing, Mixed Paper Sizes/Orientations, Toner Reduction, Poster Printing, Print Date

## SPECIFICATIONS CONTINUED

# imageFORCE C1333F/C1333P

<b>Fonts</b>	PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Barcode fonts <sup>5</sup> PS fonts: 136 Roman
<b>Operating System</b>	UFRIL: Windows® 10/11, Server 2016/Server 2019/Server 2022/Server 2025 MAC OS (10.15 or later) PCL: Windows® 10/11, Server 2016/Server 2019/Server 2022/Server 2025 MAC OS (10.15 or later) PS: Windows® 10/11, Server 2016/Server 2019/Server 2022/Server 2025 MAC OS (10.15 or later) PPD: Windows® 10/11, MAC OS X (10.15 or later)
<b>Copy Specifications<sup>6</sup></b>	
<b>Copy Speed</b>	Up to 35 ppm (Letter)
<b>First-Copy-Out Time (Letter, Color/BW)</b>	Approx. 8.1 seconds or Less
<b>Copy resolution (dpi)</b>	600 x 600
<b>Multiple Copies</b>	Up to 999 Copies
<b>Magnification</b>	Variable Zoom: 25% - 400% (1% Increments)
<b>Copy Features</b>	Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Two-Sided Original, Sort, N on 1, Different Size Originals, Sharpness, Erase Frame, Copy ID Card, Copy Passport, Color Mode, Reserved Copy
<b>Scan Specifications<sup>6</sup></b>	
<b>Type</b>	Single-Pass Duplexing Automatic Document Feeder
<b>Document Feeder Paper Capacity</b>	Up to 50 Sheets (20 lb. Bond)
<b>Document Feeder Supported Media Sizes</b>	Sheet Media Size: Legal, Letter, Statement, Custom size (1-7/8" x 3-3/8" to 8-1/2" x 14")
<b>Document Feeder Media Weights</b>	Single and Double-Sided Scanning: 13.3 lb. Bond to 27.9 lb. Bond (50 to 105 gsm)
<b>Platen Scanning Size</b>	Up to 8-1/2" x 11-3/4"
<b>Pull Scan Specifications</b>	ScanGear MF For both TWAIN and WIA Windows 10/11, macOS (10.15 or later)
<b>Scan Resolution (dpi)</b>	Up to 600 x 600
<b>Scan Method</b>	Push Scan, Pull Scan, Scan to Network, Scan to memory media (USB Memory Key), Scan to cloud-based services (Optional uniFLOW Online)
<b>Scan Speed (Letter)</b>	Copy (300 x 600 dpi): Single-Sided Scanning (BW): 40 ipm Single-Sided Scanning (CL): 20 ipm Double-Sided Scanning (BW): 80 ipm Double-Sided Scanning (CL): 40 ipm  Send (300 x 300 dpi): Single-Sided Scanning (BW): 50 ipm Single-Sided Scanning (CL): 40 ipm Double-Sided Scanning (BW): 100 ipm Double-Sided Scanning (CL): 80 ipm
<b>Memory Media</b>	Standard: USB Memory

<b>Platen Acceptable Originals</b>	Sheet, Book
<b>Send Specifications<sup>6</sup></b>	
<b>Destination</b>	E-mail/Internet FAX (SMTP), SMB, FTP
<b>Address Book</b>	LDAP (50)/Local (300)/Speed dial (281)
<b>Send Resolution (dpi)</b>	192 x 204 (I-FAX) 300 x 300 (email/SMB/FTP)
<b>Communication Protocol</b>	File: FTP (TCP/IP), SMB3.0 (TCP/IP) Email/iFax: SMTP (Send), POP3 (Receive)
<b>File Format</b>	Standard: TIFF, JPEG7, PDF (Compact, Searchable, PDF/A-1b) Optional: PDF (Encrypted, Digital Signature)
<b>Send Features</b>	Original Type Selection, Two-Sided Original, Different-Size Originals, Density Adjustment, Sharpness, Preview, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Originals
<b>Fax Specifications<sup>6</sup></b>	
<b>Modem Speed</b>	Super G3: 33.6 kbps G3: 14.4 kbps
<b>Compression Method</b>	MH, MR, MMR, JBIG
<b>Resolution (dpi)</b>	400 x 400 (Ultrafine), 200 x 400 (Superfine), 200 x 200 (Fine/ Photo), 200 x 100 (Normal)
<b>Sending/Receiving Size</b>	Sending: Statement to LGL Receiving: Statement, LTR and LGL
<b>FAX Memory</b>	Up to 512 Pages
<b>Speed Dials</b>	Max. 281
<b>Group Dials/Destinations</b>	Max. 299 Dials
<b>Sequential Broadcast</b>	Max. 310 Addresses
<b>Memory Backup</b>	Yes
<b>Fax Features</b>	Sender's Name (TTI), Direct Send, Preview, TX Report, Sequential Broadcasting
<b>Security Specifications</b>	
<b>Authentication and Access Control</b>	Department ID Authentication (Department ID and PIN Login, Function level Login) uniFLOW Online <sup>8</sup> (PIN Login, Card Login, Card and PIN Login)
<b>Document Security</b>	C1333F: Print Security (Secure Print, Encrypted Secure Print, uniFLOW Secure Print <sup>8</sup> ), Scan Security <sup>9</sup> (Encrypted PDF, Device Signature PDF/XPS), Send Data Security (Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History)  C1333P: Print Security (Secure Print, Encrypted Secure Print, uniFLOW Secure Print <sup>8</sup> )

## SPECIFICATIONS CONTINUED

# imageFORCE C1333F/C1333P

<b>Network Security</b>	<p>C1333F: TLS 1.3, IPsec, IEEE802.1X authentication, SNMPv3, Firewall Functionality (IP/MAC Address Filtering), Enabling/Disabling (Network Applications, Remote UI, USB Interface), G3 FAX separation from LAN, USB Port separation from LAN, WPA3 Support (Wi-Fi)</p> <p>C1333P: TLS 1.3, IPsec, IEEE802.1X authentication, Firewall Functionality (IP/MAC Address Filtering), Enabling/Disabling(Network Applications, Remote UI, USB Interface), USB Port separation from LAN, SNMPv3, WPA3 Support (Wi-Fi)</p>
<b>Device Security</b>	Job Log Conceal Function, Protecting MFP Software Integrity, Checking MFP Software Integrity at Startup, Verify System at Startup (NIST SP800-193: Protection) <sup>10</sup> , Checking Software Integrity & Platform Firmware Resiliency: Automatic System Recovery (NIST SP800-193: Recovery)
<b>Device Management and Auditing</b>	Administrator Password, Digital Certificate and key Management, Cooperating with External Security Audit System (Security Information and Event Management), Security Policy Setting
<b>Environmental Specifications</b>	
<b>Operating Environment</b>	Temperature: 10 to 30°C Humidity: 20 to 80% RH (Relative Humidity)
<b>Power Requirements</b>	<p>C1333F: 110V-127V 60Hz 6.6A</p> <p>C1333P: 110V-127V 60Hz 6.8A</p>
<b>Power Consumption</b>	<p>C1333F: Maximum: Approx. 1610 W or less Standby: Approx. 24.0 W<sup>11</sup> Sleep Mode: Approx. 1.0 W<sup>12</sup></p> <p>Typical Electricity Consumption (TEC) rating: 0.34 kWh<sup>13</sup></p> <p>C1333P: Maximum: Approx. 1610 W or less Standby: Approx. 24.0 W<sup>11</sup> Sleep mode: Approx. 1.0 W<sup>12</sup></p> <p>Typical Electricity Consumption (TEC) rating: 0.33 kWh<sup>14</sup></p>
<b>Environmental Standards</b>	ENERGY STAR <sup>®</sup> certified EPEAT Silver
<b>Consumables</b>	
<b>Toner Cartridges<sup>15</sup> (All in One Toner Cartridge)</b>	Toner T12 Yellow Toner T12 Magenta Toner T12 Cyan Toner T12 Black
<b>Toner Yield (Estimated @8.5% Coverage)</b>	Yellow/Magenta/Cyan: 5,300 impressions Black: 7,400 impressions

## Paper Source Options

<b>Feeder Options</b>	<p>PAPER FEEDER PF-K1</p> <p>Paper Capacity: 550 Sheets [20 lb. bond (75 gsm)] Paper Type: Thin, Plain, Thick, Color, Recycled, Coated, Pre-punched, Letterhead, PostCard, Paper Size: Letter, Legal, Statement, Executive, Government Letter, Government Legal, Custom Size: 4" x 5-7/8" to 8-1/2" x 14"</p> <p>Paper Weight: 16 lb. Bond to 74 lb. Cover (60 to 200 gsm) Power Source: From the Main Unit Dimensions (W x D x H): 16-1/2" x 16-7/8" x 6-1/8" Weight: Approx.10.1 lb. (4.6kg)</p>
-----------------------	--

## Accessories

<b>Card Readers<sup>16</sup></b>	MiCARD Attachment Kit-B1 <sup>17</sup> Copy Card Reader-F1 <sup>17</sup> Copy Card Reader Attachment-J1 <sup>17</sup>
<b>Data Security<sup>6</sup></b>	Send PDF Security Feature Set-E1
<b>Barcode Printing</b>	Barcode Print Kit-E1
	Provides the ability to print 1D and 2D barcodes on output

<sup>1</sup> Time from device power-on, until print ready (not print reservation).

<sup>2</sup> Including consumables.

<sup>3</sup> Print speed is based on internal testing. Print speed may vary, depending on the number of copies selected as well as the settings for size, type, and orientation of paper.

<sup>4</sup> Subscription to a third-party cloud service required. Subject to third-party cloud service provider's Terms and Conditions.

<sup>5</sup> Optional Barcode Printing Kit-E1 is required.

<sup>6</sup> Only Applies to imageFORCE C1333F model.

<sup>7</sup> Single page only.

<sup>8</sup> Requires optional uniFLOW Online/uniFLOW.

<sup>9</sup> Requires optional PDF SECURITY-E1.

<sup>10</sup> This feature is off by default and must be turned on by the administrator. Warm-up times are affected once turned on.

<sup>11</sup> Reference value: measured one unit.

<sup>12</sup> Sleep mode is not available in all circumstances due to certain settings.

<sup>13</sup> ENERGY STAR Product Specification for Imaging Equipment Version 3.2.

<sup>14</sup> ENERGY STAR Product Specification for Imaging Equipment Version 3.0.

<sup>15</sup> Includes toner, drum, developer, and waste toner hopper.

<sup>16</sup> Attachment kit required.

<sup>17</sup> Ask Canon authorized representative for reader compatibility information.



[usa.canon.com/business](https://usa.canon.com/business)



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified this model as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon, imageFORCE and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Some security features may impact functionality/performance; you may want to test these settings in your environment. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. Trellix and the Trellix logo are trademarks or registered trademarks of Musarubra US LLC or its subsidiaries in the U.S. and other countries. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Representative for details. Products shown with optional accessories. Subscription to a third-party cloud service required. Subject to third-party cloud service providers terms and conditions. uniFLOW is a registered trademark of NT-ware Systemprogrammierung GmbH. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21, or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2026 Canon U.S.A., Inc. All rights reserved.

04.29.26/26-0802-13873