



SPEC SHEET

LIFT YOUR BUSINESS

Arizona 2300 series

The Arizona 2300 series is part of the fifth generation of Arizona systems. The track record extends to more than 8,000 Arizona series printers worldwide since 2007. These systems are renowned for their impressive reliability, accuracy, and incredible, near-photorealistic quality.

Productive, Versatile, Smart

Design complex jobs once, and then easily adapt and repeat to help save time on future projects. The Arizona 2300 series is designed to serve the versatile needs of printers.

This latest addition to the award-winning series of flatbed printers is rock-solid in its basic configuration and ready for upgrades such as a roll media option and additional ink channels, including our white UV ink.

As a global leader in large format imaging systems, Canon has set the market standard for amazing productivity. Join the Arizona family and reap the benefits of instant-on printing and incredible, creative applications. Print after print. Year after year.

Product Range

Arizona 2340 GTF/XTF



Arizona 2360 GTF/XTF



Arizona 2380 GTF/XTF



TECHNICAL SPECIFICATIONS

Arizona 2300 GTF

Printing Technology

4/6/8-channel piezoelectric inkjet system using VariaDot imaging technology.
2340 GTF: CMYK **2360 GTF:** CMYK+W+W/V **2380 GTF:** CMYK+cm+W+W/V

Ink Configurations Resolution

Variable droplet sizes available from 6 to 30 picoliters. The ability to vary the drop size to 6 picoliters helps to produce sharp images with smoother gradients and quartertones than our previous models. The ability to jet larger droplets up to 30 picoliters produces uniform colors. The result is near-photorealistic quality with text as small as 2 pt. (in High Definition mode).

Print Speed

Print Modes				Flatbed		RMO	
	2340 GTF	2360 GTF	2380 GTF	ft ² /h	m ² /h	ft ² /h	m ² /h
High-Key	x	x	x	958	89.0	732	68.0
Express	x	x	x	620	57.6	491	45.6
Production-Fast			x	473	44.0	383	35.6
Production	x	x	x	395	36.7	332	30.8
Quality	x	x	x	280	26.0	242	22.5
Quality-Matte	x	x	x	204	19.0	179	16.6
Quality-Density	x	x	x	156	14.5	137	12.7
Quality-Layered (2)		x	x	140	13.0	121	11.2
Quality-Layered (3)		x	x	93	8.7	80	7.5
Fine Art	x	x	x	226	21.0	198	18.4
High Definition	x	x	x	119	11.1	109	10.1
Varnish (High Gloss)		x	x	~75	~7	N/A	N/A

**Figures are engine print speed only and do not include provisions for image processing, transfer, or post production. Results may vary based on media types and/or applications.*

Ink System

IJC357 or **IJC358** UV-curable inks packed in quick-change, 2- and 3-liter bags for Black, Cyan, Magenta, Yellow, Light Cyan, Light Magenta. White and IJC357 Varnish packed in 1-liter bags.

Available Inksets

IJC358¹ Delivers a matte finish. Recommended option for most applications. Great option for retail displays, indoor/outdoor signage, industrial, packaging, and applications where glare-sensitivity is a consideration. Excellent adhesion to complex materials such as polypropylene.

IJC357¹ Provides a semi-gloss finish with vivid color output, good for retail displays, indoor/outdoor signage, and the preferred choice for tactile printing applications. Excellent media versatility.

System Architecture

True flatbed for rigid media printing with Arizona FLXflow technology: an impressive airflow technique combined with a zone-less, double-origin table layout, supported by eight easy-to-use pneumatic registration pins. In addition, the Roll Media Option is available for flexible media printing.

Geometric Accuracy

	Measured Over Flatbed	RMO	Maximum Error Flatbed	RMO
Line length (system width)	2,500 mm	2,190 mm	± 0.8 mm	± 0.6 mm
Line length (system height)	1,250 mm	2,000 mm	± 0.4 mm	± 1.5 mm
Line straightness (system width)	2,500 mm	2,190 mm	0.7 mm	0.7 mm
Line straightness (system height)	1,250 mm	2,000 mm	0.5 mm	2.0 mm
Diagonal Error ("squareness")	1,250 x 2,500 mm	2,000 x 2,190 mm	1.0 mm	2.5 mm

Rigid Media

Maximum area: 49.2 x 98.4 inches / 125 x 250 cm

Maximum thickness: 2.0 inches / 50.8 mm

Maximum mass: 7 lbs/ft² / 34 kg/m²

Rigid Media Print Area

Up to: 49.6 x 98.8 inches / 126 x 251 cm (for edge-to-edge printing).

Media Roll Specification

35.4 to 86.6 inches / 90 to 220 cm. Up to 110 lbs. / 50 kg (at any width). Maximum diameter: 9.45 inches / 240 mm. Core: 3 inches (inside). Bias: Print-side-in or print-side-out, most types (application dependent).

Roll Media Print Width

Up to 86.2 inches / 219 cm.

Image Processing

ONYX[®] Thrive™ 19 (421 configuration or greater recommended).

Connectivity

10/100/1000 Base-T.

PRISMAguide XL

PRISMAguide XL offers a unique tool set to help save time and money in the creation of multiple-up, multi-layered, duplex, or complex applications. To activate this functionality, the "PRISMAguide XL Resale license" is needed with the Arizona 2300 series printer. It also requires ONYX Thrive to be installed.

Electrical Power / Compressed Air

2 x 200-240 VAC, 50/60 Hz, Single-phase, 16A per circuit.

Circuit Breakers: North America: 20A. Europe: 16A. ROW: See CB Scheme Report.

Clean, dry, compressed air using a Coalescing Filter. Pressure Regulator set to 100 psi (690 kPa) and connects air regulator to ½ inch or 12 mm OD air tubing. Peak flow: 4 cfm at 100 psi (113 l/min at 690 kPa).

Environment

Temperature: 64 - 86°F (18 - 30°C).

Relative humidity: 30 to 70% (non-condensing).

Ventilation: 700 cfm / 1,200 m³ per hour / minimum (see Site Preparation Guide).

Altitude: 9,020 feet (2,750 m) maximum; however, some components specify a limit of 6,560 feet (2,000 m).

Size/Weight

Printer only: 196.9 x 78.7 inches (5.0 m x 2.0 m), 1,951 lbs. (885 kg).

Printer + Roll Media Option: 196.9 x 90.2 inches (5.0 m x 2.29 m), 2,502 lbs. (1,135 kg).

Table height: 34.6 inches (0.88 m) / Overall height: 51.2 inches (1.3 m).

Warranty

24-month limited hardware warranty. Warranty may vary by country as required by law. Go to <https://www.usa.canon.com/support/p/arizona-2300-uv-flatbed-printer-series> to learn about Canon service and support options in your region.

¹ Contact your Canon representative to determine which ink set best aligns with your business requirements.

TECHNICAL SPECIFICATIONS

Arizona 2300 XTF

Printing Technology	4/6/8-channel piezoelectric inkjet system using VariaDot imaging technology.																																																																																																																			
Ink Configurations	2340 XTF: CMYK 2360 XTF: CMYK+W+W/V 2380 XTF: CMYK+cm+W+W/V																																																																																																																			
Resolution	Variable droplet sizes available from 6 to 30 picoliters. The ability to vary the drop size to 6 picoliters produces sharp images with smoother gradients and quartertones. The ability to jet larger droplets up to 30 picoliters produces uniform colors. The result is near-photorealistic quality with sharpness only before seen at resolutions of 1,440 dpi or higher. Text as small as 2 pt. is perfectly legible (in High Definition mode).																																																																																																																			
Print Speed	<table border="0"> <thead> <tr> <th rowspan="2">Print Modes</th> <th rowspan="2">2340 GTF</th> <th rowspan="2">2360 GTF</th> <th rowspan="2">2380 GTF</th> <th colspan="2">Flatbed</th> <th colspan="2">RMO</th> </tr> <tr> <th>ft²/h</th> <th>m²/h</th> <th>ft²/h</th> <th>m²/h</th> </tr> </thead> <tbody> <tr> <td>High-Key</td> <td>x</td> <td>x</td> <td>x</td> <td>1,023</td> <td>95</td> <td>732</td> <td>68.0</td> </tr> <tr> <td>Express</td> <td>x</td> <td>x</td> <td>x</td> <td>691</td> <td>64.2</td> <td>491</td> <td>45.6</td> </tr> <tr> <td>Production-Fast</td> <td></td> <td></td> <td>x</td> <td>514</td> <td>47.8</td> <td>383</td> <td>35.6</td> </tr> <tr> <td>Production</td> <td>x</td> <td>x</td> <td>x</td> <td>427</td> <td>39.7</td> <td>332</td> <td>30.8</td> </tr> <tr> <td>Quality</td> <td>x</td> <td>x</td> <td>x</td> <td>297</td> <td>27.6</td> <td>242</td> <td>22.5</td> </tr> <tr> <td>Quality-Matte</td> <td>x</td> <td>x</td> <td>x</td> <td>212</td> <td>19.7</td> <td>179</td> <td>16.6</td> </tr> <tr> <td>Quality-Density</td> <td>x</td> <td>x</td> <td>x</td> <td>164</td> <td>15.3</td> <td>137</td> <td>12.7</td> </tr> <tr> <td>Quality-Layered (2)</td> <td></td> <td>x</td> <td>x</td> <td>148</td> <td>13.8</td> <td>121</td> <td>11.2</td> </tr> <tr> <td>Quality-Layered (3)</td> <td></td> <td>x</td> <td>x</td> <td>99</td> <td>9.2</td> <td>80</td> <td>7.5</td> </tr> <tr> <td>Fine Art</td> <td>x</td> <td>x</td> <td>x</td> <td>235</td> <td>21.8</td> <td>198</td> <td>18.4</td> </tr> <tr> <td>High Definition</td> <td>x</td> <td>x</td> <td>x</td> <td>131</td> <td>12.2</td> <td>109</td> <td>10.1</td> </tr> <tr> <td>Varnish (High Gloss)</td> <td></td> <td>x</td> <td>x</td> <td>97</td> <td>~9</td> <td>N/A</td> <td>N/A</td> </tr> </tbody> </table>								Print Modes	2340 GTF	2360 GTF	2380 GTF	Flatbed		RMO		ft ² /h	m ² /h	ft ² /h	m ² /h	High-Key	x	x	x	1,023	95	732	68.0	Express	x	x	x	691	64.2	491	45.6	Production-Fast			x	514	47.8	383	35.6	Production	x	x	x	427	39.7	332	30.8	Quality	x	x	x	297	27.6	242	22.5	Quality-Matte	x	x	x	212	19.7	179	16.6	Quality-Density	x	x	x	164	15.3	137	12.7	Quality-Layered (2)		x	x	148	13.8	121	11.2	Quality-Layered (3)		x	x	99	9.2	80	7.5	Fine Art	x	x	x	235	21.8	198	18.4	High Definition	x	x	x	131	12.2	109	10.1	Varnish (High Gloss)		x	x	97	~9	N/A	N/A
Print Modes	2340 GTF	2360 GTF	2380 GTF	Flatbed		RMO																																																																																																														
				ft ² /h	m ² /h	ft ² /h	m ² /h																																																																																																													
High-Key	x	x	x	1,023	95	732	68.0																																																																																																													
Express	x	x	x	691	64.2	491	45.6																																																																																																													
Production-Fast			x	514	47.8	383	35.6																																																																																																													
Production	x	x	x	427	39.7	332	30.8																																																																																																													
Quality	x	x	x	297	27.6	242	22.5																																																																																																													
Quality-Matte	x	x	x	212	19.7	179	16.6																																																																																																													
Quality-Density	x	x	x	164	15.3	137	12.7																																																																																																													
Quality-Layered (2)		x	x	148	13.8	121	11.2																																																																																																													
Quality-Layered (3)		x	x	99	9.2	80	7.5																																																																																																													
Fine Art	x	x	x	235	21.8	198	18.4																																																																																																													
High Definition	x	x	x	131	12.2	109	10.1																																																																																																													
Varnish (High Gloss)		x	x	97	~9	N/A	N/A																																																																																																													
Ink System	UV-curable inks IJC357 or IJC358 packed in quick-change, 2- and 3-liter bags for Black, Cyan, Magenta, Yellow, Light Cyan, Light Magenta. White and IJC357 Varnish packed in 1-liter bags.																																																																																																																			
Available Inksets	<p>IJC358¹ Delivers a matte finish. Recommended option for most applications. Great option for retail displays, indoor/outdoor signage, industrial, packaging, and applications where glare-sensitivity is a consideration. Excellent adhesion to complex materials such as polypropylene.</p> <p>IJC357¹ Provides a semi-gloss finish with vivid color output, good for retail displays, indoor/outdoor signage, and the preferred choice for tactile printing applications. Excellent media versatility.</p>																																																																																																																			
System Architecture	True flatbed for rigid media printing with Arizona FLXflow technology: an impressive airflow technique combined with a zone-less, double-origin table layout, supported by 16 easy-to-use pneumatic registration pins. In addition, the Roll Media Option is available for flexible media printing.																																																																																																																			
Geometric Accuracy	<table border="0"> <thead> <tr> <th></th> <th>Measured Over Flatbed</th> <th>RMO</th> <th>Maximum Error Flatbed</th> <th>RMO</th> </tr> </thead> <tbody> <tr> <td>Line length (system width)</td> <td>2,500 mm</td> <td>2,190 mm</td> <td>± 0.8 mm</td> <td>± 0.6 mm</td> </tr> <tr> <td>Line length (system height)</td> <td>3,080 mm</td> <td>2,000 mm</td> <td>± 1.0 mm</td> <td>± 1.5 mm</td> </tr> <tr> <td>Line straightness (system width)</td> <td>2,500 mm</td> <td>2,190 mm</td> <td>0.7 mm</td> <td>0.7 mm</td> </tr> <tr> <td>Line straightness (system height)</td> <td>3,080 mm</td> <td>2,000 mm</td> <td>0.7 mm</td> <td>2.0 mm</td> </tr> <tr> <td>Diagonal Error ("squareness")</td> <td>3,080 x 2,500 mm</td> <td>2,000 x 2,190 mm</td> <td>1.0 mm</td> <td>2.5 mm</td> </tr> </tbody> </table>									Measured Over Flatbed	RMO	Maximum Error Flatbed	RMO	Line length (system width)	2,500 mm	2,190 mm	± 0.8 mm	± 0.6 mm	Line length (system height)	3,080 mm	2,000 mm	± 1.0 mm	± 1.5 mm	Line straightness (system width)	2,500 mm	2,190 mm	0.7 mm	0.7 mm	Line straightness (system height)	3,080 mm	2,000 mm	0.7 mm	2.0 mm	Diagonal Error ("squareness")	3,080 x 2,500 mm	2,000 x 2,190 mm	1.0 mm	2.5 mm																																																																														
	Measured Over Flatbed	RMO	Maximum Error Flatbed	RMO																																																																																																																
Line length (system width)	2,500 mm	2,190 mm	± 0.8 mm	± 0.6 mm																																																																																																																
Line length (system height)	3,080 mm	2,000 mm	± 1.0 mm	± 1.5 mm																																																																																																																
Line straightness (system width)	2,500 mm	2,190 mm	0.7 mm	0.7 mm																																																																																																																
Line straightness (system height)	3,080 mm	2,000 mm	0.7 mm	2.0 mm																																																																																																																
Diagonal Error ("squareness")	3,080 x 2,500 mm	2,000 x 2,190 mm	1.0 mm	2.5 mm																																																																																																																
Rigid Media	<p>Maximum area: 121.3 x 98.4 inches / 308 x 250 cm (320 x N cm permitted w/308 cm vacuum)</p> <p>Maximum thickness: 2.0 inches / 50.8 mm</p> <p>Maximum mass: 7 lbs./ft² / 34 kg/m²</p>																																																																																																																			
Rigid Media Print Area	Up to: 121.7 x 98.8 inches / 309 x 251 cm / (321 x N cm permitted w/308 cm vacuum).																																																																																																																			
Media Roll Specification	35.4 to 86.6 inches / 90 to 220 cm. Up to 110 lbs. / 50 kg (at any width). Maximum diameter: 9.45 inches / 240 mm. Core: 3 inches (inside). Bias: Print-side-in or print-side-out, most types (application dependent).																																																																																																																			
Roll Media Print Width	Up to 86.2 inches / 219 cm.																																																																																																																			
Image Processing	ONYX [®] Thrive™ 19 (421 configuration or greater recommended).																																																																																																																			
Connectivity	10/100/1000 Base-T.																																																																																																																			
PRISMAguide XL	PRISMAguide XL offers a unique tool set to help save time and money in the creation of multiple-up, multi-layered, duplex, or complex applications. To activate this functionality, the "PRISMAguide XL Resale license" is needed with the Arizona 2300 series printer. It also requires ONYX Thrive to be installed.																																																																																																																			
Electrical Power / Compressed Air	<p>2 x 200-240 VAC, 50/60 Hz, Single-phase, 16A per circuit.</p> <p>Circuit Breakers: North America: 20A. Europe: 16A. ROW: See CB Scheme Report.</p> <p>Clean, dry, compressed air using a Coalescing Filter. Pressure Regulator set to 100 psi (690 kPa) and connects air regulator to ½ inch or 12 mm OD air tubing.</p>																																																																																																																			
Peak flow:	4 cfm at 100 psi (113 l/min at 690 kPa).																																																																																																																			
Environment Temperature:	64 - 86 °F (18 - 30°C).																																																																																																																			
Relative humidity:	30 to 70% (non-condensing).																																																																																																																			
Ventilation:	700 cfm / 1,200 m ³ per hour / minimum (see Site Preparation Guide).																																																																																																																			
Altitude:	Maximum limit of 6,560 feet (2,000 m).																																																																																																																			
Size/Weight	Printer only: 196.9 x 150.8 inches (5.0 m x 2.0 m), 4,169 lbs. (1,891 kg).																																																																																																																			
Printer + Roll Media Option:	196.9 x 162.2 inches (5.0 m x 4.12 m), 4,720 lbs. (2,141 kg).																																																																																																																			
Table height:	34.6 inches (0.88 m) / Overall height: 51.2 inches (1.3 m).																																																																																																																			
Warranty	24-month limited hardware warranty. Warranty may vary by country as required by law. Go to https://www.usa.canon.com/support/p/arizona-2300-uv-flatbed-printer-series to learn about Canon service and support options in your region.																																																																																																																			

¹ Contact your Canon representative to determine which ink set best aligns with your business requirements.



usa.canon.com/largeformat