



CINE-SERVO 40-1200mm T5.0-10.8

Model Name		CINE-SERVO 40-1200mm T5.0-10.8 RF	CINE-SERVO 40-1200mm T5.0-10.8 PL
Mount Type		RF mount	PL mount
Lens Communication		Canon Cinema EOS RF	Cooke/i Technology, ZEISS eXtended Data
Zoom Ratio		30x	
Built-in Extender		Yes (1.5x)	
Focal Length		40 - 1200 mm 60 - 1800 mm*	
Maximum Diameter Ratio (T-number)		T5.0 at 40 - 560 mm / T10.8 at 1200 mm T7.5 at 60 - 840 mm / T16.2 at 1800 mm*	
Number of Iris Blades		11 blades	
Angle of View	Aspect ratio 1.78:1 24.6 x 13.8 mm	34.2°x 19.6°at 40 mm / 1.17°x 0.66°at 1200 mm 23.2°x 13.1°at 60 mm / 0.78°x 0.44°at 1800 mm*	
	Aspect ratio 1.9:1 26.2 x 13.8 mm	36.3°x 19.6°at 40 mm / 1.25°x 0.66°at 1200 mm 24.6°x 13.1°at 60 mm / 0.83°x 0.44°at 1800 mm*	
	Aspect ratio 1.9:1 38.1 x 20.1 mm	35.2°x 19.0°at 60 mm / 1.21°x 0.64°at 1800 mm*	
	Aspect ratio 1.5:1 36 x 24 mm	33.4°x 22.6°at 60 mm / 1.15°x 0.76°at 1800 mm*	
Minimum Shooting Distance		3.5 m / 11.5'	
Field of View at Minimum Shooting Distance	Aspect ratio 1.78:1 24.6 x 13.8 mm	170.3 x 95.5 cm at 40 mm / 5.9 x 3.3 cm at 1200 mm 113.5 x 63.7 cm at 60 mm / 3.9 x 2.2 cm at 1800 mm*	
	Aspect ratio 1.9:1 26.2 x 13.8 mm	181.4 x 95.5 cm at 40 mm / 6.3 x 3.3 cm at 1200 mm 175.8 x 92.8 cm at 60 mm / 6.1 x 3.2 cm at 1800 mm*	
	Aspect ratio 1.9:1 38.1 x 20.1 mm	175.8 x 92.8 cm at 60 mm / 6.1 x 3.2 cm at 1800 mm*	
	Aspect ratio 1.5:1 36 x 24 mm	166.1 x 110.7 cm at 60 mm / 5.8 x 3.8 cm at 1800 mm*	
Front Diameter		Φ 136mm	
Image Circle		Φ 29.6mm / Φ 43.3mm*	
Filter Diameter: Hood/Lens		Φ 127 mm	
Drive Unit (Detachable)		3x Hirose 20-pin: 1x Zoom, 1x Focus, 1x Virtual Lens Data	
Outer Dimensions(W x H x D)		Appx. 174.9 x 170.6 x 437.2 mm	Appx. 174.9 x 170.6 x 405.2 mm
Weight		Appx. 14.8 lbs (6.7 kg)	Appx. 14.6 lbs (6.6 kg)

*When used with 1.5x extender