

Environmental Profile Sheet

The imageRUNNER ADVANCE DX C3935i/C3930i/C3926i models incorporate technologies with a strong environmental focus at every stage of the product lifecycle—Produce, Use, and Recycle. The technologies below focus on Energy Conservation, Resource Conservation, and Pollution Prevention and form the foundation of Canon’s Environmental Management System.

	Energy Conservation	Resource Conservation	Pollution Prevention
In order to help reduce dependence on petroleum-based materials, Canon uses 100% reused plastics .*			
A variety of sleep recovery triggers help encourage the use of Sleep Mode , helping to minimize power consumption.			
Power consumption in Sleep Mode is as low as 0.80 W!			
Low Typical Electricity Consumption (TEC) values , which measure power consumption during a one-week period.			
Power consumption is reduced by utilizing White LED array technology in its Color Image Reader versus using a traditional Xenon tube!			
Power consumption is reduced by utilizing Canon Image Sensor technology versus using traditional CCD sensors! Advanced Color RAPID Fusing technologies help reduce power consumption and limit the warm-up period .			
Lower Melting Temperature Toner helps reduce fusing temperature requirements .			
Use of full cardboard packaging for environmental considerations .			
All suppliers are required to meet Canon’s stringent Green Procurement policy and environmental terms. This helps Canon exceed the tough European Union’s RoHS Directive, which controls/restricts the use of certain hazardous substances .			
Each system is equipped with paper-, toner-, and energy-saving features that help to cut costs and conserve resources .			
Long-life parts and high-yield supplies help maximize uptime and help reduce the amount of materials consumed during the product life cycle.			

* Excluding a small amount of additives to improve physical properties.

Canon. The Natural Partner for Business.



imageRUNNER ADVANCE DX C3935i shown with optional Inner Finisher-L1.

Environment-Related Specifications

System Type

Color Laser Multifunctional

Functions

Standard: Print (UFR III, PCL® 6, Adobe® PostScript® 3™), Copy, Scan, Send, Store

Optional: Fax (Up to two lines)

Operation Panel

10.1" TFT LCD WSVGA
Color Flat-panel

Warm-up Time

From Power On: Approx. 10 Seconds

From Sleep Mode: Approx. 10 Seconds

Quick Startup Mode: Approx. 4 Seconds

Power Requirements

110-127 V AC, 60 Hz, 8.5 A

Power Consumption

Maximum: 1,500 W

Sleep Mode: 0.80 W

Copying/Printing: 606 W

Plug-in: 0.40 W

One Week TEC

C3935i: 0.33 kWh

C3930i: 0.29 kWh

C3926i: 0.26 kWh

One Year TEC

C3935i: 17.2 kWh

C3930i: 15.1 kWh

C3926i: 13.5 kWh

British Thermal Units (BTU)

Maximum (BTU/Hr.): 5,119

Copying/Printing (BTU/Hr.): 2,068

Plug:

NEMA 5-15P

Dimensions (W x D x H)

22-1/4" x 28-1/2" x 35-3/8" (565 mm x 722 mm x 897 mm)

Installation Space (W x D)

Basic: 38-1/2" x 44-1/8" (978 mm x 1119 mm) [Right cover and Paper Cassette open + Multi-Purpose Tray extension extended]

Fully Configured: 65" x 44-1/8" (1651 mm x 1119 mm)

Weight

Approx. 185.2 lb. (84 kg)*

Noise Levels (LwA,m [B])**

Copying/Printing***	Color	Black-and-White
C3935i:	6.4 B	6.4 B
C3930i:	6.2 B	6.1 B
C3926i:	6.2 B	6.1 B

Recycled Content

Recycled Primary Package (%)■ Approx. 27.0%

Secondary Waste Materials: †† 0.0%

Recycled PETE Product:††† 0.0%

Recycled Paper Support

100% Post-consumer Content: Yes

Environmental Standards Compliance

ENERGY STAR® Certified■■■

EPEAT® Gold■■■

Environment-conscious Features

Two-sided, Copy Sample, Confirmation/Cancel, Image Combination, ID Card Copy, Secured Print, Job Forwarding, Department ID Management, Access Management System, Authentication (Universal Login Manager), Standard Duplex Driver, Auto/Weekly Sleep Timer, Auto/Weekly Shutdown Timer, Staple-Free Stapling (Optional)

* Includes Main Unit, ADF, and Consumables.

** 1[B] =10[dB].

*** Measured in accordance with ISO7796. Presented in accordance with ISO9296.

■ Percentage based on weight of recycled content.

†† The percentage of reused waste material.

††† The percentage of recycled PETE material.

■■■ ENERGY STAR, TEC Values, and EPEAT is based off of ENERGY STAR version 3.0.

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has qualified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks of the EPA. PostScript® 3™ is either a registered trademark or trademark of Adobe Systems Incorporated in the United States and/or other countries. PCL 6 is a trademark of Hewlett Packard Company. Canon, imageRUNNER, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. All other referenced product names and marks are trademarks of their respective owners. Specifications and availability subject to change without notice. Not responsible for typographical errors.
©2023 Canon U.S.A., Inc. All rights reserved.

Canon

usa.canon.com

