



imagePRESS Lite C270/C265

MULTIFUNCTION PRINTERS



imagePRESS Lite C270 shown with optional accessories.

PRODUCT SPECIFICATIONS

MARKING ENGINE

Technology: Electrophotography

Print Speed (Color/BW)
8.5" x 11": C270: Up to 70/80 ipm
C265: Up to 65/70 ipm
11" x 17": C270: Up to 35/40 ipm
C265: Up to 32/35 ipm

Print Resolution: 2400 x 2400 dpi

First-Copy-Out Time¹
BW: C270: 4.4 Seconds/C265: 4.8 Seconds
Color: C270: 5.4 Seconds/C265: 5.9 Seconds

Warm-Up Time
From Power ON: Approx. 30 Seconds²
From Sleep Mode: Approx. 30 Seconds³
Quick Startup Mode: Approx. 4 Seconds⁴

Memory: 4.0 GB RAM

Solid-State Drive
Standard: 256 GB
Maximum: 1 TB

Mirroring Solid-State Drive
Optional: 256 GB, 1 TB
Method: Raid 1

Paper Size
Tray 1/2: Letter
Tray 3/4: 5.5" x 7.17" to 13" x 19.2"
Stack Bypass: 4" x 5.9" to 13" x 19.2"

Paper Capacity⁵
Letter: 3,300 Sheets
11" x 17": 1,100 Sheets
Stack Bypass: 250 Sheets

Paper Weight

Tray 1/2: 14 lb. Bond to 80 lb. Cover (52 to 220 gsm)
Tray 3/4: 14 lb. Bond to 140 lb. Index (52 to 256 gsm)
Stack Bypass: 14 lb. Bond to 130 lb. Cover (52 to 350 gsm)

Automatic Duplex

Paper Size: Up to 13" x 19.2"
Paper Weight: Up to 80 lb. Cover (220 gsm)

Envelopes:⁶ #10, Monarch, ISO-DL
(Custom Size: 3.94" x 5.83" to 13" x 19.2")

Long Sheets:⁷ Up to 13" x 51.2"

Direct Print Available from USB, Advanced Box, Remote UI, and Web Access⁸

Supported File Types: PDF, TIFF, JPEG, EPS⁹, XPS

Control Panel

Standard: 10.1" TFT LCD WSVGA Color Touch-Panel

Power Consumption

Maximum: C270: 2,500 W/C265: 2,000 W
Standby: C270: 111.2 W/C265: 119.2 W¹⁰
Sleep Mode: 0.9 W¹¹

Typical Electricity Consumption (TEC) Rating: C270: 1.45 kWh/C265: 1.29 kWh

Standards: ENERGY STAR Certified
Rated EPEAT Gold¹²

Power Source: C270: 208-240 V AC, 50/60 Hz, 12 A
C265: 120-127 V AC, 60 Hz, 16 A

Weight: 593 lb.

Dimensions (W x D x H): 27.1" x 37.1" x 46.7"

imagePRESS LITE C270 SERIES PRODUCT SPECIFICATIONS (Continued)

SCANNING

Type: Color Platen and Single-Pass Duplexing Automatic Document Feeder

Document Feeder

Paper Capacity:⁵ 200 Sheets

Supported Media Sizes: 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Custom Size (2.75" x 5.5" to 12" x 17")

Supported Media Weights

BW Original: 13 lb. Bond to 80 lb. Cover (50 to 220 gsm)
Color Original: 17 lb. Bond to 80 lb. Cover (64 to 220 gsm)

Platen Acceptable Originals: Sheet, Book, 3-Dimensional Objects (Height: Up to 2"; Weight: up to 4.4 lb.)

Pull Scan: Color Network ScanGear2 for both Twain and WIA

Scan Resolution (dpi): 600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Scan Speed:

Single-Sided Scanning (BW): 135 ipm

Single-Sided Scanning (Color): 135 ipm

Double-Sided Scanning (BW): 270 ipm

Double-Sided Scanning (Color): 270 ipm

SEND

Destination: Email/Internet Fax (SMTP), SMB v3.0, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)

Color Mode: Automatic-Color Select (Full Color/Grayscale), Automatic-Color Select (Full Color/Black-and-White), Full Color, Grayscale, and Black-and-White

Address Book: LDAP (2,000)/Local (1,600)/Speed dial (200)

Send Resolution (dpi): 600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Communication Protocol

File: FTP (TCP/IP), SMB v3.0, WebDAV
Email: SMTP, POP3

File Format

Standard: TIFF, JPEG, PDF (Encrypted, Compact, Searchable, Apply Policy, Optimize for Web, PDF A/1-b, Limited Color, Device Signature, User Signature, Trace & Smooth), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)

Universal Send Features: Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, Email Priority, TX Report, Original Content Orientation, Skip Blank Pages, Detect Feeder Multi Sheet Feed

FAX (OPTIONAL)

Maximum Number of Connection Lines: 2

Modem Speed

Super G3: 33.6 Kbps
G3: 14.4 Kbps

Compression Method: MH, MR, MMR, JBIG

Resolution (dpi): 400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size: Statement-R to 11" x 17"

Fax Memory: Up to 30,000 Pages

Speed Dials: Max. 200

Group Dials/Destinations: Max. 199 Dials

Sequential Broadcast: Max. 256 Addresses

Memory Backup: Yes

Fax Features: Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Select Line, Selecting the Telephone Line, Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed

SECURITY

Authentication

Standard: OAuth 2.0 Authentication, SMTP Authentication, POP Authentication before SMTP, S/MIME, Universal Log-in Manager, User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in
Optional: uniFLOW Online

Data

Standard: Trusted Platform Module (TPM 2.0), Solid-State Drive Lock, Solid-State Drive Initialize, Mail Box Password Protection, Solid-State Drive Encryption (FIPS140-3 Validated), Verify System at Startup with Auto Recovery, Trellix Embedded Control,¹⁴ HCD-PP Certification¹⁵

Optional: Solid-State Drive Mirroring

Network

Standard: Encrypted Secure Print, IP/Mac Address Filtering, IPsec, TLS Encrypted Communication (v1.0/1.1/1.2/1.3),¹³ SNMP V3.0, IEEE 802.1X, IPv6, SIEM Integration

Document

Standard: Secure Watermark, Secure Print, Forced Hold Printing, Adobe LiveCycle Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device Signature, User Signatures

INPUT ACCESSORIES

Letter Paper Deck Unit-E1

Paper Capacity:⁵ Up to 3,500 Sheets
Paper Size: Letter
Paper Weight: 14 lb. Bond to 140 lb. Index (52 to 256 gsm)
Power Source: From the Main Engine
Weight: 75 lb.
Dimensions (W x D x H): 13.4" x 24.9" x 22.5"

POD Deck Lite-C1

Paper Capacity:⁵ Up to 3,500 Sheets
Paper Size: 5.5" x 5.83" to 13" x 19.2"
Paper Weight: 14 lb. Bond to 130 lb. Cover (52 to 350 gsm)
Envelopes: 5.5" x 5.83" to 13" x 19.2"
Power Source: 120-127 V, 60 Hz, 2.2 A
Weight: 168 lb.
Dimensions (W x D x H): 25.9" x 27.0" x 22.6"

Long Sheet Feeding and Catch Tray-B1

Paper Capacity: 1 Sheet
Paper Size: 4" x 5.83" to 13" x 51.2"
Paper Weight: 17 lb. Bond to 130 lb. Cover (64 to 350 gsm)
Envelopes: 4" x 5.83" to 13" x 19.2"
Weight: 2 lb.
Dimensions (W x D x H): 85.6" x 56.1" x 56.1"

imagePRESS LITE C270 SERIES PRODUCT SPECIFICATIONS (Continued)

Multi Drawer Paper Deck-E1

Paper Capacity: ⁵	Up to 5,000 Sheets
Paper Size:	Supports Up to 13" x 19"
Paper Weight:	14 lb. Bond to 130 lb. Cover (52 to 350 gsm)
Power Source:	From the Main Engine
Weight:	392.4 lb.
Dimensions (W x D x H):	40" x 31.5" x 42.5" (990 mm x 800 mm x 1080 mm)

Stack Bypass-D1

Paper Capacity: ⁵	Up to 250 Sheets
Paper Size:	Supports Up to 13" x 19"
Paper Weight:	14 lb. Bond to 130 lb. Cover (52 to 350 gsm)
Power Source:	From the Main Engine
Weight:	15.4 lb.
Dimensions (W x D x H):	3.2" x 20.4" x 13.9" (82 mm x 518 mm x 351 mm)

FINISHING ACCESSORIES

Copy Tray-R2

Paper Capacity: ⁵	Up to 250 Sheets
Paper Size:	14 lb. Bond to 130 lb. Cover (52 to 350 gsm)
Paper Weight:	4" x 5.83" to 13" x 19.2"
Weight:	2.6 lb.
Dimensions (W x D x H):	16.6" x 15" x 6.8"

Document Insertion Unit-R1¹⁶

Tray Capacity ⁵	
Upper Tray:	Up to 200 Sheets
Lower Tray:	Up to 200 Sheets
Paper Weight:	14 lb. Bond to 110 lb. Cover (52 to 300 gsm)
Paper Size:	7.2" x 7.2" to 13" x 19.2"
Power Supply:	100-240 V, 50/60 Hz, 1.0 A
Weight:	135 lb.
Dimensions (W x D x H):	29.4" x 31.3" x 55.4"

Document Insertion/Folding Unit-K1¹⁷

Number of Trays:	1
Tray Capacity: ⁵	Up to 100 Sheets
Insertion Paper Size:	13" x 19", 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive
Insertion Paper Weight:	16 lb. Bond to 140 lb. Index (60 to 256 gsm)
Fold Types:	C-Fold, Z-Fold
Fold Paper Size	
C-Fold:	Letter-R
Z-Fold:	11" x 17", Legal, Letter-R
Fold Paper Weight:	16 lb. Bond to 28 lb. Bond (60 to 105 gsm)
Power Requirements:	100-240 V AC, 50/60 Hz, 1 A
Weight:	167.6 lb.
Dimensions (W x D x H):	26.1" x 26.8" x 48.9"

Multi Function Professional Puncher-C1¹⁶

Paper Weight	
Punching:	20 lb. Bond to 110 lb. Cover (75 to 300 gsm)
Paper Size	
Punching:	Letter-R, Letter, Legal, 11" x 17", 12" x 18"
Die Set Patterns:	Loose Leaf 3-Hole/5-Hole, Velo Bind 11-Hole, Plastic Comb 19-Hole, Twin Loop 21-Hole/ 32-Hole, Color Coil 44-Hole/Crease Die
Power Supply:	100-127 V, 60 Hz, 15 A
Weight:	225 lb.
Dimensions (W x D x H):	17.5" x 31.3" x 41"

Paper Folding Unit-K1¹⁶

Paper Size	
Double Parallel:	Legal, Letter-R
C-Fold/Accordion/ Half-Fold:	Letter-R
Z-Fold:	Letter-R, 11" x 17", Legal
Paper Weights:	14 lb. Bond to 28 lb. Bond (52 to 105 gsm)
Power Source:	From Finisher
Weight:	157 lb.
Dimensions (W x D x H):	13.3" x 31.3" x 46.9"

Staple Finisher-AC1/Booklet Finisher-AC2

Tray Capacity ⁵	
Top Tray:	Up to 250 Sheets
Middle Tray:	Up to 250 Sheets
Lower Tray:	Up to 3,000 Sheets
Saddle-Stitch Tray:	Up to 25 Booklets
Paper Weight	
Stacking:	14 lb. Bond to 130 lb. Cover (52 to 350 gsm)
Corner Stapling:	14 lb. Bond to 140 lb. Index (52 to 256 gsm)
Booklet-Making:	14 lb. Bond to 140 lb. Index (52 to 256 gsm)

Staple Positions: Corner, Double-Side, Eco

Paper Size

Stapling:	Executive, Letter-R, Letter, Legal, 11" x 17"
Saddle Finisher:	5.5" x 7.2" to 11.8" x 17"

Stapling Capacity⁵

Corner/Double-Side:	Up to 65 Sheets
Eco-Stitched:	Up to 5 Sheets
Saddle-Stitched:	Up to 20 Sheets
V-Folding:	Up to 3 Sheets Without Stitch

Power Source: From the Main Unit

Weight Staple Finisher: 80 lb.

Booklet Finisher: 131 lb.

Dimensions (W x D x H): 25.5" x 25.9" x 44.1"

2-/3-Hole Puncher Unit-A1¹⁷

Paper Weight:	14 lb. Bond to 110 lb. Cover (52 to 300 gsm)
Paper Sizes	
2-Hole:	Legal, Executive, Letter, Letter-R, 11" x 17"
3-Hole:	11" x 17", Letter, Executive
Paper Weight:	14 lb. Bond to 110 lb. Cover (52 to 300 gsm)
Power Supply:	From the Finisher

Staple Finisher-AG/Booklet Finisher-AG1

Tray Capacity ⁵	
Top Tray:	Up to 1,000 Sheets
Lower Tray:	Up to 4,000 Sheets
Saddle-Stitch Tray:	Up to 30 Booklets or Limitless
Paper Weight	
Stacking:	14 lb. Bond to 130 lb. Cover (52 to 350 gsm)
Corner Stapling:	14 lb. Bond to 110 lb. Cover (52 to 300 gsm)
Booklet-Making:	14 lb. Bond to 110 lb. Cover (52 to 300 gsm)
Staple Positions:	Corner, Double-Side
Paper Size	
Stapling:	8.3" x 11" to 11.7" x 17"
Saddle Finisher:	8.3" x 11" to 13" x 19.2"
Stapling Capacity	
Corner/Double-Side:	Up to 100 Sheets
Saddle-Stitched:	Up to 25 Sheets
V-Folding:	Up to 5 Sheets Without Stitch
Power Source:	120/240 V, 60 Hz, 8 A
Weight	
Staple Finisher:	287 lb.
Booklet Finisher:	397 lb.
Dimensions (W x D x H):	31.5" x 31.3" x 48.8"

imagePRESS LITE C270 SERIES PRODUCT SPECIFICATIONS (Continued)

Puncher Unit-BS1¹⁶

Paper Sizes

2-Hole:	Legal, Executive, Letter, Letter-R, 11" x 17", Custom Size (7.2" x 7.2" to 11.8" x 17")
3-Hole:	11" x 17", Letter, Executive-R, Custom Size (9.5" x 7.2" to 11.8" x 17")

Paper Weight:	14 lb. Bond to 110 lb. Cover (52 to 300 gsm)
Punch Waste Capacity:	Up to 6,000 Sheets
Power Supply:	From the Finisher

Booklet Trimmer-G1¹⁶

Margin Trimming:	Front-Edge Trim
Trim Amount:	0.08" to 1.1"
Paper Weight:	14 lb. Bond to 110 lb. Cover (52 to 300 gsm)
Power Supply:	From the Finisher
Weight:	392 lb.
Dimensions (W x D x H):	82.5" x 30.8" x 41"

Print Servers

imagePRESS Printer Kit-G1E (Standard)

PDL:	PS, PCL, UFR
Memory:	3.5 GB
Hard Drive:	1.5 TB

imagePRESS Server M20

Fiery System Software:	FS500
CPU:	Intel® Pentium® Processor G4400, 3.7 GHz
Memory:	8 GB
Hard Drive:	500 GB
OS:	Linux
Standard:	Fiery Command WorkStation, Paper Catalog, Fiery Spot On, Fiery Remote Scan, Hot Folders
Optional:	APPE, Automation Package, ColorRight Package, Impose, Compose, JobMaster

- ¹ Letter-sized stocks.
- ² Time from device power ON until copy-ready (not print reservation).
- ³ Time from exiting Sleep Mode to when printing is operational.
- ⁴ Time from device power ON to when key operations can be performed on the touch-panel display.
- ⁵ Capacity based on 20 lb. Bond Letter.
- ⁶ Envelope Attachment Kit required.
- ⁷ The service mode setting is required.
- ⁸ PDF print from websites is supported.
- ⁹ EPS can be printed directly only from the Remote User Interface.
- ¹⁰ Reference Value: measured one unit.
- ¹¹ 0.9 W Sleep Mode is not available in all circumstances due to certain settings.
- ¹² For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net.
- ¹³ Letter, 300 dpi
- ¹⁴ Requires Unified Firmware Platform v3.10 or newer.
- ¹⁵ For HCD-PP compliance, a Common Criteria Certification is required and currently under evaluation.
- ¹⁶ Staple/Booklet Finisher-AG1 required.
- ¹⁷ Staple Finisher-AC1 or Booklet Finisher-AC2 required.

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon and imagePRESS are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. uniFLOW is a registered trademark of NT-ware Systemprogrammierung GmbH. All other referenced product names and marks are trademarks of their respective owners. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. Some security features may impact functionality/performance; you may want to test these settings in your environment. All features discussed may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Subscription to a third-party cloud service required. Subject to third-party cloud service providers' Terms and Conditions. All printer output images are simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors. ©2024 Canon U.S.A., Inc. All rights reserved

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims on unauthorized copying.

11/24-1462-11568

Canon

usa.canon.com



Trellix

UFP UNIFIED FIRMWARE PLATFORM

CANON GENUINE TONER, CARTRIDGE & PARTS