

Canon

FAXPHONE L190

Revolutionizing Today's Workspace

Multifunction Laser Fax Machine

- 33.6 Kbps **Super G3 fax** for quick results¹
- **Up to 512 sheets of memory** capacity allows multiple faxes to be stored²
- **40 one-touch speed dials** and 200 coded dials for a comprehensive address book
- **Telephone handset included** as standard
- **Quick first print** arrives in just 5.8 seconds⁴
- Print and copy at the same speed of **up to 26 pages per minute**³
- Low energy consumption **uses just 1.3W** in Energy Saver mode
- **Single Cartridge System** for easy supplies replenishment
- **Duplex Versatility** - fax, print and copy two-sided documents with ease





FAXPHONE L190

Technical Information

FAX SPECIFICATIONS

Modem Speed	33.6 Kbps (Super G3) ¹
Fax Resolution	Up to 200 x 400 dpi (super fine)
Transmission Time	Approx. 3.0 seconds per page
Memory Capacity	Up to 512 sheets ²
Speed Dialing	40 one-touch speed dials; 200 coded dials
Group Dialing	239 destinations
Sequential Broadcasting	250 destinations
PC Fax	Yes (TX only)
Fax Features	Fax Forwarding, Dual Access, Remote Reception, Distinctive Ring Pattern Detection, Error Correction Mode, Auto Redial, Fax Activity Reports
Telephone Handset	Included

PRINTER SPECIFICATIONS

Print Speed	Up to 16 ppm (2-sided, plain paper letter) ³ Up to 26 ppm (1-sided, plain paper letter) ³
First Print Time	Approx. 5.8 seconds (letter) ⁴
Printer Language	UFR II LT (Host-based)
Print Resolution	Up to 600 x 600 dpi (1200 x 600 dpi quality)
Print Size	Up to 8.5" x 14"
Print Memory	128MB (shared)
Print Features	Watermark, Page Composer, Toner Saver

COPIER SPECIFICATIONS

Copy Speed	Up to 16 ppm (2-sided, plain paper letter) Up to 26 ppm (1-sided, plain paper letter)
First Copy Time	Approx. 8.7 seconds ⁵
Copy Resolution	Up to 600 x 600 dpi
Halftones	256 levels
Maximum # of Copies	99 copies
Reduction/Enlargement	25% - 400% in 1% increments
Copy Size	Platen: Up to 8.5" x 11"; ADF: 5.5" x 5" to 8.5" x 14"
Copy Features	Collate, 2 on 1, 4 on 1, ID Card Copy

Features and specifications are subject to change without notice.

- The Public Switched Telephone Network currently supports fax modem speeds of 28.8Kbps or lower, depending on telephone line conditions. Sending and receiving fax machines need to conform to ITU-T v.34 guidelines.
- Based on ITU-T #1 Chart (standard mode).
- Print speed is based on internal testing. Print speed may vary depending on the number of copies selected, as well as on the settings for size, type and orientation of paper.
- May vary depending on the output environment.
- Letter size, after being restored from energy saver mode.
- Based on 20 lb. bond paper.
- USB 2.0 Hi-Speed requires Windows® 7, Windows Vista®, Windows XP/2000 or Mac OS X operating systems. For Windows 98, Me and Mac OS X v. 10.2 to 10.2.6 operating systems, the printer/scanner will operate at USB 1.1 specifications.
- Declared noise emission in accordance with ISO 9296.
- Warranty program is subject to certain conditions and restrictions. See the warranty card for details.

PAPER HANDLING SPECIFICATIONS

Standard Paper Source(s)	250-sheet cassette ⁶
Document Feeder	50-sheet Duplex ⁶
Paper Output	Approx. 100 sheets (face down)
Paper Weight	16 to 43 lb. bond
Media Sizes	Letter, Legal, Statement, A4, A5, B5, B6
Media Types	Plain Paper, Heavy Paper, Recycled Paper, Transparency, Label, Envelope
Envelope Capacity	20 envelopes

CONNECTIVITY & SOFTWARE SPECIFICATIONS

Standard Interface(s)	USB 2.0 Hi-Speed ⁷
Operating Systems	Windows® 7, Windows Vista®, Windows XP and Mac OS X 10.5.8 & up
Cable Included	Power Cord, Phone Cable (USB not included)
<i>Drivers available for download from www.usa.canon.com</i>	

ENVIRONMENTAL SPECIFICATIONS

Power Consumption	During Operation: Approx. 520W Standby: Approx. 4.5W Energy Saver: Approx. 1.3W
Typical Energy Consumption (TEC)	0.8 kWh
Noise Level⁸	During Operation: 6.5 B or less (sound power) 50 dB or less (sound pressure) During Standby: 4.3 B or less (sound power) Inaudible (sound pressure)

General Specifications

CPU	Canon Custom Processor (133 MHz)
Dimensions	18.6" (W) x 17.5" (D) x 14.1" (H)
Unit Weight (without/with cartridge)	30.0 lbs./31.3 lbs.
Package Weight	Approx. 40.6 lbs.
Warranty	1 year limited exchange/carry-in warranty ⁹ (Extended warranty available)
Cartridge 128	Yields approximately 2,100 pages based on ISO/IEC Standard
Cartridge Type	Single Cartridge System
LCD Display	5-row backlit LCD
Duty Cycle	Up to 10,000 pages per month
Languages	English, French, Spanish, Portuguese

Ordering Information

FAXPHONE and Accessories	
FAXPHONE® L190	6356B002AA
Cartridge 128 (yields approx. 2,100 pages based on ISO/IEC Standard)	3500B001AA
FAXPHONE® L190 Virtual CarePAK (2 Year Carry-in/Exchange CarePAK)	6521A109AA
FAXPHONE® L190 E-CarePAK (2 Year Carry-in/Exchange CarePAK)	5707B025AA

For More Information Visit

www.usa.canon.com/consumer

For the name of the nearest dealer, call:
1-800-OK-CANON

Canon U.S.A., Inc.

One Canon Plaza, Lake Success, NY 11042
1-800-OK-CANON



©2012 Canon U.S.A., Inc. Canon, FAXPHONE and the Super G3 logo are registered trademarks of Canon Inc. in the United States and may be registered trademarks or trademarks in other countries. image*ANYWARE* is a registered trademark of Canon U.S.A., Inc. in the United States and may be a registered trademark or trademark in other countries. Microsoft, Windows, the Windows logo and Windows 7 are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Mac and the Mac logo are trademarks of Apple Computer, Inc., registered in the United States and other countries. All other product and brand names are trademarks of their respective owners. Specifications are subject to change without notice. As an ENERGY STAR partner, Canon U.S.A., Inc. has determined that this product meets the ENERGY STAR guidelines for energy efficiency. The limited warranty given by Canon U.S.A., Inc. is for Canon FAXPHONE L190 models purchased and used in the United States.

