

\*\*\*\*\*  
\*\*\* Network Configuration Page \*\*\*  
\*\*\*\*\*

Product Information

|                  |               |
|------------------|---------------|
| Product Name     | MG3600 series |
| ROM Version      | 4.000         |
| Serial Number    | KLAE12345     |
| Default Password | A1B2C3D4      |

Wireless LAN

|              |                   |
|--------------|-------------------|
|              | Enable            |
| MAC Address  | AA:BB:CC:11:22:33 |
| WPS PIN CODE | 12345678          |

Infrastructure

|                |            |
|----------------|------------|
|                | Enable     |
| Connection     | Active     |
| SSID           | My Network |
| Channel        | 11         |
| Encryption     | AES        |
| WEP Key Length | Inactive   |
| Authentication | WPA2-PSK   |

|                 |        |
|-----------------|--------|
| Signal Strength | 100[%] |
|-----------------|--------|

|                 |               |
|-----------------|---------------|
| TCP/IPv4        | Enable        |
| IP Address      | 192.168.1.105 |
| Subnet Mask     | 255.255.255.0 |
| Default Gateway | 192.168.1.1   |

|                      |                          |
|----------------------|--------------------------|
| TCP/IPv6             | Enable                   |
| IP Address           | ffff::bbb:cccc:eeee:000a |
| Subnet Prefix Length | 64                       |
| Default Gateway      |                          |

|                   |          |
|-------------------|----------|
| IPsec             | Inactive |
| Security Protocol |          |

Access Point Mode

Disable

|                |  |
|----------------|--|
| Connection     |  |
| SSID           |  |
| Password       |  |
| Channel        |  |
| Encryption     |  |
| Authentication |  |

|                 |  |
|-----------------|--|
| TCP/IPv4        |  |
| IP Address      |  |
| Subnet Mask     |  |
| Default Gateway |  |

|                      |  |
|----------------------|--|
| TCP/IPv6             |  |
| IP Address           |  |
| Subnet Prefix Length |  |
| Default Gateway      |  |

IPsec  
Security Protocol

Other Settings

|                      |                     |
|----------------------|---------------------|
| Printer Name         | 000000000000        |
| WSD Printing         | Enable              |
| WSD Timeout          | 5[min]              |
| LPD Printing         | Enable              |
| Bonjour              | Enable              |
| Bonjour Service Name | Canon MG3600 series |
| PictBridge Commun.   | Enable              |
| DNS Server           | Auto                |
| Primary Server       | 8.8.8.8             |
| Secondary Server     | 8.8.4.4             |
| Proxy Server         | Disable             |
| Proxy Address        |                     |
| Proxy Port           |                     |