
*** Network Configuration Page ***

1 Product Information

1- 1 Product Name	PR0-1100 series
1- 2 ROM Version	2.010
1- 3 Serial Number	ABCD01234
1- 4 Default Password	AbCdEfGh

2 Network Diagnostics

2- 1 Diagnostic Result	There is no problem.
2- 2 Result Codes	C-0
2- 3 Result Code Details	http://canon.com/ijnwt

3 Wireless LAN

Enable

3- 2 Infrastructure

Enable

3- 2- 1 Signal Strength	98 [%]
3- 2- 2 Link Quality	90 [%]
3- 2- 3 Frequency	2.4 [GHz]

3- 2- 4 MAC Address	AA:BB:CC:DD:EE:FF
3- 2- 5 Connection	Active
3- 2- 6 SSID	My Network
3- 2- 7 Channel	11
3- 2- 8 Encryption	AES
3- 2- 9 WEP Key Length	Inactive
3- 2-10 Authentication	WPA2-PSK

3- 2-11 TCP/IPv4	Enable
3- 2-12 IP Address	192.168.1.150
3- 2-13 Subnet Mask	255.255.255.0
3- 2-14 Default Gateway	192.168.1.1

3- 2-15 TCP/IPv6	Enable
------------------	--------

3- 2-16 Link Local Address	ffff::dddd:cccc:bbbb:aaaa
3- 2-17 Link Local Prefix Length	64

3- 2-18 Stateless Address1	
3- 2-19 Stateless Prefix Length1	
3- 2-20 Stateless Address2	
3- 2-21 Stateless Prefix Length2	
3- 2-22 Stateless Address3	
3- 2-23 Stateless Prefix Length3	
3- 2-24 Stateless Address4	
3- 2-25 Stateless Prefix Length4	

3- 2-26 Default Gateway1	
3- 2-27 Default Gateway2	
3- 2-28 Default Gateway3	
3- 2-29 Default Gateway4	

3- 2-30 Manual Setting	Disable
3- 2-31 IP Address	
3- 2-32 Subnet Prefix Length	
3- 2-33 IPsec	Inactive
3- 2-34 Security Protocol	
3- 2-35 Wireless LAN DRX	Enable
3- 3 Wireless Direct	Enable
3- 3- 1 MAC Address	AA:BB:CC:DD:EE:FF
3- 3- 2 Connection	Active
3- 3- 3 SSID	DIRECT-V639-PRO-1100series
3- 3- 4 Password	AbCdEfGhIj
3- 3- 5 Channel	3
3- 3- 6 Encryption	AES
3- 3- 7 Authentication	WPA2-PSK
3- 3- 8 TCP/IPv4	Enable
3- 3- 9 IP Address	192.168.115.2
3- 3-10 Subnet Mask	255.255.255.0
3- 3-11 Default Gateway	192.168.115.2
3- 3-12 TCP/IPv6	Enable
3- 3-13 Link Local Address	aaaa::bbbb:cccc:dddd:eeee
3- 3-14 Link Local Prefix Length	64
3- 3-15 IPsec	Inactive
3- 3-16 Security Protocol	
3- 3-17 Wireless LAN DRX	Disable
3- 3-18 Frequency	2.4 [GHz]
4 Wired LAN	Disable
4- 1 MAC Address	AA:BB:CC:CC:BB:AA
4- 2 Connection	
4- 3 TCP/IPv4	
4- 4 IP Address	
4- 5 Subnet Mask	
4- 6 Default Gateway	
4- 7 TCP/IPv6	
4- 8 Link Local Address	
4- 9 Link Local Prefix Length	
4-10 Stateless Address1	
4-11 Stateless Prefix Length1	
4-12 Stateless Address2	
4-13 Stateless Prefix Length2	
4-14 Stateless Address3	
4-15 Stateless Prefix Length3	
4-16 Stateless Address4	
4-17 Stateless Prefix Length4	

4-18 Default Gateway1
4-19 Default Gateway2
4-20 Default Gateway3
4-21 Default Gateway4

4-22 Manual Setting
4-23 IP Address
4-24 Subnet Prefix Length

4-25 IPsec
4-26 Security Protocol

4-27 Wired LAN DRX

5 Other Settings

5- 1 Printer Name	000000000000
5- 2 Wireless Direct DevName	DIRECT-V639-PRO-1100series
5- 4 WSD Printing	Enable
5- 5 WSD Timeout	15[min]
5- 6 LPD Printing	Enable
5- 7 RAW Printing	Enable
5- 9 Bonjour	Enable
5-10 Bonjour Service Name	Canon PRO-1100 series
5-11 LLNMR	Enable
5-12 SNMP	Enable
5-14 DNS Server	Auto
5-15 Primary Server	8.8.8.8
5-16 Secondary Server	8.8.4.4
5-17 Proxy Server	Disable
5-18 Proxy Address	
5-19 Proxy Port	
5-20 Cert. Fingerprt(SHA-1)	aaaaaaaa bbbbbbbb cccccccc dddddddd eeeeeeee
5-21 Cert. Fingerprt(SHA-256)	eeeeeeee dddddddd cccccccc bbbbbbbb aaaaaaaaa 12345678 87654321 a1b2c3d4

7 Web Services

7- 1 Unsent Usage Logs	0
7- 2 Usage Log Last Sent	Tue, 22 Apr 2025 16:26:31 GMT
7- 3 Web Service Status	Disabled
7- 4 Log Transmission Status	Not activated